

# Installation Guide

USB 2.0 External VGA Video Card (GUC2015V) USB 2.0 External DVI Video Card (GUC2020DW6)

> GUC2015V/GUC2020DW6 PART NO. M1110

#### ©2009 IOGEAR. All Rights Reserved. Part No. M1110

IOGEAR, the IOGEAR logo, MiniView®, VSE are trademarks or registered trademarks of IOGEAR, Inc. Microsoft and Windows are registered trademarks of Microsoft Corporation. IBM is a registered trademark of International Business Machines, Inc. Macintosh, G3/G4 and iMac are registered trademarks of Apple Computer, Inc. IOGEAR makes no warranty of any kind with regards to the information presented in this document. All information furnished here is for informational purposes only and is subject to change without notice. IOGEAR, Inc. assumes no responsibility for any inaccuracies or errors that may appear in this document.

# **Table of Contents**

Package Contents	4
Overview	5
System Requirements	6
Software Installation	7
- For Windows XP user:	7
- For Windows Vista user:	8
- For Mac OS X 10.4 and above user:	9
Configuration	10
Software Un-installation	15
Specifications	16
Federal Communications Commission (FCC) Statement	18
CE Statement	20
Limited Warranty	21
Contact	22

# **Package Contents**

#### GUC2015V:

- 1 x USB 2.0 External VGA Video Card
- 1 x USB 2.0 Cable
- 1 x Installation CD
- 1 x User Manual
- 1 x Warranty/Registration Card

#### GUC2020DW6:

- 1 x USB 2.0 External DVI Video Card
- 1 x USB 2.0 Cable
- 1 x Installation CD
- 1 x User Manual
- 1 x Warranty/Registration Card

### **Overview**

- Easily connect up to six monitors using a USB 2.0 Cable
- Enjoy resolutions of up to 1280 x 1024 at 32 bit color with GUC2015V USB External VGA Video Card; or 1600 x 1200 with GUC2020DW6 USB External DVI Video Card..
- Allows for effortless multitasking
- Bus Powered No external power supply needed
- Supports usage through powered KVMP's or USB hubs

# **System Requirements**

Minimum system requirements:

- Computer with 1.2GHz or higher processor speed. Intel Pentium/Celeron family, or AMD K6/Athlon/ Duron family, or compatible processor recommended.
- 256MB or RAM or higher (512MB recommended)
- Available USB 2.0 port
- 30MB of available disk space
- Super VGA (800 x 600) or higher resolution video adapter and monitor CD-ROM or DVD-ROM
- Windows XP/Vista 32 and 64-bit OS
- Mac OS X 10.4 or higher with Intel based CPU

The USB VGA Video Card or USB DVI Video Card support all analogue CRT and LCD monitors or displays with a VGA connector. Monitors or displays that equipped with DVI-A or DVI-I can also be connected using a suitable VGA to DVI adapter.

### **Software Installation**

#### For Windows XP user:

 Insert the included CD to the CD-ROM/ DVD-ROM of your computer. The installation process will automatically load. Select the preferred language for the installation and click on I Accept to continue.





2. Restart your system after the installation completes.

#### For Windows Vista user:

 Insert the included CD to the CD-ROM/ DVD-ROM of your computer. The installation process will automatically load. Click on **Run setup.exe** to continue.



2. Select the preferred language for installation and click on I Accept to continue.



#### For Mac OS X 10.4 and above user:

 Insert the included CD to the CD-ROM/DVD-ROM of your computer. Browse through the content on the CD and find a folder named Mac driver.



2. Execute the Displaylink-OSX01.1.3b1.dmg to begin the installation for Mac OS.



## Configuration

#### For both Windows XP and Vista users:

 Connect the mini-B end of the included USB cable to the mini-B port on the USB External VGA Video Card or USB External DVI Video Card. Then connect the USB Type-A end of the cable to any available USB port on your computer.



Once plugged in, you will see a monitor icon showing up in the system tray.



 For GUC2015V, USB External VGA Video Card, connect the male end of the VGA cable (not included) to the VGA port on the USB External Video Card. Then connect the other male end of the VGA cable (not included) to the VGA port on your monitor/display.

#### For GUC2020DW6, USB External DVI Video

**Card,** connect the male end of the DVI cable (not included) to the DVI port on the USB External DVI Video Card. Then connect the other male end of the DVI cable (not included) to the DVI port on your monitor/display.





 Click on the monitor icon to bring up the configuration menu. When connecting the USB External VGA Video Card or USB External DVI Video Card to your computer, it is configured to function as the Extended Mode by default, and you can also change to Mirror mode as you prefer.

#### Note:

When in **Extended Mode**, you will see the wallpaper displaying on the monitor/display that is connected to the USB External VGA Video Card or USB External DVI Video Card.





When in **Mirror Mode**, you will see a clone desktop displaying on the monitor/display that is connected to the USB External VGA Video Card or USB External DVI Video Card.



4. You can also adjust the screen resolution using this menu. The supported resolution of your monitor/display will show up on the right side of the menu and you can select any preferred setting as you wish. When resetting your resolution, you will see your monitor/display flickers or turns into black for few seconds, then it will resume back to normal.



 Another way to configure your setting is to select Advanced... and it will bring up the Display Settings window. You may apply different adjustments to your USB External VGA Video Card or USB External DVI Video Card.

Display Settings	
fontor	
Drag the icons to match your monitors.	Identify Monitor
1 3	2
	_
3. IDGEAR External VGA (US8_0058-000005) on Disp	slayLink Graphics
IT This is set on the second set	
Extend the desktop onto this monitor	
Extend the desktop onto this monitor Resolution:	Colors
I this is my main monitor I bit in the desktop onto this monitor Resolution: Low	Colors: Highest (32 bit)
2 Dated the desistop onto this monitor Resolution: Low	Colors: Highest (12 bit)
Use and the deaktop onto this monitor Resolution: Low	Colors: Highest (32 bit) Advanced Settings.
Clannal the desistion conte thin monitor Recolution: Low J 1200 by 1024 pixels Monitor II got the least display?	Colors: Highest (12 bit) Advanced Settings

### Software Un-installation

#### For Windows XP user:

Click on Start, then select Control Panel. Double click on Add/Remove Programs then select Displaylink Graphics and click on Remove button to uninstall the program.

When it is finished, restart your computer.

To remove this program from your computer, click Remove.		Renove
🖬 Adiže AIR	Sce	30.4946
Adobe Flash Player 10 Active/C		
Adobe Reader 9.1	See	205.00ME
Bluetooth 3P Suite	Sce	\$3.56M
🛃 DisplayLink Core Software	See	12.05MB
No. DisplayLink Graphics	Sce	0.644
Di Google Toolbar for Internet Explorer	Site	3.96M8
👹 hp deskjet 995c series		
IIM Integrated S6K Modem	See	0.53M
🚽 1814 ThinkPad Power Management Driver		
B Intel(R) Extreme Graphics 2 Driver		
B Intel(R) PRO Network Adapters and Drivers		
The second second second		

#### For Windows Vista user:

Click on the Vista icon on your desktop, then select Control Panel. Double click on Programs and Features. Select Displaylink Graphics and click on Uninstall button to uninstall the program. When it is finished, restart your computer.

C Diginize 🤉 🏢 Views 🖓			
Name	Publisher	Installed On	See
AVG Free 8.5		5/28/2009	45.2 ME
Canon Initiet Printer Driver Add-On Module		4/7/2009	
Canon MP790		4/7/2009	
Billanon ScarGear Bater		4/7/2000	836 KB
DisplayLink Core Software	DisplayLink Corp.	7/23/2009	13.0 MB
DisplayLink Graphics	DisplayLink Corp.	7/23/2009	655 KB
a the	Ballin Comparation	4/20/2000	1.55 8.85
Microsoft Visual C++ 2005 Redistributable	Microsoft Corporation	1/14/2009	422 KB
Whetwork Print Monitor for Windows 2000.007/2003/VL.		4/9/2009	4.70 MB
ESS S3Display		3/18/2009	
1 33 S3Gemma2		3/18/2009	
and an even of the			

# **Specifications**

#### GUC2015V USB External VGA Video Card

Function	GUC2015V
Power Consumption	5V
Video Resolution	1280 x 1024
Ports	1 Female VGA / 1 USB 2.0 Type mini-B
Operating Temperature	68 ~ 122 ° F ( 20 ~ 50 ° C)
Storage Temperature	32 ~ 158 ° F ( 0 ~ 70 ° C)
Operating System Support	Windows XP, Vista
USB specificaton	2.0 compliant
Humidity	20-80% RH, (Non Condensing)
Power Connections	Optional Power Port
Connectors	
USB	1
Video Ouput	1
Color Depth	00 bit to a sheet

#### GUC2020DW6 USB External DVI Video Card

Function	GUC2020DW6
Power Consumption	5V
Video Resolution	Max. 1600 x 1200
Ports	1 Female DVI / 1 USB 2.0 Type mini-B
Operating Temperature	68 ~ 122 ° F ( 20 ~ 50 ° C)
Storage Temperature	32 ~ 158 ° F ( 0 ~ 70 ° C)
Operating System Support	Windows 2000, XP, Vista
USB specificaton	2.0 compliant
Humidity	20-80% RH, (Non Condensing)
Humidity Power Connections	20-80% RH, (Non Condensing) Bus Powered
Humidity Power Connections Connectors	20-80% RH, (Non Condensing) Bus Powered USB: 1, Video: 1
Humidity Power Connections Connectors Video Connections	20-80% RH, (Non Condensing) Bus Powered USB: 1, Video: 1 Input: USB, Output: DVI
Humidity Power Connections Connectors Video Connections Power Mode	20-80% RH, (Non Condensing) Bus Powered USB: 1, Video: 1 Input: USB, Output: DVI USB

### Federal Communications Commission (FCC) Statement

#### 15.21

You are cautioned that changes or modifications not expressly approved by the part responsible for compliance could void the user's authority to operate the equipment.

#### 15.105(b)

his equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

# THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:

- 1. this device may not cause interference and
- 2. this device must accept any interference, including interference that may cause undesired operation of the device.

FCC RF Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. End users must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

# **CE Statement**

This device has been tested and found to comply with the requirements set up in the council directive on the approximation of the law of member states relating to EMC Directive 89/336/EEC, Low Voltage Directive 73/23/EEC and R&TTE Directive 99/5/EC.

The product has been approved for LVD and covered the following countries: Belgium, Denmark, France, Germany, Italy, Portugal, U.K., Spain, Sweden

## **Limited Warranty**

IN NO EVENT SHALL THE DIRECT VENDOR'S LIABILITY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THE PRODUCT, DISK, OR ITS DOCUMENTATION EXCEED THE PRICE PAID FOR THE PRODUCT.

The direct vendor makes no warranty or representation, expressed, implied, or statutory with respect to the contents or use of this documentation, and especially disclaims its quality, performance, merchantability, or fitness for any particular purpose. The direct vendor also reserves the right to revise or update the device or documentation without obligation to notify any individual or entity of such revisions, or updates. For further inquiries please contact IOGEAR.

# Contact

#### IOGEAR

23 Hubble Irvine, CA 92618 P 949.453.8782 F 949.453.8785 Visit us at: www.iogear.com



# About Us

## FUN

IOGEAR offers connectivity solutions that are innovative, fun, and stylish, helping people enjoy daily life using our high technology products.

#### GREEN

IOGEAR is an environmentally conscious company that emphasizes the importance of conserving natural resources. The use of our technology solutions helps reduce electronic waste.

### **HEALTH**

IOGEAR supports healthy and fit lifestyles. By integrating products with the latest scientific developments, IOGEAR's solutions enhance the life of end-users.



Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com