Operation Guide 2672


About This Manual



 Button operations are indicated using the letters shown Button operations are indicated using the letters shown in the illustration.
Each section of this manual provides you with the information you need to perform operations in each mode. Further details and technical information can be found in the "Reference" section.

General Guide

Press (B) to change from mode to mode.
In any mode, press (L) to illuminate the display



Timekeeping cato

Œ

Use the Timekeeping Mode to set and view the current time and date



3. When the setting you want to change is flashing, press (C) to change it as described below

To change this setting Perform this button operation	
Seconds	Press C to reset to 00.
Hour, Minutes, Year, Month, Day, Day of week	Press \bigcirc to increase the setting. Holding down \bigcirc changes the setting at high speed.

- adds 1 to the minutes. In the range of 00 to 29, the minutes are unchanged.
 4. Press (A) to exit the setting screen.
 The year can be set in the range of 2000 to 2099.
 The watch's built-in full automatic calendar automatically makes allowances for different month lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced.

To toggle between 12-hour and 24-hour timekeeping In the Timekeeping Mode, press O to toggle between 12-hour timekeeping and

- In the IImekeeping.
 With the 12-hour format, the P (PM) indicator appears to the left of the hour digits for times in the range of noon to 11:59 p.m. and no indicator appears to the left of the hour digits for times in the range of midnight to 11:59 a.m.
 With the 24-hour format, (24 indicator), times are displayed in the range of 0:00 to 23-50
- 23:59. The P and 24 indicators are not displayed with the Timekeeping Mode time in the Alarm Mode and Dual Time Mode. The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is

applied in all other modes.

Alarm

Timekeeping Mode time (Hour : Minutes) Mode india cato 10:58 R(

15:00

pressing (B) Alarm Operation

The alarm tone sounds at the preset time for 10 seconds, regardless of the mode the watch is in.

When the daily alarm is turned on, the alarm tone sounds when the alarm time is reached. You can also turn on an Hourly Time Signal that causes

the watch to beep twice every hour on the hour.
Alarm setting (and Hourly Time Signal setting) is available in the Alarm Mode, which you enter by

To set an alarm time

RA, 10:58)**2**30

Alarm time (Hour : Minutes)

- 1. In the Alarm Mode, hold down (A) until the hour setting In the Alarm Mode, hold down (A) until the hour settin starts to flash, which indicates the setting screen.
 This operation automatically turns on the alarm.
 Press (B) to move the flashing between the hour and minutes.
 While a setting is flashing, use (C) to increase it.
- Holding down © changes the setting at high speed.
 With the 12-hour format, set the time correctly as a.m. (no indicator) or p.m. (**P** indicator). 4. Press (A) to exit the setting screen.

To stop the alarm tone after it starts to sound Press any button.

To turn the Daily Alarm and Hourly Time Signal on and off In the Alarm Mode, press © to cycle through the on and

ALM SIG

Hourly time signal on indicator off settings as shown below. Alarm On Indicator/Hourly Time Signal On Indicator



	Both on	Both off	Daily alarm only	Hourly Time Signal only		
)	The alarm on (ALM) indicator flashes while the alarm is sounding.					

> ALM

SIG


The alarm on (ALM) indicator and Hourly Time Signal on (SIG) indicator are displayed in all modes.

To test the alarm

In the Alarm Mode, hold down (C) to sound the alarm.

Stopwatch

Alarm o



- The stopwatch lets you measure elapsed time, split times, and two finishes. The display range of the stopwatch is 23 hours, 59 minutes, 59.99 seconds.
- by minutes, 59.99 seconds.
 The stopwatch continues to run, restarting from zero after it reaches its limit, until you stop it.
 The stopwatch measurement operation continues even if you exit the Stopwatch Mode.
 Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to elapsed time measurement
- elapsed time measurement.
- All of the operations in this section are performed in the Stopwatch Mode, which you enter by pressing (B).

To measure times with the stopwatch

Elapsed time							
©	©>	©>	©>	A			
Start	Stop	Re-start	Stop	Clear			
Split time							
©>		\land \longrightarrow	$\odot \longrightarrow$	A			
Start	Split (SPL displayed)	Split release	Stop	Clear			
Two Finishes							
©>		$\odot \longrightarrow$	$\textcircled{\ }$	A			
Start	Split First runner finishes. Display time of first runner.	Stop Second runner finishes.	Split release Display time of second runner.	Clear			

Dual Time

The Dual Time Mode lets you keep track of time in a different time zone. • In the Dual Time Mode, the seconds count is synchronized with the seconds count of the Timekeeping Mode.

Timekeeping Mode time (Hour : Minutes) Mode indicator



To set the Dual Time 1. Press (B) to enter the Dual Time Mode. 2. Hold down (A) until the hour setting starts to flash,

- which indicates the setting screen. 3. Press (B) to move the flashing between the hour and
- Press (b) to increase the setting. Holding down (c) changes the setting at high speed.
 Press (a) to exit the setting screen.

1



CASIO

Operation Guide 2672

Display Illumination



An LED (light-emitting diode) and a light guide panel illuminate the entire display for easy reading in the dark. • See "Display Illumination Precautions" for more important information.

To illuminate the display
In any mode, press ① to illuminate the display.
You can use the procedure below to select either one second or three seconds as the display illumination duration. When you press ①, the display will remain illuminated for about one second or three seconds, depending on the current display illumination duration setting.

To specify the display illumination duration In the Timekeeping Mode, hold down © for about two seconds to toggle the display illumination duration between three seconds (3" displayed) and one second (3" not displayed).

- displayed).
 Pressing (C) also toggles between 12-hour and 24-hour timekeeping.
 When the three-second setting is selected, the three-second (3") indicator remains on the display in all modes.
 To protect against running down the watch's battery, the watch automatically switches to the one-second setting about seven hours after the three-second setting is selected. To continue to use the three-second setting, perform the above procedure again.

Reference

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

Auto return features

If you leave a screen with flashing digits for one or two minutes without performing any operation, the watch automatically saves any settings you have made up to that point and exits the setting screen.

Display Illumination Precautions

The illumination provided by the light may be hard to see when viewed under direct sunlight.
 Display illumination automatically turns off whenever an alarm sounds.
 Frequent use of the light shortens the battery life.

CASIO

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com