

3.5" Two-Way Center-Channel Satellite Loudspeaker

RCX-3



As one of the newest members of the Reference Satellite family, the RCX-3 is the smallest and most affordable center channel in the line. As with all Reference Satellite products, this compact loudspeaker was designed to fit almost anywhere, in any type of system, in any type of environment.

Available in a black or silver finish, the RCX-3 is a two-way magnetically shielded speaker that employs a 3.5-inch aluminum woofer and 0.75-inch titanium-dome compression driver coupled to an exclusive round MicroTractrix™ Horn for maximum clarity and efficiency. This speaker also features high-quality network components and premium internal wiring.

The woofer is a long-throw unit driven by a powerful magnetic motor structure. The Cerametallic™ cone is lightweight with excellent rigidity, which dramatically reduces any resonance. As a result, the RCX-3 is capable of robust bass extending low enough for comfortable operation with today's built-in A/V preamp/processor and receiver crossovers.

The RCX-3 has an integrated pedestal stand with a ball joint that allows it to be adjusted in almost any direction by using the provided allen wrench. Keyhole points are featured on the underside of the stand base for no-hassle wall mounting. The speaker grille magnetically snaps into place over the front baffle, while sturdy five-way binding posts ensure simple connection to any type of cable.

The RCX-3 is sold in a single box that includes four RSX-3s and one RCX-3. This speaker will also be available in a complete home theater package called the Cinema 6. This package includes four RSX-3s, one RCX-3 and a Reference Series RW-8 subwoofer.

- High sensitivity
- MicroTractrix Horn tweeter for clean, detailed highs
- Ball-joint pedestal stand with keyholes allows easy placement
- Integrates well with all Klipsch powered subwoofers
- Magnetically shielded to prevent video interference

SPECIFICATIONS

BANDWIDTH	105Hz-20kHz ± 3dB
SENSITIVITY	90dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2740Hz
POWER HANDLING	40 watts (160 watts peak)
ENCLOSURE TYPE	Bass reflex via dual rear-firing ports
DRIVE COMPONENTS	Two-way system using one .75" (1.8cm) magnetically shielded, titanium dome compression driver tweeter with an integral round 90° MicroTractrix Horn and one 3.5" (8.9cm) magnetically shielded, Cerametallic cone woofer
WEIGHT	5.8 lbs. (2.6kg) including base
HEIGHT	6.5" (16.5cm) including base, 5.4" (13.7cm) w/out base
WIDTH	8.8" (22.2cm)
DEPTH	6" (12.2cm)
FINISH	Black or Silver
MOUNTING	Base swivels 360° for on-wall mounting via keyholes



www.klipsch.com
1-800-KLIPSCH

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>