

In-Ceiling Subwoofer



RW-5101-C

The RW-5101-C proves that domestic harmony and powerful home theater performance can co-exist. In other words, just because you can't see this in-ceiling subwoofer, doesn't mean you won't feel it. This hard-hitter generates clean, potent bass that'll lift you out of your seat. It also continues the Klipsch tradition of high output with low distortion and effortless dynamic range.

The RW-5101-C utilizes a 10-inch long-throw woofer for unbeatable music and movie playback and high power handling (250 watts). The driver features a stiff, well-damped Cerametallic cone, a specially treated aluminum that has been electro-chemically transformed into ceramic on both outer surfaces. This ceramic compound allows the woofer to move at high speeds without blurring the sound. Furthermore, the subwoofer features an MDF baffle and sealed back enclosure, allowing it to deliver consistent low-frequency response regardless of the ceiling space.

Easy-to-install, the RW-5101-C can accommodate new or existing ceiling structures, as the enclosure is designed to fit standard ceiling joists. It employs all-new sure-grip mounting dogs for even pressure against the drywall. These robust dogs pull tight, leaving no gaps in sight and providing long-term installation reliability.

Timbre and style matched to all of our other premium in-ceiling products, the RW-5101-C brings a great bottom-end to a wide variety of discreet stereo or home theater systems. In fact, we've got premium architectural solutions in all shapes, sizes and prices, so take your pick!

*The RW-5101-C must be used in conjunction with the company's RSA-500 subwoofer amplifier, sold separately. Two of these subwoofers can be connected to a single amplifier.

- Superb bass response, output and extension
- High sensitivity design
- 10-inch Cerametallic woofer
- Sealed back enclosure
- Maximum installation reliability
- Mix and match with all our in-ceiling products

SPECIFICATIONS

Frequency Response	35-120Hz \pm 4dB
Sensitivity	91dB @ 1watt/ 1 meter
Nominal Impedance	8 ohms
Amplifier Power	See RSA-500 specifications
Woofer	Single 10" (25.4cm) front firing, Cerametallic™ cone, stamped steel frame driver
Amplifier	Use only with RSA-500 -EQ #3
Enclosure Material	MDF baffle, ABS shell
Enclosure Type	Sealed Enclosure
Height	15.3" (38.7 cm) Max Flange Diameter
Width	N/A
Depth	9.5" (24.1 cm)
Cutout Dimensions	13.3" (33.7 cm) Diameter
Weight	13 lbs. (6 kg)
Finishes	White
Built From	2008

www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2008



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>