Floorstanding Loudspeaker



When designing the fully active XF-48 floorstander, our engineers refused to hold back. The speaker intelligently employs dual high-output fiberglass cone woofers with powerful neodymium motor structures and two passive radiators to unleash the kind of bass you hear and feel.

But what makes this flat-panel speaker remarkably superior is an all-new, patent-pending Tractrix® Horn-loaded tweeter with XT™ technology. For over 60 years, horns have been the driving force behind our stunningly precise sound, and this latest design moves us farther ahead by allowing the slender XF-48 to deliver an extremely smooth response with constant directivity.

You'll discover the XF-48's performance has but one rival: style. Its beautifully crafted aluminum extruded enclosure, featuring an anodized black-grain finish and high-gloss black accents, is the direct result of our engineers' quest for perfect balance.

The entire ICON Series is performance art at its best, capturing the spirit of our past and pushing us into the future. It is a brilliant representation of how our products have evolved and remained desirable over time. After just one listen, the ICON sound will be imprinted in your consciousness forever.

XF-48

- Fully active design with built-in amplification
- Patent-pending XT[™] Tractrix[®] Horn technology
- Dual high-output woofers
- Dual passive radiators

SPECIFICATIONS

frequency response	40Hz-23kHz +/-3dB
low frequency extension	33Hz
amplifier power	100W continuous system power / 360W peak
high frequency drivers	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix® Horn
high freq crossover	2550Hz
low frequency drivers	Dual 5.25" (13.3cm) high-output, fiberglass cone woofers with Dual 5.25" x 9" (13.3cm x 22.9cm) passive radiators
amplifier	HF: Class A/B, LF: Class D
enclosure material	Aluminum
enclosure type	Bass-reflex via dual front-firing passive radiators
inputs	Line-level RCA jack, High-level speaker binding posts
height	48.8" (123.8cm)
width	7" (17.8cm)
depth	7.9" (20cm) not including 12" (30.5cm) diameter base
weight	39lbs (17.7kg)
features	Input Sensitivity Control, Auto Power
finishes	Black anodized w/ high-gloss Black accents
voltage	110/120 VAC 60Hz
export voltage	220 VAC 50/60Hz
built from	2007

www.klipsch.com 1-800-KLIPSCH All specifications are subject to change without notice. ©2007



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com