Specifications: Models and Dimensions

HDMIDA2 one input two outputs 2.5" w x 3/4" h x 2-3/8" deep (6.3 x 1.9 x 6 cm)

HSMIDA4 one input and four outputs 6.5'' w x 1'' h x 3-1/4'' deep (16.5 x 2.5 x 8.3 cm)

HDMIDA8 one input and eight outputs 12-5/8 w x 1.75" h x 4-1/8" deep (32 x 4.5 x 10.6 cm)

Power: 5 VDC 3000 mA.

Warranty

Knoll Systems warrants its products sold in the USA and Canada by authorized Knoll dealers to be free of defects in materials and workmanship. This warranty extends for three full years from the date of purchase by the original consumer. Any products returned to Knoll Systems and found to be defective by Knoll Systems within the warranty period will be repaired or replaced at Knoll Systems option, at no charge. Knoll Systems will not be responsible for the actual cost of installation or removal of the product, nor for any incidental or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. This warranty gives you specific legal rights. You may have additional legal rights that vary from state to state.

Knoll Systems www.knollsystems.com

145 Tyee Drive Point Roberts, WA 98281 15-7163 Vantage Way, Delta Bc V4G 1N1 Tel. (604) 940 1689, fax (855) 734 3363 Made in Canada Knoll Systems All Rights Reserved







Installation Instructions v1.2

Warning: To be installed and/or used in accordance with appropriate electrical codes and regulations. If you are not sure about any part of these instructions, consult a qualified electrician.

Introduction: Thank you for your purchase of a Knoll HDMI distribution amplifier. This DA will take any HDMI signal and distribute it to up to 8 outputs. Up to 8 more HDMIDA8's can be plugged into one HDMIDA8 giving as many as 64 outputs from 9 units or 512 outputs from 73 units.

The maximum wire length for HDMI cables is about 15 meters or 50 feet. If longer wire runs are needed so the Knoll HDMI balun solutions to allow wire runs up to 35 meters or 120 feet.

Features:

- Newest version is 8 bit 3D capable with wider bandwidth.
- Tabletop box design.
- Will safely send 480i/p, 720p and 1080i/p signals.
- Easy to use. Installs in seconds and there are no user adjustments.
- Can be cascaded two times to give a maximum of 512 HDMI outputs
- Supports all HDCP forms.
- Power supply included.

Wiring:

Gently connect all HDMI inputs and outputs with the shortest HDMI cables you can find. Make sure the HDMI cables and especially the connectors are top quality.

Connection and Operation:

After connecting the HDMI wires, insert the 5 volt plug on the power supply to the HDMIDA8. Next plug the AC side of the power supply into the wall outlet. Turn on the power switch.

Troubleshooting:

If the HDMIDA8 does not appear to be functioning, make certain the source and the destination devices connected are functioning and turn on. Reconnect the devices using maximum 3 meter (10 foot) long cables (in other words make sure the problem is not long cables in which case a HDMI balun may be required). If the signal is present then make sure the HDMIDA8 is getting power. If it still does not work carefully inspect the cables and connectors for any damage.

Non HDCP Compliant Devices:

If a destination device does not appear to work, make certain that the device is HDCP compliant. A non-HDCP compliant device will not work with a signal that has HDCP encoding present.

If problems are experienced with this product, please call our tech line for help at 1 800 566 5579.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com