



The Invacare® Spree 3G Pediatric Tilt-in-Space Wheelchair offers virtually all the enhancements available on the Solara 3G wheelchair, only in a smaller package. With a compact sleek design, more configurations and additional accessories to choose from, the Spree 3G pediatric wheelchair can easily match every child's individuality.







The unique **Tilt Assist** feature makes tilting easier by reducing the effort required to tilt an occupied Solara 3G or Spree 3G wheelchair by 30%. With three settings, front, middle and rear, the simple Tilt Assist adjustments help to correct for uneven weight distribution caused by seating systems and other components.

The innovative **Low Shear Recline** minimizes shearing forces and prevents displacement of positioning tools such as laterals and headrest. Used in combination with tilt, recline can offer additional functional and clinical benefits to users and caregivers.





A durable mechanical linkage Foot-Operated Wheel Lock is positioned at the rear of the frame next to the Cable-Free Foot Release for tilt which is now labeled.

Pressing 1 of the 2 levers of the wheel lock easily locks both rear wheels.







The **DeGage Dynamic Rocker Back** accommodates those with involuntary thrusts by helping to reduce pain or discomfort for the user. See **www.degage.us** for complete details.

Transport Brackets (TRBKTS) have been redesigned to allow more access to the rear tiedown points without additional steps needed and, for the first time ever, can be ordered as a service part kit.





The Transport Ready Option (TRRO)

has been crash tested in accordance with ANSI/ RESNA WC/19 and includes a wheelchair anchored pelvic belt.

Color coded, rust-resistant **Zinc-Plated Hardware** makes adjustments simple and the Solara 3G wheelchair more durable. Clear hardware indicates an adjustment point while the black bolts are static. Our zinc-plated fasteners resist rust corrosion better than any other fastener in the industry.





The **Contracture Footrest** systems offer great strength and adjustability. The bilateral footplates offer inversion and eversion while both the platform and footplates can be adjusted laterally the full width of the chair.

Freedom Designs, Inc. custom seating systems can be ordered and installed on-chair for any Invacare® rehab chair manufactured in Ohio, including the Solara 3G and Spree 3G wheelchairs. Invacare will bill the customer for the chair and seating system on one invoice.



* TRRO includes four factory-installed transport brackets and wheelchair anchored pelvic belt. TRRO has been crash-tested in accordance with ANSI/RESNA WC Vol 1. Section 19 Frontal Impact Test requirements for wheelchairs with a 168 lbs. crash dummy, which corresponds to a person with a weight of 114 lbs. to 209 lbs. TRBKTS includes four factory-installed wheelchair transport brackets. TRBKTS has not been crash tested in accordance with WC19. Use these transport brackets only to secure an unoccupied wheelchair during transport.

As of this date, the Department of Transportation has not approved any tie-down systems for transportation of a user while in a wheelchair, in a moving vehicle of any type. It is Invacare's position that users of wheelchairs should be transferred into appropriate seating in vehicles for transportation and use be made of the restraints made available by the auto industry. Invacare cannot and does not recommend any wheelchair transportation systems.



INVACARE®

Spree 3GTilt-in-Space Wheelchair



Specifications	Invacare® Solara® 3G Wheelchair	Invacare® Spree 3G Wheelchair
Frame style	Tilt-in-Space	Tilt-in-Space
Seat width	12" — 24"	12" — 18"
Seat depth	12" — 22"	12" — 19"
Back height	17" – 20", 20", 24"	17" – 20", 20", 24"
Adjustable angle back	0°, 5°, 10°, 15°, 20°, 25°, 30°	0°, 5°, 10°, 15°, 20°, 25°, 30°
Seat-to-floor heights	12.5" – 19"*	12.5" – 19"*
Wheels	12", 16", 18", 20", 22", 24"	12", 16", 18", 20", 22", 24"
Casters	4", 5", 6", 8"	4", 5", 6", 8"
Knee-to-heel range	4.5" – 24"	4.5" – 24"
Tilt range	-5° to 50°	-5° to 50°
Weight capacity	300 lb.	
	400 lb. heavy-duty package	200 lb.
Weight of chair	34.50 lb.**	32 lb.**
Limited warranty	Lifetime on frame and crossbraces	Lifetime on frame and crossbraces

^{*}With flush seat pan **Base chair without accessories

Frame Colors



^{*} Sunkissed Orange is available through the Specials Department. (Shown on chair).

* ANSI/RESNA WC/19 sec 6.2 Presale Literature Notification Invacare® Solara® 3G/Spree 3G Wheelchairs

- Minimum turning radius 25".
 Minimum turn-around width 38.68".
 (16" W Medium frame chair without footrests).
- B. Solara and Spree wheelchairs with long frame may be longer than 1220 mm, exceeding the ADA definition of common wheelchair and the maximum length requirements of lifts on public vehicles, and may therefore present particular difficulties accessing some vehicles.
- C. Total wheelchair mass = 80 lb. (36 kg), including wheels, arms, front riggings, seat pan, Invacare® Personal Back™ 10 seat system, 3" seat cushion, tie-down brackets, wheelchair anchored pelvic belt and rigidizing bar.
- D. Average lateral dummy displacement=approximately .65" (16.5 mm).
- E. Overall Score = 16Overall Rating = B
- F. i. The Solara and Spree wheelchairs tested were sized to accommodate a 170 lb. test dummy. (Medium frame, 16"W x 19"D, 60" front rigging, 12" wheels, pneumatic flat free tires, steel seat pan, cushion, Invacare Personal Back 10 seat system, 6" x 2" semi-pneumatic casters).

- ii. The Solara and Spree wheelchairs tested were tied-down using four tie-down brackets - 2 brackets located near the front of the seat frame and 2 brackets located on the rear of the base frame.
- The Solara and Spree wheelchairs were tested with a 170 lb. test dummy.
- iv. The Solara and Spree wheelchairs tested used a wheelchair-anchored pelvic belt and vehicle-anchored shoulder belt.
- The Solara and Spree wheelchairs tested comply with the performance requirements of ANSI/RESNA WC/19 sec 5.3.
- G. For all types of vehicles, the Solara and Spree wheelchairs require four SAE J2249-compliant tie-down strap assemblies for effective securement.
- H. When the TRRO or TRBKTS option is selected, the Solara and Spree wheelchairs provide a location for anchoring of an Invacare-provided pelvic belt. This belt has been tested in accordance with ANSI/RESNA WC/19.
- I. The wheelchair-anchored pelvic belt is supplied by Invacare.

Invacare Corporation

www.invacare.com

USA

One Invacare Way Elyria, Ohio 44035-4190 (800) 333-6900

Canada

570 Matheson Blvd. E. Unit 8 Mississauga, Ontario L4Z 4G4 Canada (800) 668 - 5324

© 2011 Invacare Corporation.

All rights reserved.

Trademarks are identified by the symbols ™ and ®.

All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted.

Bodypoint is a registered trademark of Bodypoint, Inc.

Specifications are subject to change without notification.

Form No. 09-032 Rev. 01/11



www.Invacare.com/Solara3G

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com