

J E T[®]

BUILT BETTER TO BUILD BETTER™

Remote Dust Collectors



Our latest addition to our complete line of dust collectors is the convenience of a remote control and a built in timer. The remote will operate these dust collectors from anywhere in the shop. The timer will automatically shut the unit off at any predetermined time from 1 to 99 minutes. This great feature is available on all JET® dust collectors with bag filters and canister filters.

jettools.com

STOCK NUMBER	708640RC	708641RC
Model Number	DC-640RC	DC-650RC
Remote Control	yes	yes
Blower wheel diameter (in.)	9-1/2	9-1/2
Sound Rating @ 3 ft.	60-dB	60-dB
1-Hose connection diameter (in.)	4	4
Bag diameter (in.)	14	14
Filter Bag/Canister length (in.)	31	24
Collection Bag length (in.)	23-5/8	24
Collection Bag capacity	2.67 cu. ft.	2.7 cu. ft.
Air Flow @ 4" (CFM)	650	650
Particle Size	30-micron	2-micron
Static Pressure (in. of water)	7.80	7.80
Velocity @ 4" (FPM)	7,445	7,445
Overall dimensions (L x W x H/in.)	27 x 14 x 66	27 x 14 x 61
Motor (TEFC)	1HP, 1Ph, 115/230V, Prewired 115V	1HP, 1Ph, 115/230V, Prewired 115V
Net weight (lbs.)	84	86

STOCK NUMBER	708639RC	708626RCK
Model	DC-1100RC	DC-1100RCK
Remote Control	yes	yes
Blower Wheel diameter (in.)	11	11
Sound Rating @ 3 ft.	70-80 dB	70-80 dB
1-Hose Connection dia. (in.)	6	6
2-Hose Connection dia. (in.)	4	4
Bag Diameter (in.)	20	20
Filter Bag/Canister length (in.)	46	26
Collection Bag length (in.)	30	30
Collection Bag Capacity	7.36 cu. ft.	7.36 cu. ft.
Air Flow @ 4" (CFM)	1,100	1,100
Particle Size	30-Micron	2-Micron
Static Pressure (in. of water)	11.5	11.5
Velocity @ 4" (FPM)	12,571	12,571
Overall dimensions (LxWxH/in.)	37x20x79	37x20x72
Motor (TEFC)	1-1/2HP, 1Ph, 115/230V, Prewired 115V	1-1/2HP, 1Ph, 115/ 230V, Prewired 115V
Net Wt. (lbs.)	115	120

STOCK NUMBER	708634RC	708634CK	708635RCK
Model	DC-1200RC	DC-1200CK	DC-1200RCK
Remote Control	yes	no	yes
Blower Wheel dia.	12	12	12
Sound Rating @ 3 ft.	65-80 dB	65-80 dB	65-80 dB
1-Hose Connect. dia.	6	6	6
2-Hose Connect. dia.	4	4	4
Bag dia.	20	20	20
Filter Bag/ Canister length	46	26	26
Collection Bag length	34-1/2	34-1/2	34-1/2
Collection Bag Cap.	7.36 cu. ft.	7.36 cu. ft.	7.36 cu. ft.
Air Flow @ 4" (CFM)	1200	1200	1200
Particle Size	30-Mic.	2-Mic.	2-Mic.
Static Pressure (in. of water)	11.0	11.0	11.0
Velocity @ 4" (FPM)	13,745	13,745	13,745
Overall dim. (L x W x H/in.)	34x20.5x96	34x20x72	34x20x72
Motor (TEFC)	2HP, 1Ph, 230V	2HP, 1Ph, 230V	2HP, 1Ph, 230V
Net Wt. (lbs.)	143	150	150

MODEL 650 REMOTE DUST COLLECTORS

- **Hook up one to three machines** for optimum dust cleaning
- **Quick-install collection bag** makes emptying and re-attaching a snap
- **Includes four casters** for maneuverability and total portability
- **Remote Control is programmable from 1 to 99 minutes** to collect dust even while you are away from your workshop



MODEL 1100 REMOTE DUST COLLECTORS

- **Industrial-quality construction** effectively handles collection of wood chips and sawdust
- **Single-stage design** for economical and quiet operation
- **Industrial controls** designed for years of trouble-free use
- **Quick-connect collection bags with elastic band** for fast, easy installation and removal
- **High air velocity (CFM) design** stands up to any competitive specifications
- **Permanently lubricated, totally enclosed, fan-cooled motors** are rated for continuous-duty
- **Includes four casters** for maneuverability and total portability
- **Remote Control is programmable from 1 to 99 minutes** to collect dust even while you are away from your workshop



MODEL 1200 REMOTE DUST COLLECTORS

- **Industrial-quality construction** effectively handles collection of wood chips and sawdust
- **Single-stage design** for economical and quiet operation
- **Industrial controls** designed for years of trouble-free use
- **Quick-connect collection bags with elastic band** for fast, easy installation and removal
- **High air velocity (CFM) design** stands up to any competitive specifications
- **Permanently lubricated, totally enclosed, fan-cooled motors** are rated for continuous-duty
- **Includes four casters** for maneuverability and total portability
- **Remote Control is programmable from 1 to 99 minutes** to collect dust even while you are away from your workshop



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>