




myPDFmanuals

You can read the recommendations in the user guide, the technical guide or the installation guide for JVC KTSR2000J-KT-SR2000. You'll find the answers to all your questions on the JVC KTSR2000J-KT-SR2000 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual JVC KTSR2000J-KT-SR2000
User guide JVC KTSR2000J-KT-SR2000
Operating instructions JVC KTSR2000J-KT-SR2000
Instructions for use JVC KTSR2000J-KT-SR2000
Instruction manual JVC KTSR2000J-KT-SR2000


JVC



SIRIUS® Radio



KT-SR2000



INSTRUCTIONS

For Customer Use:
Enter below the Model No. and Serial No. which are located either on the rear, bottom or side of the cabinet. Retain this information for future reference.

Model No. _____
Serial No. _____

LVT1261-001A
[J]



[Your user manual](#)
[JVC KTSR2000J-KT-SR2000](#)

Manual abstract:

· If the LCD display becomes damaged or broken, do not touch the liquid crystal fluid. The fluid may be dangerous to your health or even fatal. If the liquid crystal fluid contacts your body or clothing, immediately wash it off with soap and water. **WARNING:** Do not operate the unit in a way that might divert your attention from driving safely. As a driver, you alone are responsible for safely operating your vehicle in accordance with traffic safety laws at all times.

WARNINGS: · Store the battery in a place where children cannot reach. If a child accidentally swallows the battery, consult a doctor immediately. **4 Box Contents** · Do not recharge, short, disassemble, or heat the battery or dispose of it in a fire. Doing any of these things may cause the battery to give off heat, crack, or start a fire. · Do not leave the battery with other metallic materials.

Doing this may cause the battery to give off heat, crack, or start a fire. · When throwing away or saving the battery, wrap it in tape and insulate; otherwise, the battery may start to give off heat, crack, or start a fire. **CAUTIONS:** Take the following precautions to keep the unit in proper working order: · Be sure the unit is connected to a 12 V DC power supply with a negative ground connection. · Do not install the unit where it will be exposed to high levels of humidity, moisture, or dust. · When replacing a fuse, use only a new one with the proper rating.

Using a fuse with the wrong rating may cause the unit to malfunction. · To prevent a short circuit when replacing a fuse, first unplug the cigarette lighter adapter from the cigarette lighter. · When drilling holes to mount the unit, make sure not to damage wiring or other systems. After you unpack your JVC PnP, make sure everything here is included: SIRIUS® Radio Remote Controller Battery (CR2032) (The battery has been installed when shipped from the factory.)

If anything is missing or damaged, or if your JVC PnP fails to operate, notify your shipper immediately.

It is recommended that you keep the original packaging in case you need to ship your JVC PnP in the future. **5 Installation: Preparation** To use your JVC PnP in your car or at home, it is required to separately purchase either KS-K6012 Car Docking Kit or KS-K6013 Home Docking Kit. KS-K6012 includes. ·

Installations · Car Docking Cradle · Suction Cup Mount · Cigarette Lighter Adapter · Magnetic Roof-mount SIRIUS Antenna **Note:** KS-K6012 does not include any connecting cord; however, you can also use an optional audio cord or cassette adapter to send the signals to your car stereo. KS-K6013 includes. ·

Installations · Home Docking Cradle · SIRIUS Antenna · Power Supply · Audio Cord **CAUTION:** Do not put JVC PnP in the cradle until you have completed the installation unless it is required for testing. **6 Installation in Your Car with KS-K6012** **CAUTION:** Do not plug the cigarette lighter adapter into the cigarette lighter until you have completed the installation. Installing in your car For more illustrated explanations, refer to the Installations supplied for your

Car Docking Kit. **2 1 Determine where you want to mount JVC PnP.** · Do not install JVC PnP where it may obstruct your view through the windshield or your view of your car's indicator displays.

· Do not install JVC PnP where it will hinder your access to the car's controls. · Do not install JVC PnP where it may hinder the function of safety devices such as an airbag. Doing so may prevent the airbag from functioning properly in the event of an accident. · Find a location that provides good visibility of and access to JVC PnP's front panel. Assemble the supplied suction cup mount to JVC PnP using the supplied screws. · When using other screws, use the screws of less than 8 mm (3/8 inch) long with a diameter of 4 mm (3/16 inch). To be continued. **7 Installation in Your Car with KS-K6012 (continued)** **3 4 Plug**

the cigarette lighter adapter into the back of the cradle--DC 12 V. Activate the FM signal transmitter and preset the frequency (see "4 FM Transmitter Options" on page 24). · It is recommended to preset the same frequency into your car stereo as you have selected so you can easily tune in to the frequency.



[Your user manual](#)

[JVC KTSR2000J-KT-SR2000](#)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>