

# Choose Kenwood's FreeTalk® XL and you'll enjoy a full line of accessories for the ultimate in operating convenience.

#### KNB-14 600 mAh, 8-hour Standard Rechargeable NiCd Battery

Extended-life Rechargeable

AA Alkaline Battery Pack

(holds 6 AA Cells; not

KNB-15A

NiCd Battery

KBP-1

included)

KSC-15

KSC-16

Rapid Rate

Single Unit Desktop Charger

KMB-14

KVC-3

KVC-4

KBH-8

Six Unit Charger

Adapter (for six KSC-15/16

Regular Rate Vehicular

Rapid Rate Vehicular

Spring-Action Plastic Belt Clip

Charger Adapter

Charger Adapter

chargers; purchase separately)

Regular Rate

Single Unit Desktop

8 hr. charge time typical)\*

(Approx. 1 hr. charge time typical)\*

Charger (Approx.

1100 mAh. 10-hour



KWR-1

KLH-6SW

KLH-83 Heavy-Duty Carrying

KLH-84B Nylon Case (Black)

KLH-84C

KLH-84G

KLH-840R Nylon Case (Orange)

KLH-84HB

KRA-17 M

Nylon Case (Black)

Volon Case (Green)

Nylon Case (Camouflage)

Case w/bungee-cord

Swivel Belt Case

Water-resistant Ra











Compact Speake Microphone



KEP-2 Earphone Kit for KMC-17/21 Speaker Microphones (2.5 mm plug)



KHS-8BL Two-wire Surveillance Palm Microphone with

KHS-7



Lightweight Single with Flexible Boom Microphone and PTT







HMC-3 Light-duty Single

Earpiece Headset











Not all accessories may be available in all markets.

#### **Specifications**

• Number of channels: 15 • Talk groups: 38 (CTCSS) • Power supply: 600mAh, rechargeable NiCd battery • Dimensions (W x H x D): 2-1/4 x 4-7/8 x 1-1/4 in (58 x 125 x 32 mm), incl. KNB-14 battery • Weight: 11.6 oz (330 g), incl. KNB-14 battery & antenna • FCC ID: ALH27303110 • FCC compliance: Parts 90, 90,210, 95(A)

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

\*Under average conditions.

'The FreeTalk' XL comes pre-programmed with 15 FCC GMRS (General Mobile Radio Service) frequencies for convenience, however, an FCC license is required for operation (see the FreeTalk® instruction manual for frequencies and easy licensing information). The GMRS emergency channel (channel 10) should only be used for soliciting/rendering traveler aid or for emergency communications for immediate protection of life or property. In some areas, volunteer and public safety organizations may monitor this channel. For detailed information on GMRS service, see Kenwood's Internet web page links at www.kenwood.net. Call 1-800-950-5005 (USA only) to locate the nearest authorized Kenwood dealer

e Commerce Supply 15375 Barranca Pkwy H108 Irvine, CA 92618-2209 949-502-5588 949-480-0039 FAX www.KenwoodMPD.com radios@KenwoodMPD.com

Download from Www.Somanuals.com. All Manuals Search And Download.



# The Adventure Radio

"Get some distance out of your fun" with the Kenwood FreeTalk XL two-way portable radio. Whether camping fishing hunting biking hiking rappelling or rock climbing the Kenwood FreeTalk XL is essential gear for sports and leisure-time activities. Two-way radios maximize the use of your precious time off. And as usual, Kenwood adds a splash of fun.



# Fully equipped with 15 channels and 38 talk groups, FreeTalk® XL is the versatile choice for communications.

#### 15 Channels

The FreeTalk® XL has a full 15-position channel selector knob for easy operation. Channels 1-9 and 11-15 are for direct radio-to-radio (simplex) communications. Channel 10 is preprogrammed to the designated emergency channel. Channels 1-7 are also compatible with the popular Kenwood FreeTalk® Family Radio Service portables. FCC licensing information is included.

### **38 Multiple Talk Groups**

Talk Groups



Boasting high-quality specs and convenient features, Kenwood's FreeTalk® XL adds a dose of fun to your activities anywhere and anytime.

## ■ Die-Cast Chassis & Meets Military Standards

The aluminum die-cast chassis provides exceptional strength for rough handling that, when combined with a rugged and sealed case design, enable the FreeTalk® XL to provide years of reliable use. The FreeTalk® XL

also meets MIL-STD 810 C, D & E environmental specifications for Vibration, Shock, Humidity, Dust, and Light Rain.



Military Environmental Standards	MIL-STD 810C	MIL-STD 810D	MIL-STD 810E
Light Rain	506.1/Proc. II	506.2/Proc. II	506.3/Proc. II
Humidity	507.1/Proc. II	507.2/Proc. II	507.3/Proc. II
Dust	510.1/Proc. I	510.2/Proc. I	510.3/Proc. I
Vibration	514.2/Proc. VIII, X	514.3/Proc. I	514.3/Proc. I
Shock	516.2/Proc. I, II, V	516.3/Proc. I, IV	516.4/Proc. I, IV

# ■ Small & Lightweight

Carry the FreeTalk® XL in your pocket or on a belt and you'll hardly notice it's there because it's so small and lightweight (approximately 11 oz. and 5 inches in

# Simple Operation/ Rugged Controls

Simply turn it on and push to talk. Each FreeTalk® XL has an on/off power volume setting knob to adjust audio to a comfortable listening level. A monitor button is also provided to check for other users' activity. For added convenience, the two-color LED indicator lights red for transmit and green for an active channel.

## ■ 2 Watts Transmit Power/ Range Up To 5 Miles

The 2 watts of power that FreeTalk\* XL has to offer allows direct radio-to-radio communications on the same frequency (simplex) for up to 5 miles\*.

Conditions	FreeTalk® XL Range		
Outdoor: line of sight (no obstructions)	Up to 5 miles		
Open locations: low residential buildings	Up to 2 miles		
Indoor: • steel/concrete building • multi-floor building	Up to 250,000 sq. ft. Up to 20 floors		

\*The range of the FreeTalk" XL will vary depending on terrain, obstructions and other conditions.

Download from Www.Somanuals.com. All Manuals Search And Download.



■ Brass Reinforced Antenna Port
The sealed heavy-duty "SMA" antenna
connector and high-gain durable antenna
of the FreeTalk" XL provide excellent
strength for optimum range.

# ■ Includes 8-Hour Battery Pack, Desktop Charger & Belt Clip

The sealed rechargeable NiCd battery pack slides on quickly and easily to the radio. This means that you don't have to contend with cumbersome latches and there are no battery compartment lids to lose or break. Charging a radio with battery installed or a spare battery pack is a simple drop-in task with the supplied desktop charger. A long-use, 10-hour KNB-15A battery option is also available and the spring belt-clip mounts directly to the body chassis.

#### ■ Time-Out timer

When the continuous transmit limit of 3 minutes is reached, the time-out timer automatically switches the FreeTalk® XL to receive operation. This limits per transmission talk time of each unit to help reduce channel congestion and conserve battery power.

- **Battery Saver**
- **Low Battery Alert**
- Powerful Audio
- Protected Accessory Port

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com