



Kidde is a leading global supplier of fire and safety products, systems and services under a range of well-known and trusted brand names to industrial, commercial, aerospace, combustion control and retail customers. The Kidde Group comprises three divisions: Aerospace & Specialist Equipment, Residential & Commercial Fire Protection and Industrial Fire Protection and has operating companies in 29 countries together with worldwide distribution for its products and systems.

Kidde Residential & Commercial is the world's leading manufacturer of home safety products, including fire extinguishers, carbon monoxide alarms, smoke alarms and fire escape ladders.

Kidde Residential and Commercial Division 1394 South Third Street Mebane, NC 27302 Tel. 919.563.2711 www.kiddeUS.com

. . .

. . .

•

0

0

.

•

•

0

•

.

.

•



# Service Lite Fire Extinguisher

Part number 21006401 Multipurpose use

• . 

. •

.

a

0

•

0

0

.

.

•

.

•

.

•

a

a

•

•

.

.

•

•

•

•

a

•

0

0

•

.

0 • 

•

# Single Use

# UL Rated 1-A, 10-B:C



# Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The XL2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Available with metal retention bracket. Order pt # 21006402

#### At a Glance

- Model XL2.5MP
- Multipurpose Dry Chemical
- Single Use
- **UL** listed
- UL rated 1-A,10-B:C
- U.S.C.G, DOT approved
- Monoammonium Phosphate 12 year limited warranty
- Suitable for use on most common fires

## **Features**

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.6 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved plastic strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection
- Available with metal strap bracket Pt. # 21006402





For use on the following types of fire:







# **Product Specification**

-	
Net agent weight (Average)	2.6 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



21006401

UPC: 0-47871-06401-4 I2F: 100-47871-06401-1

21006402 UPC: 0-47871-06402-1 I2F: 100-47871-06402-8



30

Kidde Residential and Commercial Division 1394 South Third Street, Mebane, NC 27302 • Tel. 919.563.2711 • www.kiddeus.com

# Service Lite Fire Extinguisher

• . 

• . •

•

0

•

0

•

•

•

a

•

•

•

•

.

•

•

. •

• .

•

.

•

a

•

•

•

0

•

•

• 0 • a

•

a

• 

• 0

0

•

.

0 • •

•

Part number 21006204 Low & Moderate Hazard use Single use

## UL Rated 3-A, 40-B:C



#### Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FX340SC is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & nylon valve assembly.

#### **FOR LOW & MODERATE HAZARDS**

A 3-A:40-B:C rated extinguisher is required for protecting both LOW & MODERATE hazard occupancies such as: living areas of the home, offices, churches, assembly halls, classrooms, hotel guest areas, home garage & workshop, light manufacturing, dining areas, auto showrooms, parking garages & storage

## **Features**

- Pressure gauge allows for immediate pressure status
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection



UPC: 0-47871-06204-1 I2F: 100-47871-06204-8

21006204

# Packaging Options

# Product Specification

For use on the following

types of fire:

Product Specification	
Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.75 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	UL Listed

MASTER PACK

Master pack

Kidde Residential and Commercial Division 1394 South Third Street, Mebane, NC 27302 • Tel. 919.563.2711 • www.kiddeus.com



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com