

## Rear Blades

<b>RBT45 Series</b>		
	<b>RBT4596</b>	<b>RBT45108</b>
<b>Blade Width</b>	96"	108"
<b>Approximate Weight (lbs.) with hydraulic links</b>	1130	1166
<b>Maximum Engine Horsepower</b>	125	
<b>Maximum G.V.W. (lbs.)</b>	9500	
<b>Hitch Type</b>	Cat. 2 & 3 (Fits Land Pride Quick Hitch)	
<b>Blade Angle</b>	15 positions up to 45 degrees clockwise and counter clockwise forward and same for reverse. (Center, 7 clockwise and 7 counter clockwise)	
<b>Manual Linkage:</b>	Infinite number of positions up to 45 degrees clockwise and counterclockwise forward and same for reverse.	
<b>Hydraulic Cylinder:</b>		
<b>Angle Cylinder</b>	4" X 16"	
<b>Blade Tilt</b>	Up to 15 degrees left and right.	
<b>Manual Ratchet Jack</b>	Infinite number of positions up to 15 degrees left and right.	
<b>Hydraulic Cylinder:</b>		
<b>Tilt Cylinder</b>	3" X 6"	
<b>Blade Offset</b>	15 positions up to 35 inches. (Center, 7 left and 7 right)	
<b>Manual Linkage:</b>	Infinite number of positions up to 35 inches left and right.	
<b>Hydraulic Cylinder:</b>		
<b>Offset Cylinder</b>	4" X 16"	
<b>Moldboard Height</b>	19"	
<b>Moldboard Thickness</b>	5/16" with 1/4" boxed reinforcement	
<b>Cutting Edge</b>	1/2" x 6" Heat treated and reversible	
<b>Main Frame</b>	Fully enclosed welded, formed box	
<b>Parking Stand</b>	Retractable	
<b>Options</b>	Skid Shoes, End Plates, Single or Dual Gauge Wheel, Double Selector Valve, Cushion Valve	

*Designs, specifications, features and information are subject to change without notice.*

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>