

Features and Benefits

Zero Turn Mowers, ZXT Pro

ZXT54 & ZXT60 Series

Features	Benefits
54 or 60" Cutting width	Sized right and priced right for high-end residential and cost conscious ranchers, farmers, estate owners, and commercial operators.
Mid-mount deck design	Puts deck closer to operator's line of sight for more efficient and precise operation.
Drive tire stance	49" outside tire width provides for excellent stability over uneven and hilly ground along with good maneuverability.
Excellent trim capability	49" wheel stance provides for good trim capability especially when equipped with a 60" deck.
Adjustable steering levers	Comfort Grip steering levers are designed with a wide range of adjustments to accommodate almost any size of operator.
Ground speed	Forward 11 mph and reverse 5.5 mph for high productivity.
Premium drive tires	24x10.5-12 for excellent traction, stability and a smooth ride.
Floating deck design	Chain suspension flotation provides excellent flotation over uneven terrain.
Rapid deck height adjustment	Spring loaded and foot operated lever action deck height adjuster with pin locator makes for quick, easy, and precise cutting height adjustments.
Anti-scalp rollers	Four anti-scalp rollers with two located on deck ends and two located toward mid-decks keeps scalping to a minimum.
1" to 5" Cutting height	Cutting height in 1/4" increments for good cutting height range control.
Front castor action wheels	Two front mounted 13x6.5-6 ribbed tread wheels mounted in heavy duty pivoting castor forks for quick and durable response.
Lockable floating front axle.	Floating front axle provides for smoother ride, more uniform cut, and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain. A foot activated axle lock provides for temporary curb or edge cutting without grounding or hanging up the deck.
High blade tip speed	18,515 fpm on the 54" deck and 18,700 fpm on the 60" deck for clean quality of cut.
Easy access spindle housings	1" diameter greaseable spindle housing with easy access lubrication points. Housings are ductile iron designed to handle heavy shock loads.
Kevlar drive belts	Single hydrostatic pump drive belt and single deck drive belt made with Kevlar™ fiber for long belt life.
Lever activated park brake	A manually activated over-center lever next to the operator's seat easily and conveniently activates or releases a highly durable and reliable enclosed wet disc brake. Mower will not move until brake is released.
Seat safety interlocks	Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade PTO switch in "on" position.
Choice of engines	Proven 26 hp Briggs and Stratton ELS, 25 hp Kawasaki, 31 hp Kawasaki, or 24 hp Honda to meet customer preferences with power and performance to spare.
Engine air filtration	Premium Honda and Kawasaki engines come standard with a remote air intake which filters out 95 percent of airborne particulate prior to contact with the primary cartridge filter. The Briggs ELS comes standard with a proven 2-stage quick access filter cartridge.
Easy engine access	Easy access to oil dipstick, spark plugs, oil drain ports, air filters and oil filters for convenient serviceability.
Hour meter	Measure actual engine run time to monitor service intervals.
Center mounted rear engine placement	Rear engines are center mounted for maximum stability, easy service access, and maximized leg room.

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Zero Turn Mowers, ZXT Pro

ZXT54 & ZXT60 Series

Electric start	12 volt keyed ignition switch and choke control are positioned.
Twin six gallon fuel tanks	12 gallon fuel capacity for plenty of operating range. Tanks are sleekly styled with molded in drink holders. A Combination tank selector and shutoff valve is standard equipment. Fuel caps are vented and placed inboard and center mounted to protect caps and prevent overflow spills on inclines.
Isolated exhaust muffler	Mufflers are tucked away to reduce noise and to provide additional protection against burns.
Completely independent twin hydrostatic drives	Outboard heavy-wall tubular frame members also serve as independent left and right side hydraulic reservoirs for hydrostatic drive motors and fan cooled hydrostatic pumps located on each side of the machine eliminating the possibility of cross-contamination.
Stronger yet cleaner design	Integral frame and hydraulic reservoir construction reduces component clutter under the seat for easy cleanout and service access.
Ergonomically designed control console	Instrumentation and console controls are positioned for easy visual or fingertip access.
Hinged seat	Provides easy service access without tools.
Hinged foot platform	Provides quick and convenient service access to topside deck components without the need for tools.
Comfortable seats	Deluxe Cushion or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
Easy cleanout deck design	Cutting decks are designed to allow air and debris to move across the deck for improved cooling and easy cleanout
Optional ROPS	OSHA certified folding ROPS available for added operator protection.
Sun Canopy	An optional folding soft sun canopy is available to fit fixed or folding ROPS.
Snow Plow	An optional 60" or 72" motion activated snow plow is available for snow removal and year round usage. Mower deck does not need to be removed to attach the snow plow.

Designs, specifications, features and information are subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>