

Features and Benefits

Rotary Tillers, Reverse Tine Rotation

RTR20 & RTA20 Series

Features	Benefits
20 Series	Fills the gap between our 15 and 25 Series Tillers, both in size and price.
Tractor HP	23 - 40 HP.
Gearbox Warranty	5 Years Parts and Labor. Shows our confidence in the product.
Working Widths	64" & 72" Meets a wide range of customer needs.
Formed Deck	Handles material more efficiently, sheds water.
Integral Hitch	Upper hitch, gearbox and gearbox mount brought together to form a stronger overall hitch frame.
Clevis Style Lower Hitch	Allows easier hook-up of lower 3-point arms.
Cat. 1 Hitch fits Land Pride Quick-Hitch	Allows for quick and easy one-person hook-up. Offset is not comparable with Quick-Hitch.
RTR Reverse rotation model or RTA forward rotation model	Land Pride has the market on reverse rotation. This brings in a quality tiller at a more affordable price for landscapers. We offer forward rotation for contractors who want it.
Reverse tilling action	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
Sideshift capability	Sideshifts by loosening 6 U-bolts and sliding hitch points and gearbox over. Allows covering right tire track.
Parking Stand	Allows for easy hook-up and storage
Six tines standard on RTR20 Four tines standard on RTA20 with six being optional	Six tines cut through the ground smoother.
C Tines	C Tines take less horsepower to move through the ground.
17" Rotor swing diameter	For deep tilling action.
Double lip seal on rotor bearing	Double lip seal keeps the dirt out and the grease in.
#80 Drive chain enclosed in oil bath	Heavy-duty drive chain reduces stretching. Oil keeps constant lubrication and holds wear to a minimum.
Easy to adjust chain tightener	Cast iron chain tightener is a simple bolt adjustment to keep constant tension on the chain.
Stamped chain cover	Stamped forming adds additional strength.
Adjustable skid shoes	Control depth from various settings.
Cat. 3 driveline with slip-clutch (option)	Heavy driveline for rough conditions. Slip-clutch protects other drive train components.
Material separator behind tilling action (RTR only)	3/8" Rods sift the material letting bigger items fall first. Sifted soil falls last burying the bigger items. Attachment is one all welded piece for easy assembly.
Formed rear deflector with springs	Formed steel gives the rear deflector additional strength. Springs allow deflector to bounce as it hits obstructions.

Designs, specifications, features and information are subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>