

FLATRON L1715S FLATRON L1715S

17" (17.0" VIS) ACTIVE MATRIX LCD COLOR MONITOR



- ▶ **Brilliant Active Matrix TFT Display**
- ▶ **Auto-Synchronous Support from 640 x 350 up to 1280 x 1024 @ 75Hz**
- ▶ **Simple One Touch-Auto-Setup Function**
- ▶ **LightView Function (Brightness Control)**
- ▶ **VESA DDC2B, DDC1, Plug and Play Compatible**
- ▶ **Universal 90-264 VAC Power**
- ▶ **EPA Energy Star and VESA DPMS Compliant**
- ▶ **TCO'99 Low-Emission Compliant**

FLATRON™



Digitally yours

FLATRON L1715S

FLATRON L1715S

17" (17.0" VIS) ACTIVE MATRIX LCD COLOR MONITOR

FLATRON L1715S www.LGusa.com

The LG Flatron L1715S is the perfect general use space saving monitor with the quality and reliability you expect from LG. With auto-synchronous support from 640 x 350 up to 1280 x 1024 @ 75Hz and a brilliant active matrix TFT display, viewing is a pleasure. Plus it is PC and MAC compatible, has features like simple one button auto setup and is VESA DDC2B, DDC1, Plug and Play compatible - all in a slim design. The FLATRON L1715S Active Matrix LCD Color Monitor from LG. Simply Brilliant.

DISPLAY TYPE	17.0" (17.0" VIS) Active Matrix TFT Color LCD Screen
DISPLAY AREA	13.3" x 10.6" (338mm x 270mm)
DISPLAY COLORS	More than 16.1 Million (6 Bit + FRC)
PIXEL PITCH	0.26mm x 0.26mm Pixel
PIXEL CONFIGURATION	RGB Stripe Arrangement
SURFACE TREATMENT	Hard Coating 3H, Anti-Glare
ELECTRONIC INTERFACE	LVDS
BACKLIGHTING	4CCFL
MAXIMUM RESOLUTION	1280 x 1024
BRIGHTNESS	250cd/m ² (Typical)
CONTRAST RATIO	450:1 (Typical)
RESPONSE TIME	16ms (Typical)
VIEWING ANGLE	H: 160°, V: 140°
HORIZONTAL SCANNING FREQUENCIES	30-83kHz, Auto-Synchronous
VERTICAL SCANNING FREQUENCIES	56-75Hz, Auto-Synchronous
AUTO-SYNC SUPPORT	640 x 350 up to 70Hz, 640 x 480 up to 70Hz, 720 x 400 up to 70Hz, 800 x 600 up to 75Hz, 832 x 624 up to 75Hz, 1024 x 768 up to 75Hz, 1280x1024 up to 75Hz
CONTROL TYPE	On-Screen Display of Adjustments
INPUT SIGNAL	RGB Analog
INPUT TERMINALS	Standard VGA D-Sub 15-pin Connector
SYNC SIGNALING	Separate H/V
MEMORY MODES	13 Factory Preset, 10 User-Settable
VESA PLUG AND PLAY LEVEL	DDC2B, DDC1
DIGITAL ON-SCREEN CONTROLS	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase (+/-), 5 Language Select, Image Size Auto-Adjust, OSD Position, Color Temp (9300K, 6500K, User), Information, LightView
FRONT PANEL CONTROLS	Power, Menu, Adjust (Up/Down/Left/Right), Auto-Set, LightView
POWER REQUIREMENTS	90-264 VAC, 50-60Hz
DPMS POWER CONSUMPTION	On: 40 Watts, Standby: 3 Watts, DPMS Off: 3 Watts
TILT/SWIVEL	Tilt: Down 0°/Up 25°
VESA MOUNTING COMPLIANCE	Standard VESA Mounting, 100mm x 100mm Screw Spacing
DIMENSIONS WITH BASE (WxDxH)	15.2" x 6.0" x 14.7" (386mm x 152mm x 372mm)
SHIPPING DIMENSIONS (WxDxH)	17.1" x 6.6" x 18.7" (438mm x 167mm x 476mm)
WEIGHT	9.5 lbs (4.3 kg) Net: 12.6 lbs (5.7 kg) Shipping
SAFETY/REGULATORY	TCO'99, UL1950, FCC-B, EPA Energy Star, IEC950, CSA, CE, TUV-GS, SEMKO, GOST, ISO 9241-3,7,8, C-TICK, VCCI-2
ACCESSORIES	Power Cord, Signal Cable, Manual, Install Disk
LGEUS WARRANTY	3 Year QuickSwap Replacement Program
UPC#	719192165892



LG ELECTRONICS U.S.A., INC.

HEADQUARTERS

1000 Sylvan Avenue, Englewood Cliffs, NJ 07632 ▶ Tel: (201) 816-2000, Fax: (201) 816-2188 ▶ www.LGusa.com

©2003 LG Electronics U.S.A., Inc. All trademarks are property of their respective owners. Design and specifications subject to change without notice. 9/03



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>