


# LIGHTOLIER® Performance Recessed CFL Downlighting **1001HSW**

Page 1 of 2

5" Aperture Horizontal Wall Wash, Compact Fluor., Performance Series, Reflector Trim



Complete Fixture consists of Frame-In Kit and Reflector Trim. Select each separately.

UniFrame™ Compact Fluorescent Performance Series Reflector Trims		Compatible Frame-In Kits (See Individual Frame-In Kit Specification Sheets)		
Catalog No.	Description	Catalog No.	Installation Type	Lamping
<b>1001HCLSW</b> <b>1001HCDSW</b> <b>1001HWHWS</b>	5" Horizontal Single Wall Wash – Specular Clear 5" Horizontal Single Wall Wash – Clear Diffuse 5" Horizontal Single Wall Wash – Matte White	<b>1001F13U</b>	UniFrame™ Non-IC 120/277v	13w Quad Triple
		<b>1001F18U</b> <b>1001FR18U</b> <b>1001F18UEM</b>	UniFrame™ Non-IC 120/277v UniFrame™ Non-IC Remodeler 120/277v UniFrame™ Non-IC Emergency 120/277v	18w Triple
		<b>1001F26U</b> <b>1001FR26U</b> <b>1001F26UEM</b>	UniFrame™ Non-IC 120/277v UniFrame™ Non-IC Remodeler 120/277v UniFrame™ Non-IC Emergency 120/277v	26w Triple
		<b>1001FD26L1</b> <b>1001FD26L2</b>	UniFrame™ Non-IC Lutron Dimming 120v UniFrame™ Non-IC Lutron Dimming 277v	26w Triple
		<b>1001FD26MX1</b> <b>1001FD26MX2</b>	UniFrame™ Non-IC Advance Mark10 Dimming 120v UniFrame™ Non-IC Advance Mark10 Dimming 277v	26w Triple
		<b>1001FD13M7U</b>	UniFrame™ Non-IC Advance Mark7 Dimming 120/277v	13w Triple
		<b>1001FD18M7U</b>	UniFrame™ Non-IC Advance Mark7 Dimming 120/277v	18w Triple
		<b>1001FD26M7U</b>	UniFrame™ Non-IC Advance Mark7 Dimming 120/277v	26w Triple
		<b>1001F13ICU/N</b>	Performance IC 120/277v	13w Quad/Triple
		<b>1001F18ICU/N</b>	Performance IC 120/277v	18w Triple
		<b>1001F26ICU/N</b>	Performance IC 120/277v	26w Triple
		<b>1001FDICMX1/N</b> <b>1001FDICMX2/N</b>	Performance IC Advance Mark10 Dimming 120v Performance IC Advance Mark10 Dimming 277v	26w Triple

## Features

- Reflector:** Formed aluminum. Matte White flange.
- Finishes:** CL = Specular Clear (Iridescent Free coating)  
CD = Clear Diffuse  
WH = Matte White Paint
- Wall Wash Kick Reflector:** Formed aluminum. Clear finish.
- Performance Data:** 60° Cutoff angle.  
See attached photometric reports for distribution and efficiency data.  
Go to [www.lightolier.com](http://www.lightolier.com) for .IES files.

## Labels

cULus Listed. Suitable for Damp Locations. I.B.E.W.

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**


**Notes:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
[www.lightolier.com](http://www.lightolier.com) © 2008 Philips Group • C0808



## Lighting Data

### Footcandles On Wall: Multiple Units



EXAMPLE: 26w with multiple clear reflector units located 2' from wall and spaced 3' on center, the illumination on the wall 3' down from ceiling will be 23 f.c. beneath units and 21 f.c. between units.

### 26 Watt Triple Tube Lamp

#### 2' From Wall-2' On Center    2' From Wall-3' On Center

Distance From Ceiling in Feet	2' On Center			
	1'	29	27	29
	2'	43	43	43
	3'	33	33	33
	4'	24	25	24
	5'	17	18	17
	6'	12	13	12
	7'	9	9	9
	8'	7	7	7
	9'	5	5	5

Distance From Ceiling in Feet	3' On Center			
	1'	23	16	23
	2'	27	29	27
	3'	23	21	23
	4'	17	17	17
	5'	12	12	12
	6'	9	9	9
	7'	7	7	7
	8'	5	5	5
	9'	4	4	4

### 13 Watt Quad Tube Lamp

#### 2' From Wall-2' On Center    2' From Wall-3' On Center

Distance From Ceiling in Feet	2' On Center			
	1'	13	12	13
	2'	19	19	19
	3'	16	16	16
	4'	12	12	12
	5'	8	8	8
	6'	6	6	6
	7'	4	4	4
	8'	3	3	3
	9'	2	2	2

Distance From Ceiling in Feet	3' On Center			
	1'	11	7	11
	2'	12	13	12
	3'	11	11	11
	4'	8	8	8
	5'	6	6	6
	6'	4	4	4
	7'	3	3	3
	8'	2	2	2
	9'	1	1	1

### 18 Watt Triple Tube Lamp

#### 2' From Wall-2' On Center    2' From Wall-3' On Center

Distance From Ceiling in Feet	2' On Center			
	1'	27	26	27
	2'	41	42	41
	3'	32	33	32
	4'	23	23	23
	5'	16	17	16
	6'	11	12	11
	7'	8	8	8
	8'	6	6	6
	9'	5	5	5

Distance From Ceiling in Feet	3' On Center			
	1'	22	16	22
	2'	26	27	26
	3'	22	21	22
	4'	16	16	16
	5'	12	12	12
	6'	9	9	9
	7'	7	7	7
	8'	5	5	5
	9'	4	4	4

Footcandle values are initial, rounded off and based on minimum of six units.

### Job Information    Type:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 www.lightolier.com © 2008 Philips Group • C0808

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>