



Complete Fixture consists of Frame-In Kit and Reflector Trim. Select each separately.

Uniframe™ Frame-In Kit	Uniframe™ Compact Fluorescent Performance Series Reflector Trims							
	Vertical Open	Vertical Wall Wash - Single	Vertical Wall Wash - Double	Horizontal Open	Horizontal Wall Wash - Single	Horizontal Wet Location Lensed / Diffused		Horizontal Cross Blade
1101FR18U 18w Quad/Triple GX24q-2 Base 120v – 0.17amp max 277v – 0.08amp max 1101FR2642U 26w Quad/Triple GX24q-3 Base 120v – 0.24amp max 277v – 0.11amp max	1101CL 1101CD 1101WH	1101CLSW 1101CDSW 1101WHSW	1101CLDW 1101CDDW 1101WHDW	1101HCL 1101HCD 1101HWH	1101HCLSW 1101HCDSW 1101HWHSW	Clear Lens 1101HCLC 1101HCDC 1101HWHC Opal Lens 1101HCLO 1101HCDO 1101HWHO	Fresnel 1101HCLF 1101HCDF 1101HWHF	1101HACB 1101HWHCB
	Universal Series Reflector Trims (Reference Trim Spec Sheet for Recommended Lamping)							
	Performance Cone	Cone	Satin Cone	Baffle	Wall Wash	Wet Location		
	1113CFL 1113CDCFL	1112* 1113* 1113BK* 1113WH 1113CD* 1145 1146 1146CD 1143 1144 1144CD	1108* 1110*	1105* 1105BNM 1105WH 1176 1176WH	1135 1135WH 1195 1196 1196CD	1121 1124 1134 1177SH 1178SH 1190		

*Add NM suffix to catalog number for Natural Metal flange and finish.

Features

- Uniframe™ Mounting Ring:** .032" (#22ga.) thick Galvanized Steel. Accommodates existing ceilings up to 2" thick. Attaches securely to any type of ceiling material without tools using (3) mounting straps provided. Includes adhesive backed aperture template.
- Trim Clips:** "Push In / Twist Out" clips hold reflector flush to ceiling.
- Junction Box:** 2" x 4" x 3-1/2" (22cu.in.) .032" (#22ga.) galvanized steel. UL Listed for 90° C supply wire. Attaches to mounting ring without tools.
- Ballast:** 120V – 277V UL Listed Electronic Ballast, end of lamp life protection, class "P" thermally protected, class "A" sound rating.
- Socket:** Four-pin base, molded thermoplastic socket, prewired with No. 18 AWM leads to ballast.
- Socket Housing:** .036" (#20ga.) Galvanized Steel housing attaches to reflector trim by spring clip for precise optic alignment.

Labels

cULus Listed. Suitable for Damp Locations.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • E0708

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>