



LINK ELECTRONICS, INC.

AES/EBU DIGITAL AUDIO DA MODEL LEI-540



MADE IN THE USA



FEATURES

- ◆ AES-EBU Audio DA
- ◆ Stand-alone
- ◆ Six Outputs AES3-ID
- ◆ Two Outputs AES3-1992
- ◆ Transformer Coupled
- ◆ Front Panel Select BNC/Terminal Input

The LEI-540 accepts either AES3-1992 or AES3-ID inputs and provides a total of eight outputs of digital audio: six to AES3-ID specifications, two to AES3-1992 specifications. Transformer coupled inputs and outputs are standard to eliminate the possibility of ground loops. Captive screw terminal blocks are used for the AES3-1992 input/outputs while BNC's are used for the AES3-ID connections.

A front panel switch selects between BNC and screw terminal, (AES3-ID, AES3-1992). Sample rate LED's show three rates, 48KHz, 44.1KHz and 32KHz. An error detection LED indicates any errors on the incoming signal. An AC power switch on the front panel allows the user to turn the unit on or off at will. No need to go behind the rack to check the fuse; the fuse is on the front panel. Many features are found in the LEI-540 for professional use.

The digital signal path uses state-of-the-art integrated circuits. The data is re-sliced and re-clocked for jitter attenuation. Sample rates are automatically detected and indicated by front panel LEDs. Data errors are also detected and reported by a red LED on the front panel.

The 500 series is housed in the same case as the well-accepted 700 series. A black front panel distinguishes between the two series. Three 500 or 700 series can be mounted in the PRT-700 rack tray.

Designed with the professional in mind, the LEI-540 will provide years of error free performance. Backed by LINK's standard 10-year warranty, the LEI-540 combines high-performance and economy.

LINK ELECTRONICS, INC. ◆ 2137 Rust Avenue ◆ Cape Girardeau, MO 63703-7668

Phone 573 334 4433 ◆ FAX 573 334 9255

MODEL LEI-540 DIGITAL AUDIO DA AES/EBU

SPECIFICATIONS

INPUTS:

Number: Two (selectable)
Interface: AES3-1992 (twisted-pair) or AES3-ID (BNC)
Format: Bi-Phase Mark Encoded
Impedance: 110Ω or 75Ω
Sampling Frequency Range: 30kHz TO 50kHz
Level: 200mV Minimum

DIGITAL OUTPUTS:

Number: Six, AES3-ID
..... Two, AES3-1992
Format: Bi-Phase Mark Encoded
Impedance: 110Ω OR 75Ω
Level:
BNC: 1.0 Vp-p
Terminal: 4.2Vp-p Typical
Jitter: <0.02UI
Reclocking: Yes
Propagation Delay: 3 AES Frames
Connectors: Terminal Block or BNC

FRONT PANEL INDICATORS:

Power Indication: Green LED
Error/No Signal: Red LED
Sample Rate Indication: 48KHz, 44.1KHz, 32KHz, Green LEDs

FRONT PANEL CONTROLS

Power On/Off: Push Button
Input Select: AES3-1992 or AES3-ID

MECHANICAL:

Height: 1 Inch
Width: 5.5 Inches
Depth: 9.25 Inches
Weight: 2.5 Pounds



LEI-540 REAR PANEL



PRT-700 RACK TRAY

LINK ELECTRONICS, INC.

2137 Rust Avenue
Cape Girardeau, MO 63703
Phone: 573 334 4433
FAX: 573 334 9255

PROFESSIONAL SERIES--

stand-alone television system products--by **LINK**

LEI-540/110802

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>