



LINK ELECTRONICS, INC.

SD SDI VIDEO CLOSED CAPTION ENCODER/DECODER MODEL PDP-886



FEATURES

- ◆ Dual Microprocessor
- ◆ EDH Processing
- ◆ SD SDI Input/Output
- ◆ Optional, Dual Modem
- ◆ RS232 OR RS422 Data Inputs
- ◆ Encode/Decode Field 1 and Field 2
- ◆ Two Encoded Serial Digital Outputs
- ◆ Two Open-Caption Decoded SD Analog
- ◆ Two Closed Caption Encoded SD Analog
- ◆ V-Chip Compatible

SD SDI PDP-886. When the PDP-886 is used with closed caption software, the unit inserts Closed Caption data into a component serial digital datastream. There are two encoded serial digital outputs plus four SD Analog NTSC/PAL outputs. One set of the SD Analog outputs are open caption and the second SD Analog set of outputs are closed caption.

Serial control is handled via two RS-232/422 ports, selectable by an internal switch. A front panel LCD indicates Encode, Standard, Decode and Baud Rate. There are two microprocessors incorporated, two ports for each microprocessor (RS-232/422 and modem). The SD SDI signal will bypass in case of AC failure on one output.

An encoded test message may also be selected from the front panel, showing Link as the manufacturer name, model number and firmware version. A total of nine data channels for video line 21 may be selected: CC1, CC2, T1, and T2 in Field 1 along with CC3, CC4, T3, T4, and XDS in Field 2.

A built-in EDH (Error Detection and Handling) processor can monitor the incoming signal for impairments and insert new EDH data. This function will insure that the output EDH Checksum will reflect the new Line 21 waveform. An optional internal telephone modem is available for each processor. Three LED's on the front panel indicate RI, OH, and CD.

LINK ELECTRONICS, INC. ◆ 2137 Rust Avenue ◆ Cape Girardeau, MO 63703-7668

Phone 573 334 4433 ◆ FAX 573 334 9255

Download from www.somanuals.com. All Manuals Search And Download.

MODEL PDP-886 CLOSED CAPTION ENCODER, DECODER SPECIFICATIONS

INPUT:

Number: One (1)
 Standard: SMPTE 259M-C 270Mb/s
 Connector: 75Ω BNC
 Impedance: 75Ω ±1%
 Return Loss: >18dB to 270MHz
 Signal Level: 800mV ±10%

SD SDI OUTPUT:

Number: Two (2)
 Standard: SMPTE 259M-C 270Mb/s
 Connector: 75Ω BNC
 Impedance: 75Ω ±1%
 Return Loss: >18dB to 270MHz
 Signal Level: 800mV ±10%

SD ANALOG DECODER OUTPUT:

Number: Two, SD SD Analog NTSC/PAL Composite
 Level: 1 Vpp
 Impedance: 75Ω ±1%
 Connector: 75Ω BNC
 Standard: NTSC/PAL COMPOSITE
 SNR: >65dB
 Differential Phase: <1.0°
 Differential Gain: <1.5%

DATA INPUTS, Common to Both Versions

Number: 4
 RS-232/422: Two, 9-pin D Sub
 Modem: Two, RJ-11
 Protocol: 1200,n,8,1
 Baud Rate: 1200, 2400, 4800, & 9600

FRONT PANEL:

AC Power: ON/OFF
 By-Pass: Push/Push, Maintained
 Test: Push/Push, Momentary
 Three Position DIP Switch: Selects Baud rate of 1200, 2400, 4800 or 9600, plus pedestal
 LED Indicators: Video Presence, RS232 Data Presence, Pedestal
 Modem LED's: RI, OH, CD, Each Modem
 LCD Display: Encoding Mode, Field 1 or Field 2
 Decoding Mode: CC1, CC2, T1, T2, CC3, CC4, or XDS
 Standard: NTSC or PAL
 Baud Rate: 1200, 2400, 4800 & 9600

ENVIRONMENTAL:

Temperature: 0° to 50°C Ambient
 Humidity: 10% to 90% non-condensing
 AC Input: 85 to 265 VAC, 50/60Hz
 Power: 36 VAR

MECHANICAL:

Height: 1.750"
 Width: 19"
 Depth: 12"



LINK ELECTRONICS, INC. ♦ 2137 Rust Avenue ♦ Cape Girardeau, MO 63703-7668
 Phone 573 334 4433 ♦ FAX 573 334 9255

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>