

	SB-1000	SB-1300	SB-1500
WATER			
GALLON CAPACITY	8.4	10.0	11.4
HEATING SURFACE (SQ. FT.)	101.6	115.6	130.6
INLET WATER CONNECTION	2" x 2"	2" x 2"	2" x 2"
OUTLET WATER CONNECTION	2-1/2"	2-1/2"	2-1/2"
DRAIN	3/4"	3/4"	3/4"
20°F ΔT WATER FLOW (GPM) *	55	65	74
HEAD LOSS (FT. OF HD.) *	31	30	33
35°F ΔT WATER FLOW (GPM) *	32	37	42
HEAD LOSS (FT. OF HD.) *	13	11	12
MAX. WORKING PRESSURE (PSI)	160	160	160
# OF RELIEF VALVES	1	1	1
RELIEF VALVE SIZE	1"	1"	1"
RELIEF VALVE RATING (MBH)	1,954	1,954	1,954
RELIEF VALVE PRESSURE RATING (PSI)	50	50	50
GAS			
INLET CONNECTION	1-1/2"	1-1/2"	1-1/2"
MAX. INLET PRESSURE, NAT	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, NAT	5" w.c.	4" w.c.	4" w.c.
MAX. INLET PRESSURE, LP	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, LP	8" w.c.	8" w.c.	8" w.c.
BTU/HR INPUT	1,000,000	1,300,000	1,500,000
BTU/HR OUTPUT (HIGH FIRE)	940,000	1,222,000	1,410,000
BTU/HR OUTPUT (LOW FIRE)	94,000	122,200	141,000
ELECTRICAL			
VOLTAGE/HEATER	120	120	120
VOLTAGE/CONTROL	24	24	24
TOTAL AMPS	5.5	5.5	5.5
# OF ELECTRICAL CONNECTIONS	1	1	1
DIMENSIONS			
HEIGHT	58-3/4"	58-3/4"	58-3/4"
WIDTH	31"	31"	31"
DEPTH	48"	52-1/4"	55-1/2"
SERVICE CLEARANCES			
FRONT	31"	31"	31"
BACK (PIPING)	24"	24"	24"
RIGHT SIDE	0	0	0
LEFT SIDE	0	0	0
TOP	13"	13"	13"
DIRECT VENTING			
SIZE	6"	6" / 7"	6" / 7"
VENT CATEGORY	IV	IV	IV
VENT MATERIAL	PVC/CPVC/SS	PVC/CPVC/SS	PVC/CPVC/SS

* The flow rate and head loss values listed here are for each of the boiler's heating modules.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>