

COZY

Direct Vent Gas-Fired Baseboard Heaters

Cozy Comfort...with our Warmest Regards!



NEW
PATENTED HEATING
TECHNOLOGY



The patented **COZY** Gas-Fired, Direct Vent Baseboard Heater is **new** and **unique** from any gas heater currently offered! With high efficiency and state-of-the-art styling, it is a perfect answer in the following heating applications and installs on **any outside wall**:

- Retrofitting expensive electric baseboard heaters (approximately 75% less operating cost).
- Single and multi-family dwellings, high-rise, commercial and manufactured housing applications.
- Transitional entryways, under-window installations.
- Residential add-ons and sun porch applications.
- Cold-spots, or any application where **space is at a premium!**

COZY gas-fired baseboard technology was developed by three utility companies in Canada. They are eminently reliable and safe. Cozy Baseboard Heaters are approved for use in mobile home applications. Always consult with your local building code officials.

FEATURES INCLUDE:

- Two models 5,000 BTU (4 Ft.) and 9,000 BTU (6 Ft.) to choose from.
- 24 Volt thermostat (115 volt required).
- Wall thermostat and power cord (9 Ft.) included.
- Transistorized control module.
- Tubular, aluminized combustion chamber warranted for 10 years – no pro rata.
- High efficient in-shot burner.
- Standard vent fits any 4" – 16" outside wall application.
- Sealed combustion, draws no room air and exhausts unburned flue products to the outside.
- Convenient direct spark igniter – standard.
- Requires only a 2 1/2" wall opening.
- Up to three (3) units may be operated in series on one wall thermostat.
- Flame proving, automatic draft induced control assures maximum efficiency and safety.
- Vent may be installed from the inside for multi-story applications (See Vent Weather Seal Kit).

LTS 

Manufacturers of Heating Equipment Since 1888



GOZY

Comfort & Hi-Efficiency!



5,000 BTU
(Face Off)
48" (122 cm)



9,000 BTU
(Face Off)
72" (183 CM)

STANDARD ITEMS



4"-16" Vent System (Standard)



Standard Vent 1-1/2" I.D. Seal

Direct Spark Ignition Module Self-Diagnosing



Mounting Template, 24 Volt Wall T-Stat Kit, Power Cord and Flex Connector with Ball Valve

OPTIONAL ACCESSORIES



Side Valve Concealer



Bottom Valve Concealer



Vent Weather Seal Kit with 2" I.D. Seal



Vent Riser Kit

SPECIFICATIONS

Model No.	Input BTU/Hr.	Watts	Type Gas	Type Control	AFUE	Width	Depth	Height	Gas Conn.	Voltage	Minimum Center of Vent to Floor	Wall Opening	Wall Max Thickness	Wall Min Thickness	Ship Weight
BBT53	5,000	1,465	Nat.	24 Volt	73.0%	48"	5-3/8"	9-3/8"	3/8"	115V	7-7/16"	2-1/2"	16"	4"	46 lbs
BBT54	5,000	1,465	L.P.	24 Volt	73.0%	48"	5-3/8"	9-3/8"	3/8"	115V	7-7/16"	2-1/2"	16"	4"	46 lbs
BBT103	9,000	2,930	Nat.	24 Volt	80.4%	72"	5-3/8"	9-3/8"	3/8"	115V	7"	2-1/2"	16"	4"	62 lbs
BBT104	9,000	2,930	L.P.	24 Volt	80.4%	72"	5-3/8"	9-3/8"	3/8"	115V	7"	2-1/2"	16"	4"	62 lbs

1 Watt = 3.413 BTU

NOTE: Conversion Kits are available for Nat or L.P. Gas (specify existing model no.)

Louisville Tin & Stove Co.

INCORPORATED
P.O. BOX 2767 • LOUISVILLE, KENTUCKY 40201-2767
PHONE: (502)589-5380 • FAX: (502)589-5382

www.cozyheaters.com
cozyinfo@cozyheaters.com

Form No. BBT 20M 3/04

LTS

Manufacturers of heating equipment

for over 118 years



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>