### **MACE Security Product Warranty**

Mace will repair or replace, without charge, any merchandise proved defective in material or workmanship for a period of one year after the date of shipment.

### Exceptions to this warranty are as noted below:

Mace will warrant all replacement parts and repairs for 90 days from the date of Mace shipment. All goods requiring warranty repair shall be sent freight prepaid to Mace, Fort Lauderdale. Repairs made necessary by reason of misuse, alteration, normal wear, or accident are not covered under this warranty.

Mace assumes no risk and shall be subject to no liability for damages or loss resulting from the specific use or application made of the Products. Mace's liability for any claim, whether based on breach of contract, negligence, infringement of any rights of any party or product liability, relating to the Products shall not exceed the price paid by the Dealer to Mace for such Products. In no event will Mace be liable for any special, incidental or consequential damages (including loss of use, loss of profit and claims of third parties) however caused, whether by the negligence of Mace or otherwise.

If a warranty repair is required, the Dealer must contact Mace at (877) 585-6223 or (954) 585-6223 to obtain a Repair Authorization (RA) number, and provide the following information:

- 1. Model and serial number
- 2. Date of shipment, P.O. number, Sales Order number, or Mace invoice number
- 3. Details of the defect or problem

### **MACE Electronic Surveillance Products**

3233 SW 2nd Ave. Fort Lauderdale, FL 33315 USA toll-free(877)585-MACE local(954)585-6223 fax(954)585-6225 www.mace.com



# High Resolution Color Camera

Model : CAM94
Instruction Guide




**MACE Electronic Surveillance Products** 





(\*) Must use regulated & specified power supply

Marie serior beginner and technique		
.xsm HA %00		VibimuH gnissrad0
-10°C ~ +50°C		.qməT gnijayəq0
Max. 250mA (AC24V) / Max. 280mA (DC12V)		Power Consumption
VC24√ \ DC12√ ∓ 10%		Power Supply(*)
C/CS MOUNT		suəj
(bsoJ Ω3T) q-qV 0.1 SAV		Video Output
0.6 Lux / F1.2, 50 IRE		noitsnimuIII .niM
AWA		White Balance
Internal / Line Lock		Sync, System
More than 48dB (AGC OFF)		oite# N\2
1/50~1/100,000 sec.	1/60~1/100,000 sec.	Shutter Speed
S25 T-V-Lines		Resolution
15.625KHz (H), 50Hz (V)	15.734KHz (H), 59.94Hz (V)	Canning Frequency
625 Lines 2:1 Interlace	525 Lines 2:1 Interlace	Scanning System
752H X 582V (440K pixels)	(380K pixels) 7494 X H897	Elfective Pixels
1/3" Interline transfer type COLOR (SONY)		ToznaZ agsml
l∆q	DSTN	M∃TI










# **■** DIWENSION

- Power Supply: AC24V / DC12V Dual Voltage
  - Excellent Color Rolling Suppression
    - Auto Iris Function (Video/DC)
- BLC ON/OFF, ESC ON/OFF, Internal / Line Lock, AWB / ATW
  - High Resolution of 525 TV-Lines
    - SONY SS-HQI Chip
  - SONY 1/3" Super HAD Color Camera

# ■ FEATURES


# High Resolution Color CCD Camera



# **■ INSTALLATION PRECAUTIONS**

- The mounting bracket must be mounted to a structured member such as a wall or ceiling after using suitable fastener by install guide.
- The maximum recommended load of the mounting bracket is 5Kgs.
- If user uses a over spec adaptor, then camera is not working.
- Adaptor Spec : AC 24V Class 2 power supply (AC24V/DC12V)

## **■ FUNCTION**



- ESC ON / OFF
- BLC ON / OFF
- Internal / Line Lock
- AWB / ATW
- AUTO IRIS LENS (VIDEO / DC)

■ VIDEO- TYPE & DC TYPE AUTO IRIS LENS INSTALLATION AND ADJUSTMENT

The camera supports auto-iris lens.


To install and adjust a VIDEO or DC-type auto-iris lens, do the following:

- Thread the auto-iris lens onto the lens mount on the front of the camera.
- Solder the lens control wires to the connector (cf. Table 1)
- Plug the connector into the auto iris jack
- Select lens switch and set ESC mode to OFF
- Apply power to the camera

[TABLE. 1 : PIN CONFIGURATION OF AUTO-IRIS JACK]

Pin	VIDEO-TYPE	DC-TYPE
1	Voltage +	Damp Coil –
2	Open	Damp Coil +
3	Video	Drive Coil +
4	Ground	Drive Coil –

[FIG.1: AUTO-IRIS LENS CONNECTION CONFIGURATION]



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com