

Jig Saw

4350T, 4350CT, 4350FCT Top Handle Type



Satisfy Professional's Needs





HIGH QUALITY & RELIABILITY

by Superior Maneuverability



Toolless Blade Change Enables extremely quick blade changes.

Low Noise Low Vibration **Electronic** Control*


LED Job Light* Capacity in Wood

Powerful Motor *4350CT, 4350FCT, 4351CT, 4351FCT



Low Noise & Low Vibration

employs lightweight Rod and balance plate mechanism* to reduce vibration dramatically. Reducing vibration makes operator feel more comfortable when cutting various workpieces.



*balance plate mechanism: Counterbalance mechanism to reduce vibration by moving Plate in the opposite direction of Rod

Electronic Control



Variable Speed Control by Dial ensures optimum cutting speed per job.

- Constant Speed Control keeps minimizing the speed loss under loaded conditions.
- Soft Start suppresses the shock when starting.

Comparison of Features and Specifications

For Model	4350T	4350CT	4350FCT	4351T	4351CT	4351FCT
Handle type	Top handle			Body handle		
Continuous rating Input	580W	720W	720W	580W	720W	720W
Electronic Control*	-			-		
Built-in Job Light	-	-		-	-	

*Electronic Control:

Variable Speed Control by Dial, Constant Speed Control and Soft Start

(4350FCT, 4351FCT only) rubberized grip provides more control and comfort. Tnakita **Rigid Aluminum Base Blower function Cover Plate** keeps the cut line clean Protects workpiece from scratches

LED Job Light

3 Orbital settings + Straight cutting

Ergonomically designed

Optimum cutting action can be selected by simply turning the change lever.

Dust Nozzle

(Standard Equipment: European countries only)



Can be connected to vacuum with Hose Complete 28-5.

Comparison of Cutting Efficiency

Note: 1. The test results depend to a great extent on the hardness of materials, etc. The numbers in the charts below are relative values when the capacitie of 4340FCT are indexed at 100.

Test conditions:

Test material: 48mm thick MDF Orbital mode: 3 Blade: B-10

Work speed Makita 4350FCT slow 0 80 100 fast

Test conditions:

Test material: 3.2mm thick SPCC Orbital mode: 0 Blade: B-22

Work speed Makita 4350FCT 100 slow 0 80 100 fast

Accessories

Guide Rail

Bevel cutting Aluminum base can be tilted

or right.

up to 45-degrees to the left

1.4m: Part No. 194368-5 3.0m: Part No. 194367-7

Guide Rail Adapter Set

Part No. 193517-1



Anti-Splintering Device

(For cleaner cuts) Part No. 192557-6 **Guide Rule Set**

Part No. 193516-3

Cover Plate Part No. 417852-6

Dust Nozzle

Part No. 417853-4

Hose Complete 28-5 Part No. A-34229





Items of standard equipment and specifications may differ by country or area

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com