

Gas nailer GN900SE

First fix cordless framing nailer



Satisfying the professional's needs



LITHIUM-ION

The new gas nailer designed for the demands of the professional. Suitable for timber frames, roofing, joist and a host of other applications Makita now have a better solution with this easily portable machine.

Gas nailer GN900SE

Fire up to 7,200 nails per hour.

The Makita clipped head gas nailer has arrived! Using tried and tested technology. It is suitable for timber frames, roofing, joist and a host of other applications we now have the answer, in a truly portable machine.

No leads, no hoses, just fast and versatile power.

The GN900SE uses our tried and tested Lithium-ion 7.2 volt battery system with a 30 minute charge time which makes the Makita GN900SE four times quicker than the leading competitor. The small and light weight 7.2 volt battery will allow you to fire up to 4000 nails per charge. The GN900SE features our LED low battery and error detection system, and a shock absorbing battery fitting to protect the terminals

The 40 gram gas cell will allow you to fire up to 1200 shots per cell using our 34° nail and gas packs at a rate of 2-3 nails per second.

In true Makita tradition the gas nailer is light weight, comfortable and perfectly balanced, it is also easy to use and well engineered. All that you have come to expect from Makita.

Charges 4 times quicker than the leading competitor.



The only gas nailer with Lithium-ion battery technology

LITHIUM-ION



Gas cell chamber
Quick and easy load system.



LED light service indicator

Green: Good battery
Red: Low/dead battery
Orange: Error codes



30 minute charge time

Hex wrench

Attached to the machine for easy access to adjust the depth of the nail drive.



Battery BL7010



Charger DC07SA

7.2v Li-ion battery

Use of a li-ion battery allows for compact and lightweight tool design. 30 min charge time.



Air filter

Protects cylinder from dirt and debris to prevent malfunction.

Hook

Easily clipped on to a belt or extends to sit over small joists and scaffolding.

44 nail magazine

Will hold 50mm - 90mm nails with easy view quick load system.

Contact nose

5 stage depth adjustment and anti slip contact.



GUARANTEE

Subject to normal terms and conditions

Choosing the correct nail

| TYPE | EXPLANATION |
|--------------------|--|
| Smooth bright | Good for use on internal jobs where there is no or very little exposure to moisture. Use on non permanent work such as shuttering. |
| Galvanised | The most popular as it gives good protection against corrosion and can be used for most applications. |
| Hot Dip Galvanised | Recommended for use on external work or where corrosion could damage the finish or integrity of the joint. |

Choosing the correct shank

| TYPE | EXPLANATION |
|---------|---|
| Smooth | The most common nail, it can be used for most joints. |
| Ring | Identified by the rings around the shaft, these nails are generally used where a very strong joint is required. |
| Unilock | A cross between Smooth and Ring types, for use where a medium strength joint is required. |

Nail and fuel packs

2,200 pcs includes 2 gas canisters

3,300 pcs includes 3 gas canisters

| PART NUMBER | DESCRIPTION | QUANTITY |
|-----------------------------------|--|----------|
| ● Nails Bright | | |
| 194764-7 | Clipped Head 2.9 x 51 Ring Bright | 3,300 |
| 194772-8 | Clipped Head 2.9 x 63 Ring Bright | 3,300 |
| 194776-0 | Clipped Head 3.1 x 75 Ring Bright | 2,200 |
| 194767-1 | Clipped Head 3.1 x 90 Smooth Bright | 2,200 |
| ● Nails Galvanised | | |
| 194765-5 | Clipped Head 2.9 x 51 Ring Galvanised | 3,300 |
| 194766-3 | Clipped Head 2.9 x 57 Ring Galvanised | 3,300 |
| 194768-9 | Clipped Head 2.9x63 Ring Galvanised | 3,300 |
| 194770-2 | Clipped Head 3.1 x 63 Ring Galvanised | 2,200 |
| 194773-6 | Clipped Head 3.1 x 75 Ring Galvanised | 2,200 |
| 194777-8 | Clipped Head 3.1 x 90 Smooth Galvanised | 2,200 |
| ● Nails Hot Dip Galvanised | | |
| 194769-7 | Clipped Head 2.9 x 63 Ring Hot Dip Galvanised | 3,300 |
| 194771-0 | Clipped Head 3.1 x 63 Ring Hot Dip Galvanised | 2,200 |
| 194774-4 | Clipped Head 3.1 x 75 Ring Hot Dip Galvanised | 2,200 |
| 194775-2 | Clipped Head 3.1 x 75 Unilock Hot Dip Galvanised | 2,200 |
| 194778-6 | Clipped Head 3.1 x 90 Smooth Hot Dip Galvanised | 2,200 |

Job packs

1,100 pcs includes 1 gas canister

| PART NUMBER | DESCRIPTION | QUANTITY |
|-----------------------------------|---|----------|
| ● Nail Bright | | |
| 194780-9 | Clipped Head 2.9 x 51 Ring Bright | 1,100 |
| 194784-1 | Clipped Head 2.9 x 63 Ring Bright | 1,100 |
| ● Nails Galvanised | | |
| 194782-5 | Clipped Head 2.9 x 51 Ring Galvanised | 1,100 |
| 194785-9 | Clipped Head 2.9 x 63 Ring Galvanised | 1,100 |
| 194788-3 | Clipped Head 3.1 x 63 Ring Galvanised | 1,100 |
| 194792-2 | Clipped Head 3.1 x 75 Ring Galvanised | 1,100 |
| 194796-4 | Clipped Head 3.1 x 90 Smooth Galvanised | 1,100 |
| ● Nails Hot Dip Galvanised | | |
| 194783-3 | Clipped Head 2.9 x 57 Ring Hot Dip Galvanised | 1,100 |
| 194786-7 | Clipped Head 2.9 x 63 Ring Hot Dip Galvanised | 1,100 |
| 194790-6 | Clipped Head 3.1 x 63 Ring Hot Dip Galvanised | 1,100 |
| 194793-0 | Clipped Head 3.1 x 75 Ring Hot Dip Galvanised | 1,100 |
| 194797-2 | Clipped Head 3.1 x 90 Smooth Hot Dip Galvanised | 1,100 |



Satisfying the professional's needs

Makita UK

Michigan Drive, Tongwell, Milton Keynes, Buckinghamshire MK15 8JD
T: 01908 211678 F: 01908 211400

www.makitauk.com

98N315 0808

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>