



Manitowoc

FILTER/DRIER

Installation Instructions

IMPORTANT

TO PREVENT FUTURE FAILURES AND MAINTAIN WARRANTY STATUS, FOLLOW THESE SPECIAL INSTRUCTIONS FOR INSTALLATION OF THE COMPRESSOR:

1. The filter/drier, included with this compressor assembly, must be installed in the system before the replacement compressor is started.
2. Drier, 8930283 (UK165S), is to be installed in the suction line as close to the compressor as possible.
3. Install a pressure access fitting before the suction drier.
4. Install correct Manитowoc liquid line drier.

The filter/drier installed in the suction line is required to protect the replacement compressor from being contaminated with microscopic metal particulates that may have been generated by the previous compressor failure. The liquid line drier cannot filter out all of the particulates because of the refrigerant flow bypassing it during harvest.

With mild system contamination, it is not necessary to remove the filter/drier in the suction line. If this is a severe system contamination, follow the clean up procedures published in our Manitowoc technical manuals, ultimately leaving a suction line filter/drier in the system.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>