



J-0320/J-0420 LEFT SIDE SPLASH SHIELD

Installation Instructions

1. Place ice machine toggle switch in “OFF” position.
2. Clean and dry the left sidewall, without removing the water trough.
3. Remove backing from foam tape which has been applied to mylar splash shield.
4. Install the shield so that the notched out area is placed under the water trough tight to the bottom back corner of the bulkhead wall.
5. Press the mylar against the sidewall so that the tape adheres.
6. Place ice machine toggle switch in “ON” position.
7. Check one ice making cycle for proper operation.

Manitowoc Ice, Inc.

2110 South 26 Street, P.O. Box 1720, Manitowoc, WI 54221-1720 USA
Telephone 920-682-0161, Fax - Sales: 920-683-7589, Service/Parts: 920-683-7585, Other: 920-683-7879

8009713
Rev. 06/10/97

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>