

THE BEST WARRANTY IN THE BUSINESS

5 YEARS ON ALL PARTS.

OUR FASTEST-SELLING WASHER

Maytag® Commercial Neptune® high-efficiency washers use less water and energy than conventional washers, cutting your utility costs. High-speed extraction helps dryers keep pace with washers.

COMPUTER TRAC® CONTROLS

Maytag® Computer Trac® controls are easy to program and provide simple one-touch cycle selection.



FOR YOUR OPERATION:

- Up To 32% Greater Capacity Than Conventional Washers
- High-Speed Extraction Cuts **Drying Time**
- Automatic Load-Balancing System
- Simple One-Touch Cycle Selection
- Display Counts Down Time Remaining In Cycle
- Extra-Large Door Opens 180°
- · Reversible Door
- Simple Soft-Mount Design
- Optional Liquid Chemical Supply System
- Meets ADA Accessibility Guidelines

BUILT-TO-LAST™ FEATURES:

- Built-In Anti-Vibration Mechanism
- Porcelain-Enamel Top
- Precision Endurance Drive
- Controlled Induction Motor

MAYTAG® COMMERCIAL NEPTUNE® HIGH-EFFICIENCY WASHER

MAH21PN





*N*ATER AND SEWER COST

Based on testing with a 10-pound AHAM load with 30% hot-, 55% warm- and 15% cold-water wash at five turns per day and 365 days per year. Water, gas and sewer costs based on 2000 average U.S. national rates. Individual savings may vary.

28'/4"* (71.8 cm) Door open 90° 50'/2"* (128.3 cm) 413/4"** (106 cm) 413/4"** (106 cm)

* Includes hinge on back of washer.



5 YEARS — ALL PARTS

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.

* This limited-time Maytag* Extra-Protection 5-Year Warranty offer is available through December 31, 2004.

Neptune® High-Efficiency Washer —

MICROPROCESSOR CONTROL

	Neptune® High- Efficiency Washer
WASHER SPECIFICATIONS	- Eury W
MODEL	MAH21PN
MOTOR	
Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction	•
Wash — HP (kw)	1/4 (.19)
Extract — HP (kw)	1/2 (.37)
APPROXIMATE WATER USAGE — gal. (liters)	
Factory preset hot cycle average, hot water	51/2 (18.9)
Factory preset warm cycle average, hot water	2 (9.5)
Factory preset average, overall	15 (56.7) [†]
ELECTRICAL RATING	
120V, 60 Hz	•
Export models — 220 – 240V, 50 Hz	•
FUSE REQUIREMENTS	
Amps	15
Export amps	10
CYLINDER	
Volume — cu. ft. (liters)	2.9 (82.1)
Diameter — in. (cm)	211/2 (54.6)
Depth — in. (cm)	16 (40.6)
DOOR OPENING	
In. (cm)	151/2 (39.4)
WASH SPEED	
Maximum rpm	47 – 51
EXTRACT SPEED	
Maximum rpm	1,000
Maximum g-force	307
OPERATING PRESSURE	
Psi (bar)	15 – 120 (1 – 8)
INLET HOSE	
Ft. (m)	4 (1.22)
DRAIN HOSE	
In. (cm)	42 (109.7)
ADJUSTABLE LEVELING LEGS	•
COLOR	
White	•
APPROXIMATE WEIGHT	
Crated — lbs. (kg)	225 (102)
Uncrated — lbs. (kg)	195 (88)

'Average based on testing with an 8-pound AHAM load. If optional additional rinse is used, add 5 gallons; not dependent on incoming pressure or time.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.













Dimensions will vary according to adjustment of leveling legs; add 2" (5.1 cm) minimum.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com