

Engine Drive Trailers

Issued March 2006 • Index No. AY/20.0

Engine Drive
Accessories 

Quick Specs

Trailer	Net Payload	For Use With
HWY-1000	1000 lb (454 kg)	Miller Legend, Bobcats, and Trailblazers
Mid-Frame	1424 lb (645 kg)	Big Blue 300 and PRO 300
4 West	2570 lb (1166 kg)	Big 40, Big Blue 400 and 500, Big Blue Turbo, Miller Du-Op, and Big Blue Air Pak
HWY-224, OFR-224	2650 lb (1202 kg)	All Engine Drive Products
HWY-430	3750 lb (1701 kg)	All Engine Drive Products

The Power of Blue.®



HWY-1000 Trailer #195 013

A 1000 lb (454 kg) capacity highway trailer with welded steel tubing frame, heavy-duty axle with roller bearing hubs and leaf-spring suspension. Includes jack stand, 2 in (50 mm) ball hitch, fenders and lights.

Note: Trailer is shipped unassembled.

Cable Tree #195 023

Provides an area to conveniently wrap weld cables and extension cords.

Lunette Eye 2-1/2 in (64 mm) #043 824



Shown with ball hitch, fenders and lights.

Mid-Frame Trailer #195 481

A 1424 lb (645 kg) capacity highway trailer with welded steel tubing frame, heavy-duty axle with roller bearing hubs and leaf-spring suspension. Includes jack stand, and safety chain (order hitch separately).

Note: Trailer is shipped unassembled.

Ball Hitch, 2 in #195 493

Lunette Eye 2-1/2 in (64 mm) #043 824

Fender Kit #195 482

Light Kit #195 483 Requires fender kit.

Cable Tree #195 023

Provides an area to conveniently wrap weld cables and extension cords.



4 West Four-Wheel Steerable Off-Road Trailer #042 801

A heavy-duty 2570 lb (1166 kg) capacity trailer designed for use in mines, quarries, and other rough terrain. Has narrow 22 ft (6.7 m) turning radius. Includes 3 in lunette eye, universal hitch and safety chains.

Note: Trailer is shipped unassembled.



HWY-224 Trailer #043 805

For highway use.

OFR-224 Trailer #043 802

For off-road use.

A 2650 lb (1202 kg) capacity trailer. Welded steel tubing frame, heavy-duty axle with roller bearing hubs and leaf-spring suspension. Includes jack stand, 2 in (50 mm) ball hitch. *HWY-224 also includes fenders and lights.*

Note: Trailer is shipped unassembled.

Cable Tree #043 826

Provides an area to conveniently wrap weld cables and extension cords.

Lunette Eye 2-1/2 in (64 mm) #043 824



HWY-430 Tandem Axle Trailer #043 806

Smooth riding with 3750 lb (1701 kg) capacity. Includes hand-operated parking brake, hydraulic brake system, and a break-away device to lock brakes if the trailer comes loose. Includes jack stand, fenders and lights. (Hitch must be ordered separately.)

Note: Some assembly required.

Cable Tree #043 826

Provides an area to conveniently wrap weld cables and extension cords.

Ball Hitch 2 in (50 mm) #043 864

Lunette Eye 3 in (76 mm) #043 863



1 year — parts and labor unless specified.

MADE IN **USA**
APPLETON, WI **USA**



Miller Electric Mfg. Co.

An Illinois Tool Works Company
1635 West Spencer Street
Appleton, WI 54914 USA

International Headquarters

Phone: 920-735-4505
USA FAX: 920-735-4134
Canadian FAX: 920-735-4169
International FAX: 920-735-4125

Web Site

www.MillerWelds.com



Specifications (Subject to change without notice.)

Model	Gross Axle Weight Rating	Gross Vehicle Weight Rating	Net Payload	Height of Bed	Road Clearance	Track (Center to center of tires)	Standard Tires (Standard rating or P-size rating)	Dimensions	Net Weight
HWY-1000	1500 lb (680 kg)	1265 lb (574 kg)	1000 lb (454 kg)	18-1/2 in (470 mm)	6-1/2 in (165 mm)	50 in (1270 mm)	4.8-12	Length: 98 in (2489 mm) Width: 57-1/2 in (1460 mm)*	265 lb (120 kg)
Mid-Frame	1500 lb (680 kg)	1666 lb (755 kg)	1424 lb (645 kg)	18-1/2 in (470 mm)	6-1/2 in (165 mm)	45 in (1143 mm)	B78-13	Length: 98 in (2489 mm) Width: 52 in (1321 mm)*	242 lb (110 kg)
4 West	2000 lb/axle (907 kg/axle)	3000 lb (1361 kg)	2570 lb (1166 kg)	21-1/4 in (540 mm)	8 in (203 mm)	55-1/4 in (1403 mm)	B78-13	Length: 91 in (2311 mm)** Width: 61-1/4 in (1556 mm)	430 lb (195 kg)
HWY-224 OFR-224	3500 lb (1588 kg)	2960 lb (1343 kg)	2650 lb (1202 kg)	18-1/2 in (470 mm)	7-1/2 in (191 mm)	52 in (1321 mm)	B78-13B	Length: 122-1/2 in (3112 mm) Width: HWY-61 in (1549 mm)* OFR-58-1/2 in (1486 mm)	355 lb (161 kg)
HWY-430	2200 lb/axle (998 kg/axle)	4280 lb (1941 kg)	3750 lb (1701 kg)	19-1/4 in (489 mm)	8-1/2 in (216 mm)	52 in (1321 mm)	B78-13B	Length: 156-1/2 in (3975 mm) Width: 61 in (1549 mm)*	530 lb (240 kg)

* Width at outside of fenders. ** Does not include tongue.

Ordering Information (Note: Trailers are shipped unassembled.)

Trailers and Accessories	Stock No.	Description	Qty.	Price
HWY-1000 Trailer	#195 013	Trailer with jack stand, 2 in ball hitch, fenders and lights		
Cable Tree	#195 023	Trailer-mounted cable holder		
Lunette Eye, 2-1/2 in	#043 824			
Mid-Frame Trailer	#195 481	Trailer with jack stand and safety chain. Order hitch separately		
Ball Hitch, 2 in	#195 493			
Lunette Eye	#043 824			
Fender Kit	#195 482			
Light Kit	#195 483	Requires fender kit		
Cable Tree	#195 023	Trailer-mounted cable holder		
4-West Trailer	#042 801	4 wheel steerable implement trailer		
HWY-224 Trailer	#043 805	Trailer with lights, fenders and 2 in ball hitch. For highway use		
OFR-224 Trailer	#043 802	Trailer with 2 in ball hitch. For off-road use		
Lunette Eye, 2-1/2 in	#043 824	For HWY-224 or OFR-224		
Cable Tree	#043 826	Trailer-mounted cable holder for HWY-224 or OFR-224		
HWY-430 Trailer	#043 806	Order hitch separately		
Ball Hitch, 2 in	#043 864	For HWY-430 only		
Lunette Eye, 3 in	#043 863	For HWY-430 only		
Cable Tree	#043 826	Trailer-mounted cable holder for HWY-430		

Date: Total Quoted Price:



Distributed by:

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>