



High Speed POS Printer

RP-300-H



The RP-300H is an extremely fast and powerful thermalbond printer with up to 200 mm/s printing speed and a resolution of 180 dpi. With its compact size and integrated wall-mounting feature, the durable model is perfect for use in various application areas. A variety of interface possibilities allow for the easy connection of the printer to an existing cash register system. The thermal paper roll prints cost effectively until the end. And the best thing is that thanks to singular, one-of-a-kind technology the RP-300H with 8MB of logo memory also simultaneously (approved by) prints coupons, promotional texts, rebate offers or other customer information.

Special Features:

- ➔ Resolution 180 dpi
- ➔ Integrated wall mounting
- ➔ Signal tone remote
- ➔ Available in black and light grey
- ➔ Interface options: RS232, USB, parallel, LAN, WL AN
- ➔ Auto cutter
- ➔ Power unit included

High Speed POS Printer RP-300-H

Technical specifications

Print method	Direct Thermal
Printing speed	200 mm/sec.
Dot density	180 x 180 DPI
Dot pitch	0,141 x 0,141 mm
Effective printing width	72 mm, 512 Dots/lines
Printing direction	Unidirectional with friction feed
Character per line	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns
Paper Type:	Thermal paper
Width:	50 mm - 82,5 mm
Thickness:	0,06 - 0,09 mm
Rolldiameter:	max. Ø 83 mm
Roll core inner:	12,5mm +/- 0,5 mm
Reliability TPH:	100 km
MCBF:	60,000,000 Lines
Character set	95
Alphanumeric:	128 x 18 page (1 space page)
Extended graphic:	14
International:	
Barcode	EAN-8, EAN-13, CODE39, ITF, UPC-A, CODABAR, CODE93, CODE128, PDF417(2D)
Emulation	ESC/POS Command compatible TMT-88III
Driver	Epson driver compatible
Sensor	Papier end sensor, Cover open sensor, Black mark sensor (option), Paper low sensor (option)
Cash drawer driver	2 circuits (24V, 1A)
Interface	Serial RS-232C, Parallel (IEEE-1284), USB, Ethernet, Wifi, USB Combo
Power	100 - 240 V / 24 V 2,5 A
Dimension	152 (W) x 204 (D) x 150 (H) mm
Weight	1,7 Kg incl. auto cutter
Option	Water spill proof cover



Partner Tech Taiwan

Tel: +886-2-29188500
Fax: +886-2-29153405
E-mail: sales@partner.com.tw
Address: 10F, 233-2, Pao Chiao Road,
Hsin Tien, Taipei, Taiwan, R.O.C

Partner Tech USA

Tel: +1-949-598-1888
Fax: +1-949-598-0088
E-mail: sales@partnertechcorp.com
Address: 51 Parker Irvine, CA 92618

Partner Tech Europe

Tel: +49 (0)40 450 635-0
Fax: +49 (0)40 450 635-130
E-mail: info@partner-tech.eu
Address: Fasanenweg 25,D-22145
Hamburg,,Germany



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>