

NEC MultiSync® P221W

22" widescreen professional LCD display ideal for graphics applications

Designed with key features for the graphics/photography professional, the 22" NEC MultiSync P221W is a smart investment for your desktop, while ensuring accurate, consistent and repeatable color performance.

- Best-in-class active matrix LCD technology with wide viewing angle and wide color gamut provides optimum performance for displaying color images
- Wide color gamut achieves 96% coverage of AdobeRGB (92% color gamut size vs. NTSC [1953])
- Internal 10-bit programmable lookup tables (LUTs) allow the display of 16.7 million colors out of a palette of 1.05 billion for lossless color and smooth images and hardware calibration
- AmbiBright™ ambient light sensor automatically adjusts the display's brightness based on lighting conditions
- XtraView+™ technology provides for the widest viewing angles available (up to 178°) with minimal off-angle color shift
- Four-way ergonomic stand boasts pivot, swivel, tilt and height-adjustment up to 150mm to maximize your viewing comfort



The P221W's design allows you to adjust the display to your exact ergonomic preferences. In addition to tilt and swivel functionality, the height adjusts up to 150mm, and the display pivots between landscape to portrait orientations.



Available as an option for the P221W, the SpectraView_{II}TM system uses a color sensor to take color measurements of the display screen during calibration. The software analyzes these measurements and sends color adjustment commands directly to the display monitor. This means that color adjustments are made in the monitor rather than in the video graphics adapter, resulting in full use of the number of colors available on the graphics adapter and a much brighter image with the maximum possible color, resolution and fidelity.



Model	MultiSync P221W
Display	<p>Viewable Size Image 22"</p> <p>Pixel Pitch 0.282mm</p> <p>Pixels Per Inch 89 @ native resolution</p> <p>Brightness (typical) 300 cd/m²</p> <p>Contrast Ratio (typical) 1000:1</p> <p>Viewing Angle (typical) 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR > 10</p> <p>Response Time (typical) Rapid Response™ (8ms Gray-to-Gray; 16ms Black-to-Black)</p> <p>Panel Bit Depth 10-bit internal LUTs, displays 16.7 million colors out of 1.05 billion color palette</p> <p>Color Gamut*</p> <p>Coverage AdobeRGB** - 96%</p> <p>Size AdobeRGB - 92%</p>
Synchronization Range	<p>Horizontal 31.5 - 93.8/119.2 KHz (Analog/Digital)</p> <p>Vertical 51 - 85 Hz</p>
Input Signal	<p>Video Analog RGB 0.7 Vp-p/75 Ohms</p> <p>Sync Separate sync: TTL Level (Positive/Negative)</p> <p>Composite sync: TTL Level (Positive/Negative)</p> <p>Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)</p>
Inputs	DVI-D & VGA 15-pin D-sub
Resolutions Supported (Analog/Digital)	<p>720 x 400 @ 70-85 Hz</p> <p>640 x 480 @ 60-85 Hz</p> <p>800 x 600 @ 56-85 Hz</p> <p>832 x 624 @ 75 Hz</p> <p>1024 x 768 @ 60-85 Hz</p> <p>1152 x 864 @ 70-85 Hz</p> <p>1152 x 870 @ 75 Hz</p> <p>1280 x 960 @ 60 Hz</p> <p>1280 x 1024 @ 60-75 Hz</p> <p>1600 x 1200 @ 60 Hz</p> <p>1920 x 1200 @ 60Hz</p>
Native Resolution	1680 x 1050 @ 60Hz
Additional Features	<p>AmbiBright - ambient light sensor, ultra-thin frame (bezel), No Touch Auto Adjust™, NaViSet™ software, tilt, VESA Mount, sRGB, tilt, swivel, height-adjustable stand (150mm), pivot, quick-release stand, vacation switch, 10-bit LUTs, black level adjustment, overdrive, ECO Mode™, real-time clock, Analog/Digital CableComp™, TileMatrix™, TileComp™, SpectraView_{II}™ software-enabled</p>
Touch-Capable	Designed for integration
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption (typical)	<p>On 62W</p> <p>Power Savings Mode 2W</p>
Dimensions (WxHxD)	<p>Net (with stand) 19.9 x 16.1-22 x 9.7 in. / 506.4 x 410-560 x 247.3mm</p> <p>Net (without stand) 19.9 x 12.9 x 3.7 in. / 506.4 x 328.7 x 94mm</p>
Net Weight	<p>(with stand) 18.5 lbs. / 8.4 kg</p> <p>(without stand) 12.6 lbs. / 5.7 kg</p>
VESA Hole Configuration Specifications	100 x 100mm
Environmental Conditions	<p>Operating Temperature 5-35° C / 41-95° F</p> <p>Operating Humidity 30-80%</p> <p>Operating Altitude 3048m / 10,000 ft.</p> <p>Storage Temperature -10-60° C / 14-140° F</p> <p>Storage Humidity 10-85%</p> <p>Storage Altitude 12,192m / 40,000 ft.</p>
Safety Standards	UL / C-UL, CE, Gost/PCT, PSB, CCC, NOM, TUV GS, FCC Class B/Canadian DOC, C-tick, MPR II / MPR III, VCCI (class 2), TUV-Ergonomie, TCO 03, , Energy Star 4.0 Tier 2, GEEA
Limited Warranty	3 years parts and labor, including backlight
Technical Support	M - F (7am - 7pm CST)

* Color gamut size and coverage calculated as 2-D gamut area in CIE 1931 xy colorspace. Size is the total relative display gamut area and includes any colors outside the reference gamut. Coverage is the relative display gamut area contained inside the reference gamut. NTSC values provided for comparison purposes - modern broadcast video uses SMPTE-C, ITU-R BT, 709-5/sRGB or EBU primaries.

** AdobeRGB is a standard defined by Adobe Systems Incorporated.



MultiSync is a registered trademark, and AmbiBright, SpectraView, and XtraView+ are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change. 10/08 ver. 1.

©2008 NEC Display Solutions of America, Inc. All rights reserved.

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

NEC

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>