New Holland BC5000 Series Small Square Baler Specifications



BC5050 BC5060 BC5070 BC5080

MODEL Bale Size:	BC5050	BC5060	BC5070	BC5080
Cross section, in. (cm) Length, in. (cm)	14x18 (36x46)	14x18 (36x46) Adjustable, 12 t	14x18 (36x46) o 52 (31 to 132)	16x18 (41x48)
SUPER-SWEEP PICKUP:				
Width inside, in. (m) Width on flare, in. (m) Number of teeth Floating windguard Drive	65 (1.65) 70 (1.8) 88 on four tooth bars Eight rodsV-belt to roller chain to "lo	65 (1.65) 70 (1.8) 110 on five tooth bars Eight rods st motion" reel drive	75 (1.9) 80 (2) 156 on six tooth bars Thirteen rods	75 (1.9) 80 (2) 156 on six tooth bars Thirteen rods
Gauge wheel	3.00x12; semi-pneumatic	3.00x12; semi-pneumatic	15x6.00x6	15x6.00x6
ROTARY FEEDING SYSTEM: Type	_	Packer fork in combination with two paired rotors	Packer fork in combination with three paired rotors	Packer fork in combination with three paired rotors
Drive	_		nain drive shaft; sealed ball bearin	
FLOW-ACTION® FEEDING SYSTEM: Type	Six feeder tines on a moving finger bar	_	_	_
Drive	Chain; sealed ball bearings	_	_	_
FEED OPENING, sq. in. (cm³)	283 (1826)	283 (1826)	283 (1826)	318 (2052)
PLUNGER: Stroke length, in. (cm) Speed (540 rpm) Construction	30 (76.2) 79 SPM High-strength steel through	30 (76.2) 93 SPM out; modified extension is built int	30 (76.2) 93 SPM o the plunger face, eliminating the	30 (76.2) 93 SPM need for bolt-on extensions
TYING MECHANISMS: Type Protection Capacity (twine)	Knotter Shearbolt Four balls NA	Knotter or twister Shearbolt Six balls Four coils	Knotter or twister (heavy-duty) Shearbolt Eight balls Four coils	Knotter (heavy-duty) Shearbolt Eight balls NA
MAIN DRIVE: Flywheel diameter, in. (cm) PTO Protection Gearbox	22 (56) Three-joint	22 (56) Three-jointShearbolt, overrunn oid with tapered roller bearings;	22 (56) Three-joint ing and slip clutchesheat-treated alloy steel running ir	22 (56) Three-joint
TIRES:				
Flotation (right) (left)	25x7.50-15, 6PR 27x9.50-15, 6PR	27x9.50-15, 6 PR 31x13.50-15, 6PR	27x9.50-15, 6PR 31x13.50-15, 6PR	11Lx15, 6PR 14Lx16.1, 6PR
DIMENSIONS: Height (max.), in. (cm) Width, in. (cm) Length:, in. (cm)	58 (146) 108 (275)	70 (178) 110 (279)	71 (180) 120 (304)	71 (180) 120 (304)
With 3-joint PTO and quarter-turn bale chute	240 (610)	247 (626)	247 (626)	247 (626)

New Holland BC5000 Series Small Square Baler Specifications



BC5050 BC5060 BC5070 BC5080

MODEL WEIGHT (APPROXIMATE): With three-joint PTO,	BC5050	BC5060	BC5070	BC5080
twine version, lb. (kg) With three-joint PTO, wire version, lb. (kg)	3,085 (1399)	3,400 (1542)	3,715 (1685)	4,200 (1905)
	NA	3,536 (1603)	3,851 (1746)	NA
RECOMMENDED TRANSPORT SPEED, mph (km/h)	20 (32)	20 (32)	20 (32)	20 (32)
TRACTOR REQUIREMENT* Horsepower (min.), hp (kW)	35 (26)	62 (45)	75 (56)	80 (60)

^{*}Tractor weight must be greater than baler weight; excludes bale thrower.

OPTIONS

BC5050: two- or three-joint PTO (Cat. IV); hydraulic pickup lift; hydraulic tongue swing; needle slot baffle kit; auxiliary lights; road light kit; safety chain; wagon hitch and bale loading chute; triple-purpose chute; quarter-turn bale chute; hydraformatic bale tension; ball hitch (BC5070, BC5080 only); replaceable bale chamber, hydraulic doors kit and bale case extension kit (BC5080 only); bale case extension; grass feeder kit; safety chain; two-position hitch.

Visit our Web site at www.newholland.com/na. Or, call toll-free 866-NEW-HLND (866-639-4563).

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com