New Holland TV6070 Bidirectional™ Tractor Specifications



TV6070

Rated PTO power, HP (kw)

ENGINE

Make/model

Type

Fuel Injection

Bare engine power, HP (kw)

Rated speed, RPM

Idle speed, RPM

Displacement, cu. in. (L)

Aspiration

Air cleaner

Cold start aids

Bio diesel compatibility

ELECTRICAL

Type

Batteries

Cold start rating, each, CCA

Alternator, amps

TRANSMISSION

Type

Pump

Ground speeds in ranges, MPH (KPH)

Braking

AXLES AND BRAKES

Axle type

Differential lock, cab end Differential lock, engine end

Oscillation, degrees

Brake type

Total brake area, in.2 (cm2)

Parking brake

PTO SYSTEMS

Type Shafts

Locations:

Engagement

TV6070

105 (78)

6-cylinder parent bore diesel

Bosch mechanical pump, direct injection

155 (116) 2,200

850-950

6 / 411 (6 / 6.7)

Turbocharged/air-air intercooled Dual element dry with aspirated spin tube precleaner

Grid heater/coolant block heater

Up to 100%

12v negative ground

Two group 31 low maintenance

950

120

Multi-range closed-loop hydrostatic Variable displacement, mechanical operator control

Electronically controlled 8-range variable displacement

0 to 6.7 (10.8)

0 to 7.7 (12.4) 0 to 8.3 (13.4) 3

0 to 9.1 (14.6)

0 to 10.3 (16.6)

0 to 11.6 (18.7)

0 to 16.2 (26.0)

0 to 19.5 (31.4)

Dynamic braking by moving lever to neutral position

HD flange with inboard planetary reduction

Standard

Optional

10 Wet disc in cab-end axle, hydraulic actuation

507 (3271)

Cable actuation of service brakes

Mechanical 540/1000 RPM

Interchangeable 1 3/8" diameter

Standard cab end

engine end

Optional

Electro-hydraulic

New Holland TV6070 Bidirectional™ Tractor Specifications



TV6070

TV6070 **HYDRAULIC SYSTEMS**

Standard system-type

Type Total flow @ 2200 engine RPM, GPM (LPM)

Pressure compensator, PSI (Bar) Remote valves-standard cab end

In-cab flow controls

Valve actuation

Remote valves-optional engine end

Valve actuation

Couplers

Optional auxiliary hydraulics

Maximum flow @ 2200 engine RPM, GPM (LPM)

Pressure compensator, PSI (Bar)

Couplers

35 (133) 4350 (300)

3/4" ISO, with 1/2" case drain

Category II, flex link ends and sway links

Electronic position control, auto and manual modes

6,500 (2950)

8,700 (3950)

4,000 (1800)

Hydrostatic power

45 degrees maximum

32' 10" (10.0)

CCLS with piston pump

29.5 (111)

3,000 (207)

3

Hand levers, foot pedals

Hand levers

1/2" ISO, 2 for each valve

CCLS with piston pump; electronic flow control

3-POINT HITCHES

Type Controls

Standard cab end

Lift capacity @ 24" behind links, lbs. (kg)

Optional cab end

Lift capacity @ 24" behind links, lbs. (kg)

Optional engine end

Lift capacity @ 24" behind links, lbs. (kg)

STEERING

Type

Articulation angle

Curb clearance circle, ft. in. (m)

CAB

Tinted safety glass, area, ft² (m²)

Climate control

Seat

Turnabout™ console

61 (5.67)

Pressurizer, heater/defroster, air conditioning

2-Door ROPS/FOPS

3-speed

Air suspension, 7 comfort adjustments

210 degree rotation to face either driving direction

DRAWBARS

Engine end

3-position adjustable, swinging Type Cab end

Standard

Optional

6.5 (25)

REFILL CAPACITIES

55 (208) Fuel tanks, gal. (L) Engine oil, gal. (L) 5 (19) Engine coolant, gal. (L) 7.25 (27) Hydraulic system/rear axle, gal. (L) 13.5 (51)

Front axle, gal. (L)

Visit our Web site at www.newholland.com/na. Or, call toll-free 866-NEW-HLND (866-639-4563).

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com