

The workhorse that's also a sprinter

Highlights:

PACE TO LEA.

Zero-tear capability (through any paper path) with auto-advance 610 characters-per-second print speed Letter-quality 24-pin printer Crisp, clear printing—even on 5-part forms Rated at 8,000-hour MTBF Co-resident Epson®, IBM® and MICROLINE emulations Networkable via optional Ethernet external print server Eight resident scalable barcodes and four text fonts ML395C prints in color via user-installable ribbon 1-year limited warranty, including parts, labor and printhead Toll-free, 7-day/24-hour Customer Support Hotline: 800-OKI-DATA (800-654-3282)1

¹ Available in the U.S. and Canada only.

This Tank-Tough[®] printer offers flexible forms handling and lightning-fast throughput.

The OKI® MICROLINE® 395 and four-color ML395C printers are built to deliver trouble-free reliability—with relentless, high-volume output, flexible paper handling, and swift printing speeds.

Each of its four print speeds is among the fastest in its class:

- At 610 cps, the High-Speed Draft mode blasts through spreadsheet reports in no time.
- The 485-cps Utility and 245-cps Near Letter Quality modes kick out drafts and memos at a rapid clip.
- And the 165-cps Letter Quality mode delivers crisp, clear correspondence and proposals in short order.

Use the ML395/395C's optional bottom push tractor and the bottom feed's straight-through paper path for those hard-to-handle labels, card stock, and forms with up to 5 parts. Add the top feed for single sheets and envelopes, the rear push feed for fanfold paper.

A time-saving "paper park" function lets you switch forms at the push of a button. And, for trouble-free unsupervised operation, there are optional singleor dual-bin cut sheet feeders.

The ML395 even saves paper: its zero-tear function advances a printed page to the perforation and lets you tear it off cleanly and precisely. Then it positions the next page for printing automatically.



OKI[®] MICROLINE[®] 395/395C

24-Pin Impact Printers

Getting The Job Done — With Style.

Make a lasting, professional-looking impression with the ML395/395C's four built-in, letter-quality resident fonts, eight resident bar code fonts, including USPScertified PostNet®—to save you money on mailings.

The ML395/395C lets you get up and running easily with all of today's popular software programs, and its Novell[®] compatibility makes it network-ready.

For quick attachment to a variety of systems, the printer also features parallel and serial interfaces, standard.

With the ML395C, your graphics, charts, transparencies and text presentations will sizzle in a vibrant rainbow of colors, as well as black.

For those users who demand the ultimate sharpness in their text, an optional black film ribbon works with both the ML395 and ML395C. Use it for proposals and letters that have to look their professional best.

Rugged. Dependable. Virtually unstoppable. The ML395/395C is all that and more. It comes with a printhead rated for 200 million characters. And the ML395 has an MTBF of 8,000 hours.

Ask for the fast, flexible 24-pin workhorse that's sure to be a winner in your busy office: the ML395/395C.

Specifications

Technology, Speed and Print Characteristics

- Printhead: 24-pin, (0.20 mm diameter)
- Graphics Resolution: 60 x 60 dpi (min.); 360 x 360 dpi (max.)
- Feed Rate: 10 ips
- Print Speed and Character Matrix:

Mode	LQ	NLQ	Utility	HS Draft	
Speed (in cps)	165	245	485	610	

Emulation, Interface and Memory

- Emulation: Epson® LQ 2550 and IBM® XL24E co-resident
- Interface: Standard: Parallel and RS232-C Serial; Optional: Ethernet via OkiLAN® 6020e 10/100 Base-T External Print Server or OkiLAN® 6010e 10 Base-T External Print Server; Co-ax Adapter or Twin-ax/Co-ax (3rd party)
- Memory: RAM: 4K; Interface Buffer: Max. 23K

Compatibility

• Operating Systems: Windows® XP, 2000, 98/95, 3.x and NT® 4.0; MS-DOS®; Novell® 4.x

Paper Handling

- Paper Input: Multi-Part Form, Continuous Form (non-overlap type), Cut Sheet, Card Stock, Envelopes (single feed)
- Number of Copies: Original plus 3
- Single Sheet Thickness: 0.002" to .0049" (0.05mm to 0.12mm)
- Multipart Thickness: Rear Feed: .014" (0.36mm); Bottom Feed: .02" (0.5mm)
- Paper Weight: Single Part 12 to 24 lb.; Card Stock – 100 lb. or less
- Paper Feeding: Bottom, Top and Rear
- Standard: Built-in Push Tractor (Rear Feed), Friction Feed (Top)
 Options: Pull Tractor, Bottom Feed Push Tractor, Single and Dual Bin Cut Sheet Feeders

Warranty and Reliability

- Limited Warranty: One year parts, labor, and printhead
- Linited Wallanty. One year parts, labor, and printineau
 MDTE: 0.000 hours (250/ duty/250/ hogs depait)
- MBTF: 8,000 hours (25% duty/35% page density)
 Monthly Workload: 17,000 pages at 25% duty cycle/-35% density
- Printhead Life: 200 Million characters avg. at 25% duty cycle
- Ribbon Life: 4 million characters

Environmental

- Size (WxDxH): 22.4" x 16.4" x 7.1"
- (57 cm x 41.7 cm x 18.0 cm)
- Net Weight: 37 lb. (17 kg); UPS shippable
- Power Consumption: 180 VA (max.) operating); 60 VA idle
- Electrical: 120V, 220/240V (+10%, -15%)
- Frequency: 50/60 Hz (±2%)
- Operating Temperature: 41° F to 104° F (5° C to 40° C) @ 20% to 80% relative humidity
- Acoustic Noise: 58dBA LQ mode; 56dBA Quiet mode

Ordering Information (Part Number)

ordering information (Fart Number)	
Printer	
MICROLINE 395 - 120V	62410501
MICROLINE 395 - 220//240V	62410502
MICROLINE 395C – 120V	62410601
MICROLINE 395C - 220//240V	62410602
Accessories	
Single Bin Cut Sheet Feeder	70010601
Dual Bin Cut Sheet Feeder	70010701
Pull Tractor Kit (with acoustic cover)	70011701
Bottom Feed Push Tractor Kit	70021601
OkiLAN® 6010e 10 Base-T Ethernet	
External Print Server	70034401
OkiLAN® 6020e 10/100 Base-T Ethernet	
External Print Server	70036001
Ribbons:	
Black Cartridge	52103601
Color Cartridge	52103701
Black Film Cartridge	52103801
Self-inking Ribbon Cartridge	42377801
Co-ax Adapter	70047201
Twin-ax/Co-ax (Also available through Third Party. Call 1-800-OKI-DATA.)	
OKIcare [®] Overnight Exchange	
Warranty Extensions ¹	
U.S. OKI SIDM Desktop 1-Yr. Warranty Ext. 58251901	Canada 58251911
	00201011

OKI SIDM Desktop 2-Yr. Warranty Ext. 58252001 58252011

 OKIcare® Depot Warranty Extensions

 U.S.
 Canada

 OKI SIDM Desktop 1-Yr. Warranty Ext.
 58251001
 58251011

 OKI SIDM Desktop 2-Yr. Warranty Ext.
 58251101
 58251111

 Desktop Upgrade to Overnight Exchange
 58251801
 58251811

For more information on OKI Impact Printers and supplies, including OKIcare® Extended Service Programs: 1-800-0KI-DATA (800-654-3282).

¹ Available in U.S. and Canada only.

All specifications subject to change without notice.

© 2004 Oki Data Americas, Inc. Oki, MICROLINE, OkiLAN Reg. T.M., Oki Electric Industry Co., Ltd. Command Performance, 7-Day/24-Hour logo T.M., Oki Data Americas, Inc. Epson Reg. T.M., Seiko Epson Corp. IBM, Reg. T.M., International Business Machines Corp. Windows, Windows NT, MS-DOS, Reg. T.M., Microsoft Corp. PostNet, Reg. T.M., USPS. Swiss, T.M., Bitstream, Inc. Energy Star Reg. T.M., U.S. EPA.



To contact Oki Data Americas, Inc. In USA: 2000 Bishops Gate Blvd. Mount Laurel, NJ 08054-4620 Tel: 800.0KI.DATA (800.654.3282) Fax: 856.222.5320

In Canada: 2735 Matheson Blvd. East Mississauga, Ontario L4W 4M8 Tel: 905.238.4250 Fax: 905.238.4421

Network Solutions Oki. for a Global Society

In Latin America and Mexico: 2000 Bishops Gate Blvd. Mount Laurel, NJ 08054-4620 Tel: 856.231.0002 Fax: 856.222.5071



Printed in the USA



www.okidata.com 800.0KI.DATA

Download from Www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com