ES2232a4/ES2632a4



Colour is an essential business tool today – adding impact and style to documents. The ES2232a4 and ES2632a4 produce the professional print quality output needed, whilst keeping colour usage and costs in check, making the ES2232a4 and ES2632a4 a highly affordable print solution from the business printing specialists. Take the next step.

Handles different needs and media

- Handles a wide range of paper sizes (A6–A4, plus banners) in weights from 64gsm up to 203gsm
- Template Manager provides easy to use templates for non-standard media such as business cards, CD labels, address labels and banners

Highest speed. Highest quality

- Fast print speed of up to 26ppm colour and 32ppm mono
- Superior print quality thanks to unique combination of ProQ2400 Multi-level technology and microfine toner
- Enjoy a better level of detail, greater colour depth, reduced grain and a high gloss feel
- Graphic Pro allows downloading of colour profiles to the optional Hard Disk Drive (HDD) for exact colour matching
- Duplex facility (optional on ES2232a4) for double-sided printing and saving paper

Restrict access. Protect data

- Safeguard confidentiality and prevent unauthorised or excessive usage
- Easy to monitor and control printing costs
- Print Control imposes rules on how the printer is used
- Secure Erase can securely delete all details of a job with the optional Hard Disk Drive

So simple to use. So easy to produce great results

- User friendly print driver with easy to follow instructions
- Toner gauge on LCD panel shows toner status at all times
- Auto Color Balance ensures consistent results throughout the life of the printer

Handles the demands of the busy workgroup

- Solid, dependable, business printer from the business printing specialists
- Award-winning single-pass digital LED printing
- Fewer moving parts means a more reliable machine
- Keeps the work flowing, smoothly handling a diverse range of media

THE ES2232a4 & ES2632a4 FEATURES AT A GLANCE

	ES2232a4	ES2632a4
Colour print speed (A4)	22ppm	26ppm
Mono print speed (A4)	32ppm	
Printer language	PCL/PostScript	
Print quality	ProQ2400 Multi-level technology	
Memory	256MB	
Duplex (for double-sided printing)	0	•

EXECUTIVE SERIES

CREATED BY OKI PRINTING SOLUTIONS

The ES2232a4 & ES2632a4 Colour and Mono Printers

Speed and throughput
Time to first print 11 seconds colour, 8 seconds mono 9 seconds colour, 8 seconds mono Warm up time up to 60 seconds from power on & up to 45 seconds from power save Processor speed 500MHz Print Quality Resolution ProQ2400 Multi-level technology, 1200 x 600dpi Enhancements Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers) Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts . OCR-A/B; USPS ZIP Barcode Compatibility Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-
Warm up time up to 60 seconds from power on & up to 45 seconds from power save Processor speed 500MHz Print Quality Resolution ProQ2400 Multi-level technology, 1200 x 600dpi Enhancements Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers) Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts . OCR-A/B; USPS ZIP Barcode Compatibility Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Print Quality Resolution ProQ2400 Multi-level technology, 1200 x 600dpi Enhancements Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers) Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts . OCR-A/B; USPS ZIP Barcode Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Print Quality Resolution ProQ2400 Multi-level technology, 1200 x 600dpi Enhancements Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers) Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts . OCR-A/B; USPS ZIP Barcode Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Enhancements Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers) Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Typefaces Printer fonts Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts . OCR-A/B; USPS ZIP Barcode Compatibility Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Compatibility Printer languages PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5 Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Connectivity Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-
OS Compatibility¹ Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (6-bit)
Barcode support Barcode with Checksum support
Utility Suite¹ Color Correct, OKI LPR (Windows only), PrintSuperVision.net (Windows only), Color Swatch, Template Manager (Windows only) Web Driver Installer (Windows only), WebPrint (Windows only), Print Control Server (Windows only), Print Control Client, Storage Device Manager* (Windows only), Color Gamma, Profile Assistant*
Memory Std RAM 256MB
Max RAM 768MB
Hard Disk Drive 40GB (Optional)
Paper handling Paper capacity 300 sheets of 80gsm. Paper sizes: A4, A5, B5, A6
Paper capacity 530 sheets of 80gsm. Paper sizes: A4, A5, B5 optional paper tray
Paper capacity of 100 sheets of 80gsm. Paper sizes: A4, A5, B5, A6; 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, Multi-purpose tray Custom Size (up to 1200mm length including Banner); 50 transparencies
Max paper capacity (including optional paper tray) 930 sheets of 80gsm
Duplex paper sizes A4, A5, B5; Custom Size: Width 148–215.9mm, Length 210–355.6mm
Paper weight 64–120gsm; 64–176gsm Additional tray; 75–203gsm Multi-purpose tray; 75–105gsm Duplex
Paper output 250 sheets face down, 100 sheets face up, 80gsm
Operating conditions Temperature/Humidity 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
Storage -10°C to 43°C, 10% to 90% RH
Power requirements Power supply Single phase 220–240VAC, frequency 50/60Hz +/-2%
Power consumption Typical 490W, Peak 1200W, Idle 100W (average), Power save <17W
Noise level Operating: Up to 55.6 dB(A), Standby: 37 dB(A), Power Save: Background Level
Dimensions (HxWxD) 339.5mm x 400mm (max 435mm) x 528mm (max 563.5mm) 339.5mm x 400mm (max 435mm) x 621mm
Weight ² Approx 26kg Approx 29kg
Accessories Duplex Optional Standard
Memory Optional 256MB, 512MB
2nd paper tray Optional
Hard Disk Drive Optional 40GB
Cabinet Optional

- $^{\scriptscriptstyle 1}$ Check local OKI Executive Series website for latest driver releases and OS compatibility
- $^{\scriptscriptstyle 2}$ Includes all consumables
- * Hard Disk Drive required

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

 $Specification\ subject\ to\ change\ without\ notice.\ All\ trademarks\ acknowledged.$

OKI EUROPE LTD.

Central House, Balfour Road Hounslow, Middlesex TW3 1HY United Kingdom T+44(0) 20 8219 2190

F+44(0) 20 8219 2199

WWW.OKIEXECUTIVESERIES.COM





Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com