



Use the 5x sportzoom and catch all the excitement, no matter where you're sitting.

5x SportZoom Bring the action 5 times closer with this compact camera. With its 5x sportzoom, 20x total zoom capability and 5.1 megapixel CCD you can create perfect images with all of the details.

2.0" LCD This large screen lets you evaluate your shots and make adjustments more easily.

TruePic TURBO™ Image Processor Exclusive Olympus technology enables smoother, more accurate images, even at low resolutions – with accelerated processing, startup and shutter release times.

15 Selectable Shooting Modes Adapt instantly to any shooting situation, including beach and snow, landscapes, portrait, sport, nighttime – anytime.

Full-Function Control P-Auto, Aperture Priority, Shutter Priority and full manual control let you change your camera setting to achieve beautiful photos under any circumstance.

High-speed Sequential Shooting With a fast 2.7 frames-per-second shooting capability, you can take as many shots as you wish, as quickly as you can.

Histogram Chart in Shooting Mode By viewing exposure information created by the histogram function, you can adjust your aperture and shutter settings to create picture-perfect images.

“Anti-Shake” in Movie Mode Reduce the effects of constant shaking while taking your pictures.

QuickTime® Movie Mode with Audio Bring your movies to life, then e-mail them to family and friends.

Direct Print Capability Use the included USB cable and connect to any PictBridge™-enabled printer – the Olympus P-10, for example – and start printing. No computer necessary.



Get closer to the action. This camera offers a powerful 5x sport zoom, 20x total zoom capability and the high resolution of a 5.1 megapixel CCD. Enhancements include a new “anti-shake” feature for improved viewing of QuickTime® movies, 15 selectable shooting modes plus full-function control, our exclusive TruePic TURBO™ Image Processor for consistent contrast and detail – and fast, sequential shooting capability (2.7fps). Auto-connect USB for image/movie transfer. And PictBridge for quick, easy printing.



Megapixel 5.1 Effective	Optical 5x Zoom	Total Zoom 20x Optical & Digital	Auto-Connect USB 2.0	QuickTime
--------------------------------------	------------------------------	---	-----------------------------------	-----------

Olympus® C-5500 SportZoom Specifications

Stock No. 225605

Imager:	5.1 megapixel effective, 5.3 megapixel gross, 1/1.8" CCD
Lens:	7.9 - 39.5mm (38 - 190mm equivalent in 35mm photography), 9 lenses in 7 groups
Zoom:	Seamless to 20x (5x optical and 4x digital combined)
Aperture Range:	f2.8-f4.8 to f8.0 (1/3 EV step)
LCD:	2.0" (50cm) TFT LCD, approx. 110,000 pixel
Viewfinder:	Real image optical viewfinder
Focus System:	CDD Contrast detection
Focus Range:	Wide: 1.9' (0.6m) - infinity, Tele: 3.9' (1.2m) - infinity Macro mode: Wide: 3" (0.08m) - 1.9' (0.6m), Tele: 1.9' (0.6m) - 3.9' (1.2m) Super Macro: .07" (0.02m) - 3" (0.08m) (Wide only)
Focus Mode:	iESP auto, Spot AF
Shutter Speed:	1/1500 sec. - 15 sec.
Shutter Lag Speed:	0.4 second
Start-Up Time:	1 second
ISO:	Auto, 100, 200 and 400 (equivalent)
Metering Mode:	Digital ESP, Spot
White Balance:	iESP2 multi-pattern auto TTL, Pre-set (Daylight, Overcast, Tungsten, Fluorescent-1, Fluorescent-2, Fluorescent-3), WB compensation +/- 7
Exposure Compensation:	±2 EV steps in 1/3 steps
Recording Modes:	DCF Exif2.2, JPEG
Adjustment Resolutions:	2592 x 1944, SHQ / HQ / 3.2 2592 x 1728, SHQ (3.2) / HQ (3.2) 2288 x 1712, HQ 2048 x 1536, SQ1 1600 x 1200, SQ1 / SQ2 1280 x 960, SQ2 1024 x 768, SQ2 640 x 480, SQ2
Shooting Modes:	15 shooting modes; P, A, S, M, Scene Preset (Portrait, Sports, Landscape, Night Scene, Picture for Keepsake, Beach & Snow, Fireworks, Sunset, Candle, Available Light Portrait), Movie
Panorama:	Up to 10 frames automatically stitchable with Olympus Master software when using Olympus brand xD-Picture Card™
Custom Settings:	4 My Mode

Sequential Shooting:	High-speed: 2.7 frames per second up to 5 frames Normal speed: 1.4 frames per second up to 10 frames in HQ mode; in default recording mode Black and White, Sepia (Adj. ±5) sharpness, contrast, color phase
Shooting Edit Effects:	QuickTime® Movie with Sound, QVGA 30fps with Digital Image Stabilization
Image Quality Adjustment:	TruePic TURBO™
Movie Mode:	Automatic Pixel Mapping (APM) available via menu setting Mode available at shutter speeds of 0.5 second or longer set automatically
Image Processing:	Still Image: Index display (4,9;16), Enlargement Up to 5x, Slide-show (Standard, Fade, Slide Zoom), Histogram, Rotation, Calendar
Pixel Mapping:	Movie: Normal, Fast Forward, Frame-by-frame
Noise Reduction:	Still Image: Resize, Trimming, Red-Eye Fix Movie: Frame Edit, Frame Index, Frame Capture
Image Playback:	PictBridge™ and DPOF Built-in, Pop-up Auto, Red-eye Reduction, Fill-in Wide: 12.5ft (5m); Tele 7.2ft. (3.5m)
Playback Edit Effects:	12 seconds/by Remote Control; Auto, 3 seconds On/Off (hold changes/Reset to default settings)
Direct Printing Options:	Simultaneous recording into image data, Automatic up to 2099
Flash:	xD-Picture Card™ (16, 32, 64, 128, 256, 512MB, or 1 GB)
Flash Modes:	USB connector (Auto-Connect), Audio/Video, and DC input
Flash Working Range:	2.0 Full Speed
Self-timer:	Windows 98/98SE, 2000 Pro/ME/XP, Mac® OS 10.2 and higher
Settings Memorization:	Operation: 32° - 104°F (0° - 40°C), 30 - 90% humidity
Date/Time Calendar:	Storage: -4° - 140°F (-20° - 60°C), 10 - 90% humidity
Removable Media Card:	4 AA Batteries
Outer Connectors:	Power Supply:
Auto-connect USB:	Battery Life (Shots):
System Requirements:	Size:
Operating Environment:	Weight:

Available Accessories

Product Number	UPC 050332-	Accessory
200899	297753	B-90SU NiMH 4 AA Rechargeable Batteries and Quick Charger Set
200728	133723	B-01 4PE Ni-MH Battery (4 battery cells)
200656	131347	LB-01 CR-V3 Lithium Battery 2 pack
200616	128088	LB-01 CR-V3 Lithium Battery 1 pack
200685	294707	C-7-AU AC Adapter Blister Pack (Digital Cameras that use 4 AA batteries)
200841	139091	32MB xD-Picture Card™
200842	139107	64MB xD-Picture Card™
200843	139114	128MB xD-Picture Card™
200844	139565	256MB xD-Picture Card™
200859	142558	512MB xD-Picture Card™
200837	139152	MACF-10 xD to CF Card Adapter
200835	139145	MAPC-10 PCMCIA xD-Picture Card™/SmartMedia™ Adapter
200830	139138	MAUSB-10 Dual Slot USB xD-Picture Card™/SmartMedia™ Reader/Writer
200335	153738	MAUSB-300 xD Picture Card™ USB Reader/Writer
200891	144422	MAUSB-100 xD USB Reader/Writer
200845	296473	xD-Picture Card™ Wallet
200784	295643	Digital Camera Gadget Bag
200860	296589	Deluxe Digital Imaging Kit
200494	298514	Digital Essentials Accessory Kit
200893	297883	2-Year Extended Digital Warranty C, D & Stylus Series
200776	136205	CB-USB4 Digital Camera USB Cable
200667	132009	CB-AVC1 Digital Camera Audio/Video Cable

Package Contents

C-5500 SportZoom Camera	Basic Instruction Manual
16MB xD-Picture Card™	Quick Start Guide
Wrist Strap	Warranty Card
Multi-terminal for USB & Audio/Video Out	CD-ROM: Olympus® Master Software and Advanced Manual
4 AA Batteries	

OLYMPUS SCHOOL OF DIGITAL PHOTOGRAPHY

The Olympus School of Digital Photography is a one-day workshop covering everything from digital image capture to final output. To register, visit www.olympusphotoschool.com or call 1-800-645-8100 x6161.



Olympus Digital Still Cameras can be used with confidence wherever you go. They are backed by a one-year repair warranty service that is available worldwide. Please contact our service center or check the Authorized Distributors list for service and applicable areas of service. May not be available in all areas.

Specifications subject to change without notice or obligation on the part of the manufacturer.

© 2005 Olympus Imaging America Inc. All rights reserved. Printed in the United States of America. Olympus is a trademark or registered trademark of Olympus Corporation, Olympus Imaging America Inc. or their affiliated entities. All trademarks and registered trademarks listed herein are the property of their respective holders. D1220-0105

Memory Card Storage Capacity

	Quality	Pixel Resolution	16MB xD-Picture Card™ (Included)	512MB xD-Picture Card™
Still Images (w/o sound) Unit: shots	SHQ	2592 x 1944	4 shots	139 shots
	HQ	2592 x 1944	12 shots	409 shots
	SHQ1	2592 x 1728	4 shots	156 shots
			14 shots	456 shots
	SQ1	2288 x 1712	5 shots	178 shots
			16 shots	523 shots
	SQ1	2048 x 1536	6 shots	221 shots
			20 shots	652 shots
	SQ1	1600 x 1200	11 shots	363 shots
			32 shots	1030 shots
	SQ2	1280 x 960	17 shots	560 shots
			49 shots	1597 shots
	SQ2	1024 x 768	26 shots	863 shots
			76 shots	2457 shots
SQ	640 x 480	66 shots	2129 shots	
		165 shots	5324 shots	
Still Image (w/ sound) Unit: shots	SHQ	2592 x 1944	4 shots	138 shots
	HQ	2592 x 1944	12 shots	399 shots
	SHQ	2592 x 1728	4 shots	155 shots
	HQ	2592 x 1728	13 shots	443 shots
	SQ1	2288 x 1712	5 shots	176 shots
			15 shots	507 shots
	SQ1	2048 x 1536	6 shots	218 shots
			19 shots	626 shots
	SQ1	1600 x 1200	11 shots	354 shots
			30 shots	968 shots
	SQ2	1280 x 960	16 shots	541 shots
			45 shots	1452 shots
	SQ2	1024 x 768	25 shots	819 shots
			66 shots	2129 shots
SQ	640 x 480	58 shots	1879 shots	
		124 shots	3993 shots	
Movie (w/o sound) Unit: min.	HQ	320 x 240	24 sec.	774 sec.
	SQ	320 x 240	48 sec.	1548 sec.
Movie (w/ sound) Unit: min.	HQ	320 x 240	23 sec.	762 sec.
	SQ	320 x 240	46 sec.	1503 sec.

All capacity figures are approximate.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>