



* IS1100NR / IS1700NR / IS2500NR / IS3500NR

IS1100NR / IS1700NR / IS2500NR / IS3500NR

Features

- * Wide DC input range
- * Output short circuit protection
- * DC input polarity protection
- * Sine Wave output
- * Designed for any kind of load
- * Adjustable low battery shutdown level
- * Automatic restart of load after overload shutdown
- * Audible alarm
- * Thermal control cooling fan
- * Generator compatible(models with AC input)
- * Smart Bypass function (models with AC input)
- * Full function of LCD display

Specifications

Model	IS1100NR	IS1700NR	IS2500NR	IS3500NR
On-battery Output Waveform	Pure Sine Wave			
Crest Factor	5 : 1			
INPUT				
Maximum Capacity	1000VA / 700W	1700VA / 1200W	2500VA / 1800W	3500VA / 2400W
Nominal Input Voltage	100/110/115/120Vac (selectable) or 200/220/230/240Vac (selectable)			
Nominal Input Frequency	47Hz ~ 65Hz, 50/60Hz auto-sensing			
Input Voltage Range	-30% ~ +33% for selected nominal voltage.25:25			
OUTPUT				
Nominal Output Voltage	100/110/115/120Vac (selectable) or 200/220/230/240Vac (selectable)			
Output Voltage Regulation (DC Mode)	±3% (output voltage adjustable by using the remote set-up software)			
Transfer Time	2ms			
Start on Battery	Yes			
Auto Restart	Yes			
PROTECTION				
Automatic Voltage Regulation (AVR)	Yes (2 Bucks, 2 Boosts)			
Data Line Surge Protection	RJ45			
Surge Energy Rating	1000VA(216 Joules); 1700VA ~ 3500VA(324 Joules) 1000VA(220 Joules); 1700VA/2500VA(440 Joules); 3500VA(660 Joule)			
BATTERY				
DC Voltage	24Vdc(20Vdc ~ 32Vdc) : 1000VA / 1700VA 48Vdc(40Vdc ~ 64Vdc) : 1000VA / 1700VA / 2500VA / 3500VA 72Vdc(60Vdc ~ 96Vdc) : 1700VA / 2500VA / 3500VA 96Vdc(80Vdc ~ 128Vdc) : 1700VA / 2500VA / 3500VA 108Vdc(90Vdc ~ 144Vdc) : 1700VA / 2500VA / 3500VA			
ADVANCED WARNINGS / DIAGNOSTICS				
Control Panel	LCD			
Audible Alarms	Alarm on battery : Low battery & Battery over voltage Alarm on abnormal operation : Over load, Short-circuit, & Over heat			
COMMUNICATIONS INTERFACE				
Communication Port	RS232 + USB Port			
ENVIRONMENTAL				
Operation Temperature	0~40°C / 32~104°F			
Storage Temperature	-15~55°C / 5~131°F			
Audible Noise (AC Mode)	≤ 50dBA			
PHYSICAL				
Dimensions (Physical / Packing)	(in) 17.7×17.7×5 / 23.2×23.2×13 (mm) 450×450×126 / 590×590×330			
Weight (Net / Gross)	44.1 / 52.9 (lbs) (kg) 20 / 24	57.3 / 66.1 (lbs) (kg) 26 / 30	75 / 83.8 (lbs) (kg) 34 / 38	

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>