

Value Series

For personal computers and SOHO

VS375C / VS400C / VS575C / VS600C / VS1000C



* VS400C
VS600C



* VS375C
VS575C

VS375C / VS400C / VS575C / VS600C

The VSC Series are perfect for your personal and small office computers. They protect systems against blackouts, sags, and surges. The smallest and lightest in its class, this high frequency and high efficiency UPS provides complete protection for a workstation and its peripherals.

Features


- * 3 UPS outlets + 3 surge protected outlets
- * Integrated protection for telephone / modem / LAN card
- * Cold start capability
- * 1050 Joules surge energy rating

- * RS232 communication port
- * Easy battery replacement
- * 4 hours recharge time
- * Smart power management software
- * Auto restart & self-diagnostics

Backup Time (Typical)

Model	Configuration	Backup Time
VS375C	1PC+1LCD	8 mins
VS400C	1PC+1LCD	9 mins
VS575C	1PC+1LCD	11 mins
VS600C	1PC+1LCD	12 mins

Front Panel




- A) ON / OFF, TEST / SILENCE
- B) AC Mode
- C) Battery Mode
- D) Battery Fault


Specifications

Model Name	VS375C / VS400C	VS575C / VS600C
Topology	Standby	
On-battery Output Waveform	Simulated Sine Wave	
INPUT		
Maximum Capacity	375VA / 225W	575VA / 345W
Nominal Input Voltage **	100 / 110 / 120Vac or 220 / 230 / 240Vac	
Nominal Input Frequency	50Hz / 60Hz Auto Sensing	
Input Voltage Range	Rated Voltage +/- 20%	
Input Short Protection	Fuse	
OUTPUT		
Nominal Output Voltage	100 / 110 / 120Vac or 220 / 230 / 240Vac	
Output Voltage Regulation	Rated Voltage +/- 5% (on battery)	
Transfer Time	4 ms (typical)	
Number of Outlets	3 Battery backup + 3 Surge (US) 3 Battery backup + 3 Surge (IEC)	
PROTECTION		
Data Line Surge Protection	RJ11 / RJ45	
Surge Energy Rating	1050 Joules	
Normal Mode Noise Suppression	Full time EMI/RFI filtering	
BATTERY		
User Replaceable Battery	12V / 3AH x 1	12V / 3.8AH x 1
Recharge Time to 90%	< 4 Hours	
COMMUNICATIONS INTERFACE		
Communication Port*	RS232	
ENVIRONMENTAL		
Operation Temperature	0°~40°C / 32°~104°F	
Storage Temperature	-20°~60°C / -4°~140°F	
Audible Noise	< 40dBA	
PHYSICAL		
Dimensions (Physical / Packing)	(in) 7.9 x 3 x 6.9 / 9.6 x 5 x 9.8	
(L x W x H)	(mm) 200 x 77 x 175 / 248 x 127 x 250	
Weight (Net / Gross)	(lbs) 5.1 / 6.4	
	(kg) 2.3 / 2.9	
CONFORMANCE		
Approvals	BSMI ; CE UL / cUL ; C-Tick , A-Tick ; GOST-R	

Rear Panel



- 100V
- 110V
- 120V



- 220V
- 230V
- 240V

Specifications are subject to change without notice.
* You can purchase RS232 to USB cable.
** See VS1000C on page 6



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>