

Surge Buster Series

For home appliances, TV, stereo systems, computer equipment

SBGH-721 / SBGL-600 / SBFH-721 / SBAH-821 /
SBAL-600 / SBUH-721 / SBUL-500



* SBGL-600



* SBFH-721



* SBGH-721

SBGH-721 / SBGL-600 / SBFH-721

To protect your valuable electronic devices from troubles caused by power disturbances, OPTI-UPS offers you its Surge Buster Series.

Power problems actually lead in numerous cases to the damage of your equipment and to data loss, both being extremely costly. Regardless of a strike of lightning, fluctuations in your main current (caused by alternating power demands in your local area), unstable current or poor power quality, you can always count on your Surge Buster.

Easy handling, fancy design and full protection, for a reasonable price, make the Surge Buster Series a must for every home. Over one decade in the UPS business, the name OPTI-UPS has become synonymous with uncompromising performance and reliability. Whatever your needs are in power supply, we will be there to protect and serve your equipment.

Features - SBGH-721 / SBFH-721

- * Power Rating: 10A, 250VAC
- * With 1-pole rocker switch
- * With 10 Amp circuit breaker
- * With children safety shutters
- * With Combo Jacks provide TEL / FAX / Modem or Network protection (Cat.5, 10/100 Base-T)
- * With Coax / DSS Protection
- * Heavy duty power cord—1.8meters, H05VV-F, 3G, 1.0mm2 with right angle plug

Features - SBGL-600

- * Power Rating: 10A, 250VAC
- * With 1-pole rocker switch
- * With 10 Amp circuit breaker
- * With children safety shutters
- * Heavy duty power cord—1.8meters, H05VV-F, 3G, 1.0mm 2 with right angle plug

Specifications

Model Name	SBGH-721	SBGL-600	SBFH-721
Outlets Number	7	6	7
Outlets Type	German Type		French Type
Electrical Rating	10A, 250VAC, 2500W		10A, 250VAC
Surge Energy Joule Rating	3444 J	238 J	714 J
Surge Protection Mode	L-N, L-G, N-G	L-N	L-N, L-G, N-G
Clamping Voltage	710 V		775V
Max. Peak Spike Current	144000A	6500A	19500A
Max. Spike Voltage		6kV	
EMI/RFI Noise Filter	Frequency	150 kHz~100 MHz	150 kHz~100 MHz
	Attenuation	Up to 40 dB	Up to 40 dB
	Jack Type	Aerial Type	Aerial Type
DSS/COAX Cable Protection	Breakdown Voltage	< 75 V	< 75 V
	Insertion Loss	< 0.1 dB	< 0.1 dB
	Surge Arrestor	Gas Tube	Gas Tube
TEL/FAX/MODEM Protection	Jack type	RJ45/8P8C (1in/1out) + RJ11/6P2C (1out)	RJ11/6P2C (1 in / 2 out)
	Energy	160J	320J
Line Protection	1 Line	N/A	2 Line
Surge Protected Indicator	Orange	N/A	Orange
Ground OK Indicator	Green	N/A	Green
Power OK Indicator	N/A	N/A	N/A
Surge Circuit Shut Down	Yes	Yes	Yes
Power Safety Shut Down (L-N)	Yes	Yes	Yes
Accessories	N/A	N/A	N/A

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>