
TX775

The Sleek & Complete Solution




- Bright 3500 ANSI lumens with a 2300:1 contrast ratio
- New form factor allows for easy replacement of lamp
- Native XGA (1024 x 768) with support up to SXGA+ (1400 x 1050)
- Designed to integrate cleanly into installations or conference room settings
- Fully featured remote control with laser and mouse controls
- Recessed focus and zoom controls prevent accidental adjustments





I/O Ports







Specifications

Display Technology:	Single 0.7" DDR DLP® Technology by Texas Instruments				
Resolution:	XGA (1024 x 768)				
Maximum Resolution:	SXGA+ (1400 x 1050)				
Brightness (Typical):	3500 Lumens				
Contrast Ratio:	2300:1 (Full On/Full Off)				
Lamp Life (STD/ECO):	2000/3000 Hours				
Lamp Type:	230W SHP				
Throw Ratio:	1.8-2.1:1 (Distance/Width)				
Image Size (Diagonal):	27.5" to 306" (0.7 to 7.8 m)				
Noise Level (STD/ECO):	33dB/31dB				
Remote Control:	Fully Featured IR Remote w/ Laser Pointer and Mouse				
Monitor Loop Through:	D-Sub 15 VGA Output (Functional in Both Normal and Standby Modes)				
Projection Distance:	3.2' to 32.8' (.08 to .83m)				
Computer Compatibility:	XGA, SVGA, VGA, SXGA+ Resized, VESA, PC and Macintosh Compatible				
Video Compatibility:	NTSC, PAL, SECAM, EDTV (480p), HDTV (576i/p, 720p, 1080i)				
Aspect Ratio:	4:3 Native, 5:4 &16:9 Compatible				
Projection Lens:	F=2.6~2.81, f=26.01~29.84mm, 1.15:1 Manual Zoom and Focus				
Audio:	One Internal 2-Watt Speaker				
Weight:	7.3 lbs (3.3 kg)				
Dimensions (W x H x D):	11.81" x 3.46" x 9.61" (300 x 100.5 x 244 mm)				
Keystone Correction:	± 15° Vertical				
Horizontal Scan Rate:	31 to 90 kHz				
Vertical Refresh Rate:	50 to 85 Hz				
Power Supply:	AC Input 100 - 240V, 50-60Hz				
Power Consumption:	295 Watts, <5W Standby Power				
Operating Temperature:	Operating: 5 to 35°C, 80% Humidity (Max) Storage: -20 to 60°C, 80% Humidity (Max)				
Displayable Colors:	16.7 Million, 256 Shades of Gray				
Projection Method:	Front, Rear, Ceiling Mount, Table Top				
Uniformity:	85%				
Security:	One Kensington® Lock Port				
User Controls:	Advanced Adjustability Options through the On-Screen Display				
I/O Connectors:	VGA-In, DVI w/HDCP, Composite Video, S-Video, Two Audio-In (RCA & Mini-Din), USB, RS-232, VGA-Out, Audio-Out, +12V Trigger				
Standard Accessories:	AC Power Cord, VGA to VGA Cable, RS-232 Cable, Composite Video Cable, Remote Control, Batteries for Remote, CD-ROM User's Manual, Quick Start Guide, Warranty Card, Lens Cap and Carrying Case				
Optional Accessories:	Bering Ceiling Mount, DVI to HDMI Adapter, DVI to HDMI Cable, DVI Cable and GrayWolflI™ Series Screens				
Warranty:	3 Years Optoma Express Replacement Service, 1 Year on Lamp				
UPC:	796435 11 126 7				

Available from:			





Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com