



HHR200A Cylindrical 4/5A size (HR17/43)

S type

■ Dimensions (with tube) (mm)



■ Typical charge characteristics



■ Specifications

Diameter	17.0+0 / -0.7mm
Height	43.0+0 / -1.5mm
Approximate Weight	32g



Nominal Voltage		1.2V
Discharge Capacity	Average ^{*1}	2040mAh
	Rated (min.)	2000mAh
Approx. Internal impedance at 1000Hz at charged state.		20m Ω
Charge	Standard	200mA X 16hrs.
	Rapid	1700mA X 1.4hrs.
Ambient Temperature	Charge	Standard: 0°C to 45°C Rapid: 0°C to 40°C
	Discharge	-10°C to 65°C
Storage	<1 year	-20°C to 35°C
	<3 months	-20°C to 45°C
	<1 month	-20°C to 55°C

*1 After charging at 0.1It for 16 hours, discharging at 0.2It.

*2 For reference only.

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and unit design.

■ Typical discharge characteristics



*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>