

***DIMENSIONS (H x W x D):***

25" x 17.75" x 12.563"
63.5 cm x 45.085 cm x
31.910 cm

WEIGHT:

39 lbs. (17.7 kg)

▲ MOUNTING OR SUSPENSION:

1-3/8" pole-mount cup for
stand mounting

FEATURES:

- Two-way sound reinforcement monitor enclosure
- 30° and 45° dual-angle monitoring
- Peavey-exclusive Sheffield Pro 1500+ woofer with 2.5" voice coil
- 1.4" 14XT™ titanium diaphragm compression driver
- Sound Guard IV tweeter protection
- 500 Watt program/1000 Watt peak power handling
- Heavy duty crossover network for driver protection and EQ
- Lightweight trapezoidal enclosure
- 90° x 40° coverage constant directivity horn for better off-axis tonality
- High quality, heavy duty carpet covering
- Steel handle
- Rugged dado and rabbet construction for lightweight-yet-strong joints
- T-Nut speaker mounting
- Heavy duty, full-length steel grille
- Pole mount included

FREQUENCY RANGE (-10 dB, HALF SPACE):

58 Hz to 21 kHz

FREQUENCY RESPONSE (±3 dB, HALF SPACE):

79 Hz to 17 kHz

SENSITIVITY (1W/1M):

98 dB

POWER RATING (PROGRAM):

500 Watts

POWER CAPACITY (PEAK):

1000 Watts

MAXIMUM SPL:

127 dB

TRANSDUCER COMPLEMENT:

Sheffield[®] Pro 1500+™ 15" premium woofer and 14XT™ 1.4" titanium diaphragm dynamic compression driver on a 90° x 40° coverage constant directivity horn

DRIVER PROTECTION:

Sound Guard™ IV for the compression driver provides long- and medium-term overload and overdrive protection

NOMINAL COVERAGE PATTERN:

90° x 40°

ELECTRO-ACOUSTIC CROSSOVER***FREQUENCY:***

2.8 kHz

NOMINAL IMPEDANCE:

8 Ohms

INPUT CONNECTIONS:

Two 1/4" phone jacks in parallel

ENCLOSURE MATERIALS AND***FINISH:***

Trapezoidal, black carpet-covered enclosure with dado joined 1/2" MDF (Medium Density Fiberboard) and a full-length, black powder-coated steel grille



SPECIFICATIONS PV[®] 15M

DESCRIPTION

The PV 15M is a two-way floor monitor utilizing a Pro 1500+ woofer and a 14XT titanium diaphragm dynamic compression driver mounted on a 90° x 40° coverage constant-directivity horn. This lightweight-yet-rugged, carpet-covered monitor enclosure with stand-mount cup facilitates portable use as a stage monitor or other sound reinforcement applications. The dual-angle enclosure provides a choice of 30°

and 45° monitoring angles for full monitoring utility. A full-length, black powder-coated steel grille provides driver protection and a professional appearance.

The PV 15M speaker system is rated at 500 Watts program power handling, and the full crossover network includes high voltage film capacitors and Sound Guard™ IV tweeter protection for clear, punchy sound and excellent long-term reliability. Two 1/4" phone

jack input connectors make hook-up and daisy-chaining to other monitors a breeze.

3 + 2 YEAR LIMITED WARRANTY

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898.




Figure 1



Logo referenced in Directive 2002/95/EC Annex IV
RO 0317/38, 13.02.03 and defined in EN 50419: 2005
The bar is the symbol for marking of new waste and
is applied only to equipment manufactured after
13 August 2005

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 711 A Street • Meridian • MS • 39301 (601) 483-5365 • FAX (601) 486-1278 • www.peavey.com

©2005

EX000035



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>