

**Dimensions (H x W x D):**

25" x 17.75" x 12.563"
63.5 cm x 45.085 cm x
31.910 cm

Weight:

43 lbs. (19.54 kg)

**Mounting or suspension:**

Die-cast aluminum 1-3/8" pole-mount cup for stand-mounting

Features:

- Two-way sound reinforcement monitor enclosure
- 30° and 45° dual angle monitoring
- Peavey exclusive Sheffield Pro 1500+ woofer with 2.5" voice coil
- 1.4" 14XT™ titanium diaphragm compression driver
- Sound Guard IV tweeter protection
- 500 Watt program/1000 Watt peak power handling
- Heavy duty crossover network for driver protection and EQ
- Lightweight trapezoidal enclosure
- 90° x 40° coverage constant directivity horn for better off-axis tonality
- High quality, heavy duty carpet covering
- Steel handle
- Rugged dado and rabbet construction for lightweight-yet-strong joints
- T-Nut speaker mounting
- Heavy duty, full-length steel grille
- SA-1 die-cast aluminum pole mount

Frequency range (-10 dB, half space):

58 Hz to 21 kHz

Frequency response (±3 dB, half space):

79 Hz to 17 kHz

Sensitivity (1W/1M):

98 dB

Power rating (program):

500 Watts

Power capacity (peak):

1000 Watts

Maximum SPL:

127 dB

Transducer complement:

Sheffield® Pro 1500+™ 15" premium woofer and 14XT™ 1.4" titanium diaphragm dynamic compression driver on a 90 x 40° coverage constant directivity horn

Driver protection:

Sound Guard™ IV for the compression driver provides long- and medium-term overload and overdrive protection

Nominal coverage pattern:

90° x 40°

Electro-acoustic crossover frequency:

2.8 kHz

Nominal impedance:

8 Ohms

Input connections:

Two 1/4" phone jacks in parallel

Enclosure materials and finish:

Trapezoidal, black carpet-covered enclosure with dado joined 1/2" MDF (Medium Density Fiberboard), and a full-length, black powder-coated steel grille



SPECIFICATIONS TLM™ 5X

Description

The TLM 5X is a two-way floor monitor utilizing a Pro 1500+ woofer and a 14XT titanium diaphragm dynamic compression driver mounted on a 90° x 40° coverage constant-directivity horn. The lightweight, yet rugged, carpet-covered monitor enclosure with stand-mount cup facilitates portable use as a stage monitor or in other sound reinforcement applications. The dual-angle enclosure provides a choice of 30°

and 45° monitoring angles for full monitoring utility. A full-length, black powder-coated steel grille provides driver protection and a professional appearance.

The TLM 5X speaker system is rated at 500 Watts program power handling, and the full crossover network includes high voltage film capacitors and Sound Guard™ IV tweeter protection for clear, punchy sound and excellent long-term reliability. Two 1/4" phone

jack input connectors make hook-up and daisy-chaining to other monitors a breeze.

3 + 2 YEAR LIMITED WARRANTY

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898.

Amplitude Response (1W 1m On-Axis)




Figure 1



80305061

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 711 A Street • Meridian • MS • 39301 (601) 483-5365 • FAX (601) 486-1278 • www.peavey.com

©2003 Printed in the U.S.A. 2/03



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>