

PEAVEY[®]
ARCHITECTURAL ACOUSTICS[®]

RTD™ 215

Stereo 2/3 Octave Equalization System

SPECIFICATIONS

SPECIFICATIONS:

All specifications are typical unless otherwise noted.

0 dBV = 1 volt

All specifications are referenced to nominal output level (0 dBV) unless otherwise noted.

All measurements are wideband 20 Hz to 20 kHz unless otherwise stated.

NOTE: All specs measured at 1V RMS input and unbalanced output. All sliders at mid position, all switches out unless otherwise noted.

FREQUENCY RESPONSE (Balanced and Unbalanced outputs)

±1 dB 20 Hz - 20 kHz

DISTORTION

.003% 20 Hz - 20 kHz

COMMON MODE REJECTION RATIO (CMRR)

36 dB typical

INPUT IMPEDANCE

Unbalanced: 20K ohms

Balanced: 20K ohms (Equal impedances to ground)

OUTPUT IMPEDANCE

Unbalanced: 100 ohms

Balanced: 160 ohms

MAXIMUM INPUT LEVEL

Unbalanced: +24 dBV (15.8V RMS)

Balanced: +24 dBV (15.8V RMS)

MAXIMUM OUTPUT LEVEL

Unbalanced: 18 dBV (8V RMS)

Balanced: 24 dBV (15.8V RMS)

NOMINAL INPUT LEVEL

Unbalanced: 0 dBV (1V RMS)

Balanced: 0 dBV (1V RMS)

NOMINAL OUTPUT LEVEL

Unbalanced: 0 dBV (1V RMS)

Balanced: +6 dBV (2V RMS)

INPUT HEADROOM

Nominal = 24 dB

OUTPUT HEADROOM

Unbalanced: 18 dB

Balanced: 18 dB

OUTPUT NOISE: UNBALANCED OUTPUT

EQ Out: -98 dBV

EQ In, all Flat: -96.5 dBV

FILTER BANDWIDTH

2/3 octave

FILTER FREQUENCIES

25, 40, 63, 100, 160, 250, 400, 630, 1K, 1.6K, 2.5K, 4K, 6.3K, 10K, and 16 kHz

FILTER Q

2.36

MAXIMUM BOOST & CUT FILTERS

±12 dB (±12 dB position)

±6 dB (±6 dB position)

MAXIMUM BOOST & CUT GAIN (Wideband gain)

±12 dB (±12 dB position)

±12 dB (±6 dB position)

HIGH CUT FILTER:

(12 dB per octave frequency)

Out: 30 kHz

In: 16 kHz

LOW CUT FILTER:

(12 dB per octave)

Out: 12 Hz

In: 40 Hz

FEATURES:

- Two 2/3 octave, 15-band equalizers (ISO standard centers)
- Switch selectable ±6 and ±12 dB ranges
- Broadband level controls
- Switch selectable low and high cut filters
- EQ Bypass functions
- Balanced inputs and transformer balanced outputs (1/4" phone jacks also provided)
- Quiet power-up and power-down modes
- +24 dBV input and output capability (headroom)
- 1 3/4" single rack space package

DESCRIPTION:

The Peavey Architectural Acoustics RTD™ 215 is a unique and extremely flexible two channel equalization system. Each channel offers 15 bands of EQ on 2/3 octave center frequencies at 25, 40, 63, 100, 160, 250, 400, 630, 1K, 1.6K, 2.5K, 4K, 6.3K, 10K, and 16 kHz, with selectable range for ±12 dB

or ± 6 dB boost or cut. This allows a range of spectral control usually not available in two channel, stereo graphic equalizers. A broadband level control is also provided with a range of ± 12 dB, as well as switch selectable low and high cut filters at 40 Hz and 16 kHz.

Balanced and unbalanced inputs and outputs are "standard equipment" and the excellent dynamic range and high signal-to-noise ratio prove that the RTD 215 is truly professional in design and application.

ARCHITECTURAL AND ENGINEERING SPECIFICATIONS

The active equalizer shall be a dual channel, fifteen band, rack-mountable unit with two-third octave filters placed on standard ISO centers. The unit shall have two high impedance $\frac{1}{4}$ " unbalanced inputs, one low impedance XLR balanced input, two low impedance $\frac{1}{4}$ " unbalanced outputs, and one low impedance XLR balanced output for each channel. Equalization func-

tions for each channel shall provide ± 12 dB @ 25, 40, 63, 100, 160, 250, 400, 630, 1K, 1.6K, 2.5K, 4K, 6.3K, 10K, and 16K Hertz. Front panel controls for each channel shall include a broad-band gain control with ± 12 dB of range to help restore the unity gain function resulting from equalization loss (or gain); an EQ bypass switch for unity gain reference measurements; a range switch to select either ± 6 or ± 12 dB of equalization range; a low cut filter switch providing low frequency roll off at 40 Hz at 12 dB per octave; and a high cut filter switch providing high frequency roll off at 16 kHz at 12 dB per octave. Finally, the front panel shall have a mains power switch with an associated power LED.

Each channel shall be capable of delivering +24 dBV (16V RMS) at the balanced output and +18 dBV (8V RMS) at the unbalanced outputs. Further, each channel shall be capable of accepting +24 dBV (16V RMS) at both the balanced and unbalanced in-

puts. The frequency response of each channel shall be ± 1 dB from 20 Hz to 20 kHz and the total harmonic distortion of each channel shall be less than .003% from 20 Hz to 20 kHz, both of these specs being measured at 0 dBV (1V RMS) using either balanced or unbalanced inputs or outputs. Hum and noise for each channel shall be less than -96 dB below 0 dBV from 20 Hz to 20 kHz unweighted. The unit will be packaged in a rugged metal chassis 19" wide by 1 $\frac{3}{4}$ " high by 10" deep, and shall operate on 120V AC, 50/60 Hz, and consume 15 watts. The published specifications shall be met or exceeded. The active equalizer shall be called a Peavey Architectural Acoustics RTD™ 215.


LIMITED WARRANTY

Peavey Electronics Corporation warrants to the original purchaser of this new Architectural Acoustics product that it is free from defects in material and workmanship. If within one (1) year from date of purchase a properly installed product proves to be defective and Peavey is notified, Peavey will repair or replace it at no charge. (Note: Batteries and patch cords not covered.) "Original purchaser" means the customer for whom the product is originally installed.

Damage resulting from improper installation, interconnection of a unit or system of another manufacturer, accident or unreasonable use, neglect or any other cause not arising from defect in material and workmanship is not covered by this warranty. The warranty is valid only as to products purchased and installed in the United States.

THIS LIMITED WARRANTY IS IN LIEU OF ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. UNDER NO CIRCUMSTANCES WILL PEAVEY BE LIABLE FOR ANY LOST PROFITS, LOST SAVINGS, INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, EVE IF PEAVEY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. THIS LIMITED WARRANTY IS THE ONLY EXPRESS WARRANTY ON THIS PRODUCT, AND NO OTHER STATEMENT, REPRESENTATION, WARRANTY OR AGREEMENT BY ANY PERSON SHALL BE VALID OR BINDING UPON PEAVEY.

Peavey's liability to the original purchaser for damages for any cause whatsoever and regardless of the form of action, is limited to the actual damages up to the greater of Five Hundred Dollars (\$500) or an amount equal to the purchase price of the product that caused the damage or that is the subject of or is directly related to the cause of action. This limitation of liability will not apply to claims for personal injury or damage to real property or tangible personal property allegedly caused by Peavey's negligence. For information on service under this warranty, call a Peavey customer service representative at (601) 483-5376.



PEAVEY
ARCHITECTURAL ACOUSTICS®

Features and specifications subject to change without notice.

A Division of Peavey Electronics Corporation

711 A Street / Meridian, MS 39301 / U.S.A. / (601) 483-5376 / Fax 486-1278
#80301337

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>