



Compact Fluorescent
Energy Saver Reflector
Floods and Dimmable
Reflector Floods

*Ideal for indoor recessed
and track lighting and
outdoor fixtures*

ENERGY SAVER



Energy saver floods

Philips Compact Fluorescent Energy Saving Reflector and Dimmable Reflector Floods provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

Direct replacement for incandescent bulbs

- Provides warm and inviting soft white light
- Fits into incandescent fixtures
- Dimmable reflector—dims down to 10%

Long life

- Lasts 7 years*

Energy savings

- Saves up to \$49 over the life of the lamp when you replace an 85W PAR38 incandescent reflector with a 23W energy saver PAR38 reflector.**

* Based on an average daily usage of 3 hours per day, 7 days per week.

** Energy savings based on wattage saved x replacement lamp rated average life (8000 hours) ÷ 1000 x \$0.10 kWh rate.

PHILIPS
sense and simplicity

Compact Fluorescent Energy Saver Reflector Floods & Dimmable Reflector Floods

Ordering, Electrical and Technical Data

Product Number	Description	Volts	Nom. Watts	Approx. Incand. Equiv.	Base	Color Temp. (Kelvin)	CRI	Approx. Initial Lumens ¹	MOL (In.)	Diam. (In.)	Rated Avg. Life (Hrs.) ²	Min. Starting Temp.	Max. Ambient Temp.
◆ 15701-6	Reflector Flood EL/A R20	120	14	50R20	Med.	2700	82	500	4 3/8	2.5	8000	-4°F/-20°C	122°F/50°C
◆ 15703-2	Reflector Flood EL/A R30	120	15	65BR30	Med.	2700	82	750	5 3/4	3.7	8000	-4°F/-20°C	122°F/50°C
◆ 13707-5	Reflector Flood EL/A R30 Dimmable	120	16	65BR30	Med.	2700	82	630	5 13/32	3.7	8000	-4°F/-20°C	122°F/50°C
◆ 15702-4	Reflector Flood EL/A R40	120	23	85BR40	Med.	2700	82	1250	6 1/2	4.7	8000	-4°F/-20°C	122°F/50°C
◆ 13708-3	Reflector Flood EL/A R40 Dimmable	120	20	85BR40	Med.	2700	82	900	6 3/32	4.7	8000	-4°F/-20°C	122°F/50°C
◆ 15715-6	Reflector Flood EL/A PAR38	120	23	85PAR38	Med.	2700	82	1250	6 1/2	4.7	8000	-4°F/-20°C	122°F/50°C
◆ 14644-9	Reflector Flood EL/A PAR38 Dimmable	120	20	75PAR38	Med.	2700	82	850	6 3/32	4.7	8000	-4°F/-20°C	122°F/50°C
◆ 15716-4	Reflector Flood EL/A PAR38 Outdoor	120	23	85PAR38	Med.	2700	82	1300	4 1/2	4.7	8000	-4°F/-20°C	122°F/50°C

Shipping Data

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H)(In.)	Case Dimensions (W x D x H)(In.)	Pallet Dimensions (W x D x H)(In.)
15701-6	15701-2	15701-7	6	6.0	0.178	1554	222	7	2.6 x 2.6 x 5.4	5.9 x 8.5 x 6.1	40.0 x 46.9 x 43.0
15703-2	15703-6	15703-1	6	1.95	0.487	450	90	5	4.2 x 4.2 x 5.9	9.0 x 13.3 x 7.1	39.8 x 45.0 x 35.3
13707-5	13707-6	13707-1	6	1.5	0.400	840	120	7	3.8 x 3.8 x 6.2	8.1 x 12.1 x 7.0	40.3 x 48.5 x 49.0
15702-4	15702-9	15702-4	6	2.60	0.889	216	54	4	5.4 x 5.4 x 7.0	11.4 x 16.8 x 8.1	39.5 x 44.9 x 32.2
13708-3	13708-3	13708-8	6	2.14	0.551	546	78	7	4.8 x 4.8 x 6.0	9.9 x 14.7 x 6.6	39.3 x 49.8 x 45.9
15715-6	15715-9	15715-4	6	3.20	0.889	216	54	4	5.4 x 5.4 x 7.0	11.4 x 16.8 x 8.1	39.5 x 44.9 x 32.2
14644-9	14644-3	14644-8	6	2.52	0.551	504	72	7	4.8 x 4.8 x 6.0	9.9 x 14.7 x 6.6	39.5 x 44.1 x 45.9
15716-4	15716-6	15716-1	6	3.20	0.560	432	72	6	4.5 x 4.5 x 5.9	9.9 x 14.6 x 6.7	39.8 x 43.7 x 40.1

- 1) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.
 2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

- ◆ Amalgam Technology provides stable light output from -4°F to 122°F.
 - ◆ ENERGY STAR® Bulb: As an ENERGY STAR® Partner, Philips has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.
 - ◆ Do not use with dimmers.
- Above specifications subject to change without notice.

WARNINGS & CAUTIONS: Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Reliable operating temperature range -4F/-20C to 122F/50C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan
Decorative Twister	●		●					●		
Universal	●	●	●	●	●	●	●	●		
3-Way	●									
Reflector Flood							●	●		
Dimmable Reflector Flood							●	●		
Candle		●	●		●					●
Vanity & Decor Globe								●	●	●
Soft White Plus	●	●	●		●	●		●		●
Outdoor		●				●				
Bug-A-Way		●								
Circline	●									
Genie	●	●	●	●	●	●	●	●	●	●



© 2008 Philips Lighting Company. All rights reserved.
 Printed in USA 1/08
 P-8516-C
www.philips.com

Philips Lighting Company
 200 Franklin Square Drive
 P.O. Box 6800
 Somerset, NJ 08875-6800
 1-800-555-0050
 A Division of Philips Electronics North America Corporation

Philips Lighting
 281 Hillmount Road
 Markham, Ontario
 Canada L6C 2S3
 1-800-555-0050
 A Division of Philips Electronics Ltd.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>