

Philips
Stereo Y cable

3.0 m

3.5 mm (F) - 2 RCA (M)

SWA2511



Ensure a reliable connection

with this stereo "Y" cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality

- Nickel-plated connectors for reliable contact

Protects against signal loss

- Bare copper shielding

Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

Environmentally friendly

- Environmentally friendly lead-free construction

PHILIPS
sense and simplicity

Stereo Y cable
3.0 m 3.5 mm (F) - 2 RCA (M)

Specifications

Inner Carton

- EAN/UPC/GTIN: 87 10895 97427 1
- Quantity: 6
- Gross weight: 0.74 kg
- Tare weight: 0.20 kg
- Net weight: 0.54 kg
- Length (cm): 20.3 cm
- Width (cm): 16.5 cm
- Height (cm): 13.5 cm

Outer Carton

- EAN/UPC/GTIN: 87 10895 97428 8
- Quantity: 12
- Gross weight: 1.88 kg
- Tare weight: 0.40 kg

- Net weight: 1.84 kg
- Length (cm): 21.0 cm
- Width (cm): 17.0 cm
- Height (cm): 20.5 cm

Packaging

- EAN/UPC/GTIN: 87 10895 95248 4
- Quantity: 1
- Gross Weight: 0.09 kg
- Tare Weight: 0.02 kg
- Net Weight: 0.07 kg
- Height: 1.6 cm
- Length: 7.9 cm
- Width: 3.8 cm

SWA25 I I/93

Product highlights

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Bare copper shielding

Bare copper shielding protects against signal loss.

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Lead-free construction

Lead-free construction of environmentally friendly materials.



Issue date 2007-12-07

Version: 2.0.5

12 NC: 9082 100 07501
EAN: 87 10895 95248 4

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>