

Philips Silicone Coated Lamps

Silicone Coating; ideal for standard, industrial rough surface, appliance and sign use



- ▶ **Special Silicone Coating**

Resists breakage

- ▶ **Absorbs Impact**

- ▶ **Resists Breakage**

Or shattering if bulb is hit or dropped

- ▶ **Resists Moisture**

- ▶ **Repels Machine Splatter**

Without breakage caused by thermal shock

Ideal for factory lighting, new construction, food serving areas, refrigerators, garden fountains and drop cords



PHILIPS

Philips Lighting Company
200 Franklin Square Drive
P.O. Box 6800
Somerset, NJ 08875-6800
1-800-555-0050

www.philips.com

Philips Lighting
281 Hillmount Road
Markham, Ontario
Canada L6C 2S3
1-800-555-0050
A Division of Philips Electronics Ltd.

A Division of Philips Electronics North America Corporation
Printed in USA 7/05 P-2544-C

Philips Silicone Coated Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Ordering Code	Watts	Volts	Pkg. Qty.	Description	Bulb Type	Base	Rated Avg. Life (Hrs.) ¹⁾	MOL (In.)	Class, Filament
General Lighting										
30031-9	25A/TF	25	120	120	Frost Silicone Coated	A-19	Medium	2500	3 ¹ / ₆	B, C-9
30033-5	40A/TF	40	120	120	Frost Silicone Coated	A-19	Medium	1500	4 ¹ / ₆	C, CC-6
30038-4	60A/TF	60	120	120	Frost Silicone Coated	A-19	Medium	1000	4 ¹ / ₆	C, CC-6
30051-7	100A21/TF	100	120	120	Frost Silicone Coated	A-21	Medium	750	5 ¹ / ₆	C, CC-8
30056-6	150PS25/TF	150	120	60	Frost Silicone Coated	PS-25	Medium	1000	6 ¹ / ₆	C, C-9
14298-3	200/TF	200	120	60	Frost Silicone Coated	PS-30	Medium	750	8 ¹ / ₆	C, C-9
Industrial Service Lamps										
25836-8*	60A/35/TF	60	120	60	Frost Silicone Coated Industrial Service	A-19	Medium	3500	4 ¹ / ₆	C, C-9
25838-4†	100A21/35/TF	100	120	60	Frost Silicone Coated Industrial Service	A-21	Medium	3500	5 ¹ / ₆	C, C-9
22965-8†	150A/25/35/TF	150	120	60	Frost Silicone Coated Industrial Service	A-25	Medium	3500	6 ¹ / ₆	C, C-9
14300-8†	200/35/TF	200	120	60	Frost Silicone Coated Industrial Service	PS-30	Medium	3500	8 ¹ / ₆	C, C-9
Rough Service Lamps										
30034-3	50A/RS/TF	50	120	120	Frost Rough Service Silicone Coated	A-19	Medium	1000	3 ¹ / ₆	B, RC-9
20922-1	75A/RH/TF 21/1	75	120	12	Frost Silicone Coated Tough Bulb	A-21	Medium	1000	5 ¹ / ₆	C, RC-9
14305-7	200PS30/RS/TF	200	120	60	Frost Rough Service Silicone Coated	PS-30	Medium	1000	8 ¹ / ₆	C, C-9
Appliance Lamps										
25109-0	40A15/TF	40	120	120	Refrigerator	A-15	Medium	1000	3 ¹ / ₂	C, C-9
Reflector Sign Lamp										
22601-9	30R20/SFL/TF	30	130	120	Reflector Sign	R-20	Medium	6000	3 ¹ / ₆	C, C-9

1) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

* Silicone Coating reduces lumen output from Standard Values from 3%–5% for all types.

† Operate base up.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>