

Compact Fluorescent **Energy Saver** Twister GU24

Ideal for table and floor lamps, ceiling fans and reading lamps

**ENERGY SAVER** 

# Energy saver GU24 twister

Philips compact fluorescent energy saving GU24 twisters feature a twist and lock connection with 2 pins for energy efficient replacement.

## Easy retrofit for GU24 fixtures or luminaires

- Simple twist and lock design to allow quick and easy replacement
- Instant on
- Compact size fits most GU24 fixtures
- Meets California's Energy Efficiency Standards for Residential and Nonresidential Buildings (24 CCR 6)

## Long life

Lasts 9 years\*

#### **Energy saving**

• Saves up to \$77 over the life of the lamp when you replace a 100W A19 incandescent lamp with a 23W Energy Saver Twister GU24\*\*



<sup>\*</sup> Based on an average daily usage of 3–4 hours per day, 7 days per week.

\*\* Based on wattage saved (77W) x replacement lamp rated average life (10,000 hours) divided by 1000 x kWh rate (10) = \$77 saved.

# Philips Compact Fluorescent Energy Saver GU24 Twister

# **Ordering, Electrical and Technical Data**

Product Number	Description	Nom. Watts	Color Temp. (K)	CRI	Approx. Initial Lumens <sup>i</sup>	MOL (In.)	Rated Avg. Life (Hrs.)²
22285-I	EL/mdT 13W GU24	13	2700	82	900	3%	10,000
22286-9	EL/mdT 18W GU24	18	2700	82	1200	31/5	10,000
22287-7	EL/mdT 23W GU24	23	2700	82	1600	<b>4</b> <sup>2</sup> /s	10,000

# **Shipping Data**

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)		Pallet Qty.	SKUs Per Layer	Layers High		Case Dimensions (W x D x H)(In.)	Pallet Dimensions (W x D x H)(ln.)
22285-I	22285-7	22285-2	6	1.9	0.084	2832	354	8	$2.1 \times 2.1 \times 4.2$	4.5 x 6.6 x 4.9	38.1 x 46.4 x 39.9
22286-9	22286-4	22286-9	6	2.5	0.133	1872	234	8	$2.5 \times 2.5 \times 4.5$	$5.5 \times 8.1 \times 5.1$	38.5 x 46.1 x 41.0
22287-7	22287-I	22287-6	6	2.8	0.159	1428	204	7	$2.7 \times 2.7 \times 4.9$	$5.8 \times 8.5 \times 5.6$	$37.0 \times 46.0 \times 39.4$

<sup>1)</sup> Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.

Above specifications are subject to change without notice.

WARNINGS & CAUTIONS: Do not use with dimmers. Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Reliable operating temperature range Reliable operating temperature range -20°F/-29°C to 185°F/85°C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

	<b>A</b>	Î	Q <sub>f</sub>			<b>P</b>			2000	
Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan
Decorative Twister	•		•		•			•		
Universal	•	•	•	•	•	•	•	•		
3-Way	•									
Reflector Flood							•	•		
Dimmable Reflector Flood							•	•		
Candle		•	•		•					•
Vanity & Decor Globe								•	•	•
Soft White Plus	•	•	•		•	•		•		•
Outdoor		•				•				
Bug-A-Way		•								
Circline	•									
Genie	•	•	•	•	•	•	•	•	•	•
GU24 Twister										



 $\@$  2008 Philips Lighting Company. All rights reserved. Printed in USA 6/08

P-5957

www. philips.com

Philips Lighting Company 200 Franklin Square Drive P.O. Box 6800 Somerset, NJ 08875-6800 I-800-555-0050

A Division of Philips Electronics North America Corporation

Philips Lighting
281 Hillmount Road
Markham, Ontario
Canada L6C 2S3
1-800-555-0050
A Division of Philips Electronics Ltd.

<sup>2)</sup> Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com