

Compact Fluorescent  
Energy Saver  
Decorative Twisters

*Ideal for general  
household use*

ENERGY SAVER



## Energy saver twisters

Philips Compact Fluorescent Energy Saving Decorative Twisters provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

### Direct replacement for incandescent bulbs

- Instant on
- Fits into incandescent fixtures
- Compact size fits many small fixtures
- Provides warm and inviting soft white light

### Available in a variety of color temperatures

### Long life

- Lasts at least 5 years\*

### Energy savings

- Saves up to \$86 over the life of the lamp when you replace a 150W A21 incandescent lamp with a 42W energy saving decorative twister\*\*

\* Based on an average daily usage of 3–4 hours per day, 7 days per week.

\*\* Energy savings based on wattage saved x replacement lamp rated average life (8000 hours) ÷ 1000 x \$0.10 kWh rate.

**PHILIPS**  
sense and simplicity

# Compact Fluorescent Energy Saver Decorative Twisters

## Ordering, Electrical and Technical Data

| Product Number | Description                 | Volts | Nom. Watts | Approx. Incand. Equiv. | Base | Color Temp. (Kelvin) | CRI | Approx. Initial Lumens <sup>1</sup> | MOL (In.) | Diam. (In.) | Rated Avg. Life (Hrs.) <sup>2</sup> | Min. Starting Temp. | Max. Ambient Temp. |
|----------------|-----------------------------|-------|------------|------------------------|------|----------------------|-----|-------------------------------------|-----------|-------------|-------------------------------------|---------------------|--------------------|
| 14792-6        | Dec Twister EL/mdT 5        | 120   | 5          | 25 A19                 | Med. | 2700                 | 82  | 250                                 | 4         | 1.75        | 8000                                | -4°F/-20°C          | 122°F/50°C         |
| 14793-4        | Dec Twister EL/mdT 9        | 120   | 9          | 40 A19                 | Med. | 2700                 | 82  | 550                                 | 4 ¼       | 1.75        | 8000                                | -4°F/-20°C          | 122°F/50°C         |
| 13804-0        | Dec Twister EL/mdT 11       | 120   | 11         | 40 A19                 | Med. | 2700                 | 82  | 675                                 | 4 ⅝       | 1.75        | 8000                                | -4°F/-20°C          | 122°F/50°C         |
| 15638-0        | Dec Twister EL/mdT 13       | 120   | 13         | 60 A19                 | Med. | 2700                 | 82  | 900                                 | 4         | 2.0         | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 14786-8        | Dec Twister EL/mdT 13 4100K | 120   | 13         | 60 A19                 | Med. | 4100                 | 82  | 900                                 | 4 ¼       | 1.75        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 14787-6        | Dec Twister EL/mdT 13 5000K | 120   | 13         | 60 A19                 | Med. | 5000                 | 82  | 900                                 | 4 ¼       | 1.75        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 20286-1        | Dec Twister EL/mdT 18       | 120   | 18         | 75 A19                 | Med. | 2700                 | 82  | 1250                                | 5 ½       | 1.89        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 15697-5        | Dec Twister EL/mdT 23       | 120   | 23         | 100 A19                | Med. | 2700                 | 82  | 1600                                | 5         | 1.89        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 13715-8        | Dec Twister EL/mdT 27       | 120   | 27         | 100 A19                | Med. | 2700                 | 82  | 1750                                | 5 ⅝       | 2.05        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 14788-4        | Dec Twister EL/mdT 27 4100K | 120   | 27         | 100 A19                | Med. | 4100                 | 82  | 1850                                | 5 ¾       | 2.05        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 14789-2        | Dec Twister EL/mdT 27 5000K | 120   | 27         | 100 A19                | Med. | 5000                 | 82  | 1850                                | 5 ¾       | 2.05        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 15639-8        | Dec Twister EL/mdT 32       | 120   | 32         | 150 A19                | Med. | 2700                 | 82  | 2200                                | 5 ½       | 2.05        | 10,000                              | -4°F/-20°C          | 122°F/50°C         |
| 13948-5        | Dec Twister EL/dT 42        | 120   | 42         | 150 A21                | Med. | 2700                 | 82  | 2600                                | 7 ½       | 2.52        | 8000                                | -4°F/-20°C          | 122°F/50°C         |

## Shipping Data

| Product Number | SKU UPC (0-46677) | Outer Bar Code (5-00-46677) | Case Qty. | Case Weight (lbs.) | Case Cube (cu. ft.) | Pallet Qty. | SKUs Per Layer | Layers High | SKU Dimensions (W x D x H)(In.) | Case Dimensions (W x D x H)(In.) | Pallet Dimensions (W x D x H)(In.) |
|----------------|-------------------|-----------------------------|-----------|--------------------|---------------------|-------------|----------------|-------------|---------------------------------|----------------------------------|------------------------------------|
| 14792-6        | 14792-1           | 14792-6                     | 6         | 1.72               | 0.083               | 2646        | 378            | 7           | 2.0 x 2.0 x 4.4                 | 4.4 x 6.4 x 5.1                  | 39.4 x 45.1 x 35.4                 |
| 14793-4        | 14793-8           | 14793-3                     | 6         | 1.82               | 0.087               | 2646        | 378            | 7           | 2.0 x 2.0 x 4.6                 | 4.3 x 6.4 x 5.3                  | 39.4 x 45.1 x 37.2                 |
| 13804-0        | 13804-2           | 13804-7                     | 6         | 0.82               | 0.109               | 2088        | 348            | 6           | 2.0 x 2.0 x 5.0                 | 4.6 x 6.7 x 6.1                  | 38.4 x 46.6 x 42.8                 |
| 15638-0        | 15638-1           | 15638-6                     | 6         | 1.70               | 0.152               | 1152        | 192            | 6           | 2.6 x 2.6 x 5.2                 | 5.4 x 8.3 x 5.9                  | 33.3 x 46.5 x 35.3                 |
| 14786-8        | 14786-0           | 14786-5                     | 6         | 2.14               | 0.161               | 1404        | 234            | 6           | 2.6 x 2.6 x 5.2                 | 5.7 x 8.3 x 5.9                  | 39.8 x 47.2 x 35.3                 |
| 14787-6        | 14787-7           | 14787-2                     | 6         | 2.14               | 0.161               | 1404        | 234            | 6           | 2.3 x 2.3 x 5.8                 | 5.7 x 8.3 x 5.9                  | 39.8 x 47.2 x 35.3                 |
| 20286-1        | 20286-6           | 20286-1                     | 6         | 6.0                | 0.153               | 1620        | 270            | 6           | 2.6 x 2.6 x 5.8                 | 5.1 x 7.5 x 6.9                  | 37.5 x 46.1 x 41.1                 |
| 15697-5        | 15697-8           | 15697-3                     | 6         | 6.0                | 0.179               | 1332        | 222            | 6           | 2.6 x 2.6 x 6.1                 | 5.7 x 8.4 x 6.5                  | 39.2 x 46.5 x 39.0                 |
| 13715-8        | 13715-1           | 13715-6                     | 6         | 1.39               | 0.209               | 1020        | 204            | 5           | 2.6 x 2.6 x 6.1                 | 5.9 x 8.5 x 7.2                  | 39.4 x 47.2 x 41.7                 |
| 14788-4        | 14788-4           | 14788-9                     | 6         | 2.38               | 0.188               | 1170        | 234            | 5           | 2.6 x 2.6 x 6.1                 | 5.7 x 8.3 x 6.9                  | 39.8 x 47.2 x 34.4                 |
| 14789-2        | 14789-1           | 14789-6                     | 6         | 2.39               | 0.188               | 1170        | 234            | 5           | 2.6 x 2.6 x 6.1                 | 5.7 x 8.3 x 6.9                  | 39.8 x 47.2 x 34.4                 |
| 15639-8        | 15639-8           | 15639-3                     | 6         | 1.64               | 0.260               | 900         | 180            | 5           | 3.0 x 3.0 x 6.2                 | 6.4 x 9.4 x 7.5                  | 38.3 x 47.0 x 37.5                 |
| 13948-5        | 13948-3           | 13948-8                     | 6         | 2.70               | 0.303               | 1080        | 180            | 6           | 3.1 x 3.1 x 7.6                 | 6.7 x 9.9 x 7.9                  | 40.1 x 49.4 x 47.6                 |

- 1) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.  
 2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

■ ENERGY STAR® Bulb: As an ENERGY STAR® Partner, Philips has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.

Above specifications are subject to change without notice.

**WARNINGS & CAUTIONS:** Do not use with dimmers. Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Reliable operating temperature range -4F/-20C to 122F/50C.

**Note:** This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

| Bulb Type                | Table/Floor Lamp | Outdoor Postlight | Wall Sconce | Surface Mount | Reading Lamp | Border Lights | Recessed Fixture | Open Hanging | Vanity Strip | Ceiling Fan |
|--------------------------|------------------|-------------------|-------------|---------------|--------------|---------------|------------------|--------------|--------------|-------------|
| Decorative Twister       | ●                |                   | ●           |               | ●            |               |                  | ●            |              |             |
| Universal                | ●                | ●                 | ●           | ●             | ●            | ●             | ●                | ●            |              |             |
| 3-Way                    | ●                |                   |             |               |              |               |                  |              |              |             |
| Reflector Flood          |                  |                   |             |               |              |               | ●                | ●            |              |             |
| Dimmable Reflector Flood |                  |                   |             |               |              |               | ●                | ●            |              |             |
| Candle                   |                  | ●                 | ●           |               | ●            |               |                  |              |              | ●           |
| Vanity & Decor Globe     |                  |                   |             |               |              |               |                  | ●            | ●            | ●           |
| Soft White Plus          | ●                | ●                 | ●           |               | ●            | ●             |                  | ●            |              | ●           |
| Outdoor                  |                  | ●                 |             |               |              | ●             |                  |              |              |             |
| Bug-A-Way                |                  | ●                 |             |               |              |               |                  |              |              |             |
| Circline                 | ●                |                   |             |               |              |               |                  |              |              |             |
| Genie                    | ●                | ●                 | ●           | ●             | ●            | ●             | ●                | ●            | ●            | ●           |



© 2008 Philips Lighting Company. All rights reserved.  
 Printed in USA 1/08  
 P-8514-D  
 www.philips.com

Philips Lighting Company  
 200 Franklin Square Drive  
 P.O. Box 6800  
 Somerset, NJ 08875-6800  
 1-800-555-0050  
 A Division of Philips Electronics North America Corporation

Philips Lighting  
 281 Hillmount Road  
 Markham, Ontario  
 Canada L6C 2S3  
 1-800-555-0050  
 A Division of Philips Electronics Ltd.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>