



PIONEER NEW MEDIA TECHNOLOGIES, INC.

DRM-1004X40 100-Disc CD-ROM/R Autochanger (Reader Model)

SPECIFICATIONS

GENERAL	
Number of Discs	Up to 100 CD-ROM discs (2 removable 50-disc magazines)
Configurations	1004X40: 4 read, 1004XR21: two read/ one write
Interface	SCSI-2
SCSI ID	Individually set for each drive and for jukebox robotics control.
Disc Exchange Time	Less than 6 seconds (even during writer operation)
Disc Load Time	Less than 3 seconds
Regulatory Approval	UL, CSA, TUV, CE, FCC, VCCI
RELIABILITY	
Change Mechanism (MSBF): Disc Change	1,000,000 times
Mail-Slot Open/Close	100,000 times
Reader Drive: MTBF	75,000 POH (Duty 20%)
Writer Drive: MTBF	50,000 POH (Duty 20%)
PHYSICAL CHARACTERISTICS	
Dimensions (W x H x D)	10-3/8" x 19-1/16" x 23-1/8" 263 x 484 x 588 mm
Weight (Net)	DRM-1004X40: 74 pounds 33.6 kg DRM-1004XR21: 73 pounds 33.1 kg
Operating Voltage	AC 100V/120V/230V
Power Consumption	DRM-1004X40: 73W (when using 4 readers) DRM-1004XR21: 64W (when using 2 readers/1 writer)
ENVIRONMENTAL CONDITIONALS	
Operating Temperature	41°F to 95°F degrees 5°C to 35°C degrees
Operating Humidity	5 to 85%RH
Storage Temperature	-40°F to 140°F degrees -40°F to 60°C degrees
Storage Humidity	10 to 90% RH

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>