



plasma Enhancer™ PRO

DCDi™

SDI and HDMI

HDTV

Pixel Magic
System™

Video Processor/Scaler PE1000 Pro

Plasma Enhancer® PE1000-Pro

Plasma Enhancer® is a video processor/scaler specially designed to enhance the video quality of Plasma TVs, LCD TVs, Projectors and RPTVs.



Plasma Enhancer® combines state-of-the-art digital video transmission, processing, scaling and format conversion technologies in a single box and delivers unprecedented high quality video in home theaters at an affordable price.

Technologies including Genesis Microchip's Emmy award winning DCDi™ and TrueLife® are employed to provide impressive de-interlaced processing and outstanding picture quality.

Plasma Enhancer® is equipped with the new Philips 5th generation high quality analog TV tuner MK5™. Boasting a best-in-class noise figure of less than 5dB throughout the frequency range, and with improved sensitivity, Plasma Enhancer® offers crystal clear analog TV reception quality.



Technical Specifications

Audio / Video Inputs

One antenna input for analog TV tuner; European (PAL & SECAM) or NTSC versions are available.

Serial Digital Interface (SDI) input x1 (Standard)

HDTV analog input for passthrough x1

HDMI (HDCP, video only) inputs x 2 for 480p/576p processing and HDTV passthrough

AV1: S-Video x1, Composite x1, Component (480i/p and 576i/p) x1, with stereo audio x1

AV2: SCART input x1 (configurable as S-Video, RGBS, Component or Composite) with stereo audio x1, aspect ratio auto-detection via pin 8

AV3 on front panel: S-Video x1, Composite x1, stereo audio x1

Audio / Video Outputs

Digital video: HDMI (HDCP, video only)

Analog video: RGBHV, RGBS or YPbPr (DB15 connector)

Stereo audio (Nicam stereo L/R audio for PAL tuner version)

Resolutions supported

480p, 540p, 576p, 720p, 1080i, 1080p, 640x480, 800x600, 848x480, 852x480, 854x480, 856x480, 1024x576, 1024x768, 1024x1024 ALiS, 1280x720, 1280x768, 1280x1024, 1360x768, 1360x1024, 1366x768, 1368x768, 1400x788, 1400x1050, 1920x1080;

User-customizable output resolutions.

User-friendly appliance

On screen display for easy system setup

Front panel lighting can be programmed off

Two different remote control units are included

Firmware upgradeable through USB port

Infrared output jack on back panel to connect to an external infrared transmitter

TV Commander™

Input Format: PAL and NTSC

Dimensions: 438 x 285 x 50 mm (17.3" x 11.2" x 1.97")

Power consumption: 20W

Weight: 3.5 Kg (7.7 lb)

Power Supply: 110/220VAC Auto-sensing

Specifications and features subject to change without notice



Website: www.pixelmagicsystems.com
Support forum: www.pixelmagicforum.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>